

**ISSN 2518-1467 (Online),
ISSN 1991-3494 (Print)**

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ФЫЛЫМ АКАДЕМИЯСЫНЫҢ

Х А Б А Р Ш Ы С Ы

ВЕСТНИК

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН

THE BULLETIN

THE NATIONAL ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN

PUBLISHED SINCE 1944

4

JULY – AUGUST 2020

ALMATY, NAS RK

NAS RK is pleased to announce that Bulletin of NAS RK scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of Bulletin of NAS RK in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential multidiscipline content to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабаршысы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруды. Web of Science зерттеушілер, авторлар, баспашилар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабаршысының Emerging Sources Citation Index-ке енүі біздің қоғамдастық үшін ең өзекті және беделді мультидисциплинарлы контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Вестник НАН РК» был принят для индексирования в Emerging Sources CitationIndex, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Вестника НАН РК в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному мультидисциплинарному контенту для нашего сообщества.

Бас редакторы

Х.Г.Д., проф., КР ҰҒА академигі
М.Ж. Жұрынов

Редакция алқасы:

Абиев Р.Ш. проф. (Ресей)
Абылқасымова А.Е. проф., академик (Қазақстан)
Аврамов К.В. проф. (Украина)
Аппель Юрген проф. (Германия)
Баймуқанов Д.А. проф., академик (Қазақстан)
Баймұратов Ү.Б. проф., академик (Қазақстан)
Байтанаев Б.А. проф., академик (Қазақстан)
Байтулин И.О. проф., академик (Қазақстан)
Банас Йозеф проф. (Польша)
Берсимбаев Р.И. проф., академик (Қазақстан)
Велесько С. проф. (Германия)
Велихов Е.П. проф., РҒА академигі (Ресей)
Кабульдинов З.Е. проф. (Қазақстан)
Қажыбек Е.З. проф., корр.-мүшесі (Қазақстан)
Қалимолдаев М.Н. проф., академик (Қазақстан), бас ред. орынбасары
Қамзабекұлы Д. проф., академик (Қазақстан)
Қойгелдиев М.К. проф., академик (Қазақстан)
Лупашку Ф. проф., корр.-мүшесі (Молдова)
Мохд Хасан Селамат проф. (Малайзия)
Новак Изабелла проф. (Польша)
Огарь Н.П. проф., корр.-мүшесі (Қазақстан)
Полещук О.Х. проф. (Ресей)
Поняев А.И. проф. (Ресей)
Сагиян А.С. проф., академик (Армения)
Таймагамбетов Ж.К. проф., академик (Қазақстан)
Хрипунов Г.С. проф. (Украина)
Шәукенова З.К. проф., корр.-мүшесі (Қазақстан)
Юлдашбаев Ю.А. проф., РҒА академигі (Ресей)
Якубова М.М. проф., академик (Тәжікстан)

«Қазақстан Республикасы Үлттық ғылым академиясының Хабаршысы».

**ISSN 2518-1467 (Online),
ISSN 1991-3494 (Print)**

Меншіктенуші: «Қазақстан Республикасының Үлттық ғылым академиясы»РКБ (Алматы қ.).

Қазақстан Республикасының Ақпарат және коммуникациялар министрлігінің Ақпарат комитетінде 12.02.2018 ж. берілген № 16895-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік.

Мерзімділігі: жылдан 6 рет.

Тиражы: 2000 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,
<http://www.bulletin-science.kz/index.php/en/>

© Қазақстан Республикасының Үлттық ғылым академиясы, 2020

Типографияның мекенжайы: «NurNaz GRACE», Алматы қ., Рысқұлов көш., 103.

Г л а в н ы й р е д а к т о р

д.х.н., проф. академик НАН РК

М.Ж. Журинов

Р е д а к ц и о н на я кол л е г и я:

Абиев Р.Ш. проф. (Россия)
Абылқасымова А.Е. проф., академик (Казахстан)
Аврамов К.В. проф. (Украина)
Аппель Юрген проф. (Германия)
Баймukanов Д.А. проф., академик (Казахстан)
Баймуратов У.Б. проф., академик (Казахстан)
Байтанаев Б.А. проф., академик (Казахстан)
Байтулин И.О. проф., академик (Казахстан)
Банас Иозеф проф. (Польша)
Берсимбаев Р.И. проф., академик (Казахстан)
Велесько С. проф. (Германия)
Велихов Е.П. проф., академик РАН (Россия)
Кабульдинов З.Е. проф. (Казахстан)
Кажыбек Е.З. проф., чл.-корр. (Казахстан)
Калимолдаев М.Н. академик (Казахстан), зам. гл. ред.
Камзабекулы Д. проф., академик (Казахстан)
Койгельдиев М.К. проф., академик (Казахстан)
Лупашку Ф. проф., чл.-корр. (Молдова)
Мохд Хасан Селамат проф. (Малайзия)
Новак Изабелла проф. (Польша)
Огарь Н.П. проф., чл.-корр. (Казахстан)
Полещук О.Х. проф. (Россия)
Поняев А.И. проф. (Россия)
Сагиян А.С. проф., академик (Армения)
Таймагамбетов Ж.К. проф., академик (Казахстан)
Хрипунов Г.С. проф. (Украина)
Шаукенова З.К. проф., чл.-корр. (Казахстан)
Юлдашбаев Ю.А. проф., академик РАН (Россия)
Якубова М.М. проф., академик (Таджикистан)

«Вестник Национальной академии наук Республики Казахстан».

ISSN 2518-1467 (Online),

ISSN 1991-3494 (Print)

Собственник: РОО «Национальная академия наук Республики Казахстан» (г. Алматы).

Свидетельство о постановке на учет периодического печатного издания в Комитете информации Министерства информации и коммуникаций Республики Казахстан № 16895-Ж, выданное 12.02.2018 г.

Периодичность: 6 раз в год.

Тираж: 2000 экземпляров.

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел. 272-13-19, 272-13-18.

<http://www.bulletin-science.kz/index.php/en/>

© Национальная академия наук Республики Казахстан, 2020

Адрес типографии: «NurNazGRACE», г. Алматы, ул. Рыскулова, 103.

E d i t o r i n c h i e f

doctor of chemistry, professor, academician of NAS RK

M.Zh. Zhurinov

E d i t o r i a l b o a r d:

Abiyev R.Sh. prof. (Russia)

Abylkasymova A.E. prof., academician (Kazakhstan)

Avramov K.V. prof. (Ukraine)

Appel Jurgen, prof. (Germany)

Baimukanov D.A. prof., academician (Kazakhstan)

Baimuratov U.B. prof., academician (Kazakhstan)

Baitanaev B.A. prof., academician (Kazakhstan)

Baitullin I.O. prof., academician (Kazakhstan)

Joseph Banas, prof. (Poland)

Bersimbayev R.I. prof., academician (Kazakhstan)

Velesco S., prof. (Germany)

Velikhov Ye.P. prof., academician of RAS (Russia)

Kabuldinov Z.E. prof. (Kazakhstan)

Kazhybek E.Z. prof., corr. member. (Kazakhstan)

Kalimoldayev M.N. prof., academician (Kazakhstan), deputy editor in chief

Kamzabekuly D. prof., academician (Kazakhstan)

Koigeldiev M.K. prof., academician (Kazakhstan)

Lupashku F. prof., corr. member (Moldova)

Mohd Hassan Selamat, prof. (Malaysia)

Nowak Isabella, prof. (Poland)

Ogar N.P. prof., corr. member (Kazakhstan)

Poleshchuk O.Kh. prof. (Russia)

Ponyaev A.I. prof. (Russia)

Sagyan A.S. prof., academician (Armenia)

Tajmagambetov Zh.K. prof., academician (Kazakhstan)

Khripunov G.S. prof. (Ukraine)

Shaukenova Z.K. prof., corr. member. (Kazakhstan)

Yuldasbayev Y.A., prof., academician of RAS (Russia)

Yakubova M.M. prof., academician (Tadzhikistan)

Bulletin of the National Academy of Sciences of the Republic of Kazakhstan.

ISSN 2518-1467 (Online),

ISSN 1991-3494 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty).

The certificate of registration of a periodical printed publication in the Committee of information of the Ministry of Information and Communications of the Republic of Kazakhstan No. 16895-Ж, issued on 12.02.2018.

Periodicity: 6 times a year.

Circulation: 2000 copies.

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,
<http://www.bulletin-science.kz/index.php/en/>

© National Academy of Sciences of the Republic of Kazakhstan, 2020

Address of printing house: «NurNaz GRACE», 103, Ryskulov str, Almaty.

**BULLETIN OF NATIONAL ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN**

ISSN 1991-3494

Volume 4, Number 386 (2020), 41 – 48

<https://doi.org/10.32014/2020.2518-1467.102>

UDC 66.047.45

MRNTI 64.29.15

**A. Ye. Khussanov¹, V. M. Atamanyuk³, B. M. Kaldybayeva¹,
A. Zh. Abilmagzhanov², D. Zh. Janabayev¹, Zh. Ye. Khussanov¹**

¹M. Auezov South Kazakhstan State University, Shymkent, Kazakhstan;

²D. V. Sokolsky Institute of Fuel, Catalysis and Electrochemistry, Almaty, Kazakhstan;

³Lviv Polytechnic National University, Lviv, Ukraine.

E-mail: kaldybaeva.b@mail.ru

**RESULTS OF EXPERIMENTAL RESEARCH
OF HYDRODYNAMICS OF A STATIONARY LAYER DURING
FILTRATION DRYING OF RAW COTTON**

Abstract. This article presents the results of experimental researches of the hydrodynamics of a stationary layer during filtration drying of raw cotton. At the same time, the total energy consumption for the process of filtration drying consists of pressure losses in the stationary layer and heating of the heat agent to a predetermined temperature. For this, it is important to establish the dependence of pressure losses in a stationary layer of wet cotton fiber on the fictitious filtration rate of the heat agent, as an important factor determining the intensity and economic efficiency of filtration drying. All experiments were carried out with appropriate hangings of cotton fiber, taking into account that the natural moisture content of cotton fiber is insignificant. Experimental studies have been conducted on filtering a thermal agent through a conditionally stationary layer of cotton fiber with different weights were performed in the form of a functional dependence $\Delta P = f(\nu_0)$. The results of comparing the ratio of experimentally determined values of pressure losses in a conditionally stationary layer of cotton fiber to those theoretically calculated as a function of the Reynolds number are presented. The absolute value of the relative error does not exceed 14.2%, which is explained by the complex structure and spontaneity of the formation of a stationary layer of cotton fiber, as well as the impact of the pressure drop on the height of the layer.

Key words: cotton fiber, hydrodynamics, filtration drying, hydraulic resistance, porosity, active specific surface area of the layer.

Introduction. It is known [1,2] that cotton is used for the production of cotton wool and various types of fabrics for industrial and household purposes, in particular chintzes, satin, batiste, cord for automobile tires and the like. Cotton fibers are widely used in new, non-traditional areas applications, such as reinforcing composites, geotextiles, personal absorption products and biomedical materials [3-7]. Therefore, the modernization of cotton processing and high-quality storage is extremely important for the development of the economy of Kazakhstan [8,9].

Currently in cotton processing plants when using drying drums of the type 2SB-10, SBT, SBU deteriorates the properties of raw materials. As a result of subsequent technological processes, the fiber grade is reduced by 25% through mechanical action, a lot of energy is spent, the color of the fiber is lost and there is also twisting of the fiber and the fiber microstructure deteriorates [10]. Drying drums used for drying raw cotton, as well as equipment and methods for drying food product and vegetative raw material [11-13], do not provide more efficient and high-quality drying of fibers, its moisture content should be between 8-9% [10].

Considering that the intensity of heat and mass transfer determines the speed of movement of the heat agent relative to the elements of the porous layer, this work presents the results of experimental researches of pressure losses in the cotton fiber layer from the point of view of the internal hydrodynamic problem during filtration drying of cotton. This method of drying can not only ensure the preservation of high quality raw cotton, but also reduce the energy costs of the primary processing process [14].

Experimental part and description of the installation. All experiments were carried out with the appropriate hangings of cotton fiber. Considering that the natural moisture content of cotton fiber is insignificant ($0.08 - 0.12 \text{ kg H}_2\text{O/kg dry. mat.}$) and the moisture is mostly related, at the temperature of the gas stream $T=293 \text{ K}$ and relative air moisture $\varphi = 60\%$ its evaporation will also be insignificant (the time of the experiment was $90 - 120 \text{ s}$, the sample mass loss during the experiment was less than 0.2%), therefore the effect of moisture evaporation on pressure loss was not taken into account.

Experimental studies of the hydrodynamics of a stationary layer of cotton fiber were carried out on an experimental installation, shown in figure 2, according to the method given in the works [14,15].




Figure 1 – Diagram of an experimental installation for researching the hydrodynamics of a conditionally stationary layer of cotton fiber:
 1 – experimental capacity;
 2 – receiver;
 3 – rotameter;
 4, 5 – control and shut-off valve;
 6 – the vacuum pump;
 7 – vacuum meter.

The experimental installation consists of a container 1 that is installed on the receiver 2, and with the help of a system of pipelines and a rotameter 3, 4 shut-off and regulating 5 valves is connected to a circulating vacuum pump 6. The rarefaction created by the vacuum pump in the receiver and under the material layer is measured by a vacuum meter 7.

The experimental tanks are presented in figure 3. The base of the container 1 is made of duralumin, and the cylindrical insert 2 and the perforated partition 3 are made of thermal insulation material (fluoroplast). In the center of the container is a measuring ruler 5, which makes it possible to determine the height of a conditionally stationary layer of cotton fiber 4 during the changes in the pressure drop.

In the experimental capacity 1, the appropriate cotton fiber suspension was loaded and installed on the receiver 2. Included a vacuum pump 6 and with the help of a control valve 5 different air flow rates were set through the cotton fiber layer. The flow rate was determined by the readings of the rotameter 3, pressure loss according to the vacuum meter 7 a change in the height of the cotton fiber layer using a measuring ruler. The number of measurements was 8 to 10 points, and each experiment was performed at

least three times until stable data was obtained. For each experiment was taken a fresh load of cotton. The weight of each cotton hitch was determined using the AXSIS-3000 electronic weight with an accuracy of 0.01g. The initial volume density for each experiment of the same weight of the hitch was the same.

The initial data for conducting experimental researches are shown in the table.

Characteristics of the cotton fiber layer [16]

Weight of the hitch G_v, kg	Porosity ε_0	Surface area F, m^2	The height of the fiber layer H_v, m
0.010	0.990	3.448	0.00101
0.015	0.987	5.172	0.00151
0.020	0.986	6.897	0.00201
0.025	0.984	8.621	0.00252
0.030	0.981	10.345	0.00302
0.060	0.966	20.689	0.00604
0.080	0.955	27.586	0.00806
0.110	0.942	37.931	0.01108

Discussion and checking the adequacy of results. Experimental researches on filtration of a heat agent through a conditionally stationary layer of cotton fiber with different weights were performed the functional dependence $\Delta P=f(v_0)$ is shown in figure 3 (a).




Figure 3 – Results of experimental researches: a) dependence of pressure losses in a conditionally stationary layer of cotton fiber on the fictitious filtration rate of the heat agent; b) dependence of the porosity of the cotton fiber layer on the fictitious filtration rate of the heat agent

Analysis of figure 3 (a) shows that the curves have a parabolic character, that is, the pressure loss in a conditionally stationary layer of cotton fiber is affected by both the viscous and inertial components. Figure 3 (b) shows a change in the porosity of the cotton fiber layer with a change in the fictitious filtration rate of the heat agent $\varepsilon = f(v_0)$.




Figure 4 – Comparison of experimental and theoretically calculated dependences
(the designation corresponds to figure 3): a) comparison of experimental and theoretically calculated
on the dependence (1) values of porosity of a conditionally stationary layer of cotton fiber;
b) dependence of the Euler number on the Reynolds number.

Approximation of experimental information by a power function allowed us to receive the following calculated dependence:

$$\varepsilon = \varepsilon_0 \cdot v_0^{-0.025} \quad (1)$$

The results of comparison of experimental data on the porosity of a conditionally stationary layer of cotton fiber with theoretically calculated ones based on the dependence (1) are shown in figure 4 (a).

As can be seen from figure 4 (a), the absolute value of the maximum relative error between the experimental data and the theoretically calculated data does not exceed 5.6%.

Generalization of experimental data (in figure 3 (a)), on the hydrodynamics of filtering a thermal agent through a stationary layer of cotton was carried out in the form of dimensionless complexes $Eu = f(Re_e)$ (in figure 4 (a)), and dependence of the hydraulic resistance coefficient of the layer $\xi = f(Re_e)$ as functions of the Reynolds number (in figure 5 (b)).

Approximation of the experimental data shown in figure 4 (b) by a power function allowed us to obtain the following calculated dependence:

$$Eu = 84000 \cdot Re_e^{-1.18}, \quad (2)$$

where Re_e – is the equivalent value of the Reynolds number.

$$Re_e = \frac{v \cdot d_e \cdot \rho}{\mu},$$

where μ – is coefficient of dynamic viscosity of the gas flow, $Pa \cdot s$;

The coefficient of hydraulic resistance of the cotton fiber layer was calculated based on the experimental data shown in figure 3 (a) from the equation [17,18]:

$$\Delta P = \xi \cdot \frac{\rho \cdot v^2}{2} = \xi \cdot \frac{\rho \cdot v_0^2}{2 \cdot \varepsilon_l^2} \quad (3)$$

where ξ – is the coefficient of hydraulic resistance of the porous layer $\xi = \lambda_l \cdot \frac{(a+b) \cdot H_v}{2 \cdot a \cdot b \cdot \varepsilon_l}$; v_0 – fictitious heat agent filtration rate $v_0 = v \cdot \varepsilon$, m / c ; ε_l – is the porosity of the layer, m^3 / m^3 ; a and b – the middle width and thickness of the cotton lint, respectively, m ; H_v – is the height of the fiber layer with density ρ_v , m .




Figure 5 – Comparison of experimental and theoretically calculated dependences
 (the designation corresponds to figure 3): a) - comparison of experimental and theoretically calculated
 on the dependence (2) of pressure losses in a conditionally stationary layer of cotton fiber
 b) - dependence of the coefficient of hydraulic resistance of cotton fiber on the Reynolds number

Approximation of experimental information shown in figure 5 (b) by a power function allowed us to receive the following calculated dependence [19,20]:

$$\xi = 160000 \cdot Re_e^{-1.16} \quad (4)$$

Comparing the proportion of experimentally determined values of pressure losses in a conditionally stationary layer of cotton fiber to those theoretically calculated based on the dependence (2) on the Reynolds number shown in figure 5 (a). The absolute value of the relative error does not exceed 14.2%, which is explained by the complex structure and spontaneity of the formation of a stationary layer of cotton fiber, as well as the impact of the pressure drop on the height of the layer.

Conclusions. One of the high-intensity methods of removing both free and bound moisture is filtration drying. This is due to the fact that during drying, the filtration heat agent is filtered through the porous structure of the wet material, which is placed on the perforated partition in the direction "wet material - perforated partition". The speed of movement of the heat agent in the pores and channels of a stationary layer of wet material determines the thickness of the boundary layer (hydrodynamic, thermal and diffusion) and accordingly, the values of the heat coefficients and mass transfer. Besides that, the surface of heat and mass transfer is the total surface of the pores and channels through which the heat agent is filtered. The filtration rate of the heat agent is determined based on technical and economic considerations, taking into account that its increase affects the growth of pressure loss. Moreover, the actual speed of movement of the heat agent relative to the layer elements is significantly higher than in the case of drying by any other methods (in boiling layer, during drying in pneumatic transport dryers, etc). Large heat and mass transfer surfaces and the speed of the heat agent in the pores and channels of the stationary layer of wet material provide high coefficients of heat and mass transfer and accordingly, the intensity of filtration drying.

А. Е. Хусанов¹, В. М. Атаманюк³, Б. М. Қалдыбаева¹,
А. З. Абильмагжанов², Д. Ж. Джанабаев¹, Ж. Е. Хусанов¹

¹М. Әуезов атындағы Оңтүстік Қазакстан мемлекеттік университеті, Шымкент, Қазақстан;

²Д. Сокольский атындағы Жанармай, катализ және электрохимия институты АҚ, Алматы, Қазақстан;

³«Львов политехникасы» Үлттық университеті, Львов, Украина

ШИТТІ МАҚТАНЫ СУЗІП КЕПТІРУ КЕЗІНДЕ СТАЦИОНАРЛЫҚ ҚАБАТТЫҢ ГИДРОДИНАМИКАСЫН ЭКСПЕРИМЕНТТЕКІ ЗЕРТТЕУ НӘТИЖЕЛЕРИ

Аннотация. Мақта талшығы армирлеуші композит, геотекстиль, жеке абсорбция құралдары және биомедициналық материалдар сияқты жаңа, дәстүрлі емес қолдану салаларында кеңінен пайдаланылады. Соңдықтан мақтаны қайта өндөуді жаңғыруту және сапалы сактау Қазақстан экономикасын дамыту үшін өте маңызды. Қазіргі уақытта мақта өңдеу зауыттарында кептіру барабанын пайдалану барысында шикізат қасиеттері нашарлайды. Келесі технологиялық үдерістер нәтижесінде талшықтың сорттылығы механикалық әсер ету арқылы 25% - ға төмендейді: артық энергия жұмсалады, талшық түсі жоғалады әрі бұралады, талшықтың микрокұрылымы нашарлайды.

Жылу мен масса алмасудың қарқыны кеуекті қабаттың элементтеріне қатысты жылу агентінің қозғалыс жылдамдығын анықтайдынын ескере отырып, аталған зерттеу жұмысында мақтаны сүзіп кептіру барасында гидродинамиканың ішкі міндеті түрғысынан мақта талшығының қабатындағы қысым шығынын тәжірибелік зерттеу нәтижесі ұсынылған. Мұндай кептіру әдісі шитті мақтаның жоғары сапасын сақтауды қамтамасыз етумен қатар, бастапқы өңдеу үдерісінің энергетикалық шығынын да төмендетуі мүмкін. Сонымен бірге Сүзгіш Кептіру үдерісіне жұмсалатын энергия шығыны тұрақты қабаттагы қысымның жоғалу уақытынан жылу агентін берілген температурага дейін қыздырады. Бұл үшін мақтаның ылғалды талшық қабатындағы тұрақты қысымның жоғалып кету жағдайының фильтрациялық кептірудің қарқыны мен экономикалық тиімділігін анықтайды фактор ретінде жылу агентін сүзгілеудің фиктивті жылдамдығына тәуелділігін анықтау маңызды болып саналады. Мақта талшығының табиги ылғалының мардымсыздығын ескере отырып, эксперимент мақта талшығын өлшеу барысында жүргізілді.

Тәуелділікті талдау мақта талшығының шартты стационарлық қабатындағы қысымның жоғалуына Тұтқыр және инерциялық құрамдастың әсерін айқыннады. Жылу агентін сүзудің фиктивті жылдамдығын ауыстыра отырып, мақта талшығы қабатындағы кеуектің өзгеру үдерісі көрсетілген. Ылғалды материалдың стационарлық қабатындың тесігі мен каналындағы жылу агентінің қозғалыс жылдамдығы шекаралық қабат қалындығын және тиісінше жылу және масайналым коэффициенттерінің мәнін анықтайды. Сонымен қатар, жылу және масса алмасу беті жылу агенті сүзетін тесіктер мен каналдардың жыныстық беті болып саналады. Жылу агентін сүзу жылдамдығы оның ұлғаюы қысымның жоғалуына әсер етегінің ескере отырып, техникалық-экономикалық пайымдарға сүйене отырып анықталады. Бұл ретте, қабат элементтеріне қатысты жылу агентінің нақты қозғалыс жылдамдығы кез келген басқа әдістермен (қайнаған қабатта, пневмокөлік кептіргішінде кептіру кезінде және т.б.) кептіру жағдайына қарағанда айтартылтай жоғары. Жылу және масса алмасудың үлкен беті және ылғалды материалдың стационарлық қабатындың тесігі мен каналдарындағы жылу агентінің жылдамдығы жылу және масса қайтарудың жоғары коэффициентін және тиісінше Сүзгіш кептірудің қарқындылығын қамтамасыз етеді.

Рейнольдс санына байланысты теориялық есептелген мақта талшығының шартты стационарлық қабатындағы қысымның тәжірибелі мәнінің қатынасын салыстыру нәтижесі келтірілген. Салыстырмалы қателіктің абсолюттік мәні 14,2%-дан аспайды, бұл жағдай мақта талшығының стационарлық қабатындың қалыптасуының күрделі құрылымы, стихиялығы, сондай-ақ қабат биіктігіне қысым ауытқуының әсері негізінде түсіндіріледі.

Түйін сөздер: мақта талшығы, гидродинамика, сүзіп кептіру, гидравликалық кедергі, кеуектілік, қабаттың белсенді беткі қабаты.

**А. Е. Хусанов¹, В. М. Атаманюк³, Б. М. Калдыбаева¹,
А. З. Абильмагжанов², Д. Ж. Джанабаев¹, Ж. Е. Хусанов¹**

¹Южно-Казахстанский государственный университет им. М. Аuezова, Шымкент, Казахстан;

²Институт топлива, катализа и электрохимии им. Д. Сокольского, Алматы, Казахстан;

³Национальный университет «Львовская политехника», Львов, Украина

РЕЗУЛЬТАТЫ ЭКСПЕРИМЕНТАЛЬНЫХ ИССЛЕДОВАНИЙ ГИДРОДИНАМИКИ СТАЦИОНАРНОГО СЛОЯ ПРИ ФИЛЬТРАЦИОННОЙ СУШКЕ ХЛОПКА-СЫРЦА

Аннотация. Волокна хлопка широко используются в новых, нетрадиционных областях применения, таких как армирующие композиты, геотекстиль, средства индивидуальной абсорбции и биомедицинские материалы. Поэтому модернизация переработки хлопка и качественное хранение имеет чрезвычайно важное значение для развития экономики Казахстана. В настоящее время на хлопкоперерабатывающих заводах при использовании сушильных барабанов ухудшаются свойства сырья. В результате последующих технологических процессов сортность волокна снижается на 25% через механическое воздействие, тратится много энергии, теряется цвет волокна, а также происходит скручивание волокна, ухудшается микроструктура волокна.

Учитывая то, что интенсивность тепло- и массообмена определяет скорость движения теплового агента относительно элементов пористого слоя, в данной работе представлены результаты экспериментальных исследований потерь давления в слое волокна хлопка с точки зрения внутренней задачи гидродинамики при фильтрационной сушке хлопка. Такой метод сушки может не только обеспечить сохранение высокого качества хлопка сырца, но и снизить энергетические расходы процесса первичной переработки. Вместе с этим суммарные затраты энергии на процесс фильтрационной сушки состоят из потерь давления в стационарном слое и нагрева теплового агента до заданной температуры. Для этого важно установить зависимость потерь давления в стационарном слое влажного волокна хлопка от фиктивной скорости фильтрации теплового агента, как важного фактора определяющего интенсивность и экономическую эффективность фильтрационной сушки. Все эксперименты проводили при соответствующих навесках волокна хлопка, учитывая то, что естественное влагосодержание волокна хлопка является незначительным.

Анализ зависимостей показывает, что на потери давления в условно стационарном слое волокна хлопка влияют как вязкостная, так и инерционная составляющие. Приведено изменение порозности слоя волокна хлопка со сменой фиктивной скорости фильтрации теплового агента. Скорость движения теплового агента в порах и каналах стационарного слоя влажного материала определяет толщину пограничного слоя и соответственно значения коэффициентов тепло- и массоотдачи. Кроме этого, поверхностью тепло- и массообмена является суммарная поверхность пор и каналов, сквозь которые фильтруется тепловой агент. Скорость фильтрации теплового агента определяют исходя из технико-экономических соображений, учитывая то, что ее увеличение влияет на рост потери давления. Причем, действительная скорость движения теплового агента относительно элементов слоя значительно выше, чем в случае сушки любыми другими методами (в кипящем слое, во время сушки в пневмотранспортных сушилках и др). Большие поверхности тепло- и массообмена и скорость теплового агента в порах и каналах стационарного слоя влажного материала обеспечивают высокие коэффициенты тепло- и массоотдачи и соответственно интенсивность фильтрационной сушки.

Приведены результаты сравнения отношения экспериментально определенных значений потерь давления в условно стационарном слое волокна хлопка к теоретически рассчитанным в зависимости от числа Рейнольдса. Абсолютное значение относительной погрешности не превышает 14,2%, что объясняется сложной структурой и стихийностью формирования стационарного слоя волокна хлопка, а также воздействием перепада давления на высоту слоя.

Ключевые слова: волокно хлопка, гидродинамика, фильтрационная сушка, гидравлическое сопротивление, пористость, активная удельная поверхность слоя.

Information about the authors:

Khussanov Alisher Ye., Candidate of technical sciences, Associate Professor of M. Auezov South Kazakhstan State University, Shymkent, Kazakhstan; khusanov_1975@inbox.ru; <https://orcid.org/0000-0002-1563-6437>

Atamanyuk Volodimir M., Doctor of Technical Sciences, Professor of Lviv Polytechnic National University, Lviv, Ukraine; atamanyuk@ukr.net; <https://orcid.org/0000-0002-8707-2319>

Kaldybayeva Botagoz M., PhD, Associate Professor of M. Auezov South Kazakhstan State University, Shymkent, Kazakhstan; kaldybaeva.b@mail.ru; <https://orcid.org/0000-0002-1570-2107>

Abilmagzhanov Arlan Zh., Candidate of Chemical Sciences, Head of Applied Research laboratory of JSC “D. V. Sokolskiy Institute of Fuel, Catalysis and Electrochemistry”, Almaty, Kazakhstan; arlandez_81@mail.ru; <https://orcid.org/0000-0001-8355-8031>

Janabayev Dauren Zh., PhD Doctoral Student M. Auezov South Kazakhstan State University, Shymkent, Kazakhstan; janabaev19@mail.ru

Khussanov Zhakhongir Ye., Candidate of technical sciences. Associate Professor of M. Auezov South Kazakhstan State University, Shymkent, Kazakhstan; zhakhangir@mail.ru; <https://orcid.org/0000-0001-7482-4828>

REFERENCES

- [1] Avtonomov A.I., Kaziev M.Z., Shlejxer A.I. i dr. (1983) Xlopkovodstvo. Kolos, M. ISBN: 3803030104-089 (in Russ.).
- [2] Maksudov I.T., Nuraliev A.N. (1994) Spravochnik po pervichnoj obrabotke xlopka. NPO «Xlopkoprom», Tashkent. ISBN: 5-8244-1048-8 (in Russ.).
- [3] Kale R.D., Bansal P.S., Gorade V.G. (2017) Extraction of Microcrystalline Cellulose from Cotton Sliver and Its Comparison with Commercial Microcrystalline Cellulose // Journal of Polymers and the Environment. 26: 355-364. doi:10.1007/s10924-017-0936-2 (in Eng.).
- [4] Zeng L., Zhao S., He M. (2018) Macro scale porous carbonized polydopamine-modified cotton textile for application a selector dein microbial fuel cells. Journal of Power Sources. 376: 33-40. DOI: 10.1016/j.jpowsour.2017.11.071 (in Eng.).
- [5] Wedin H., Niit E., Mansoor Z. A., Kristinsdottir A. R., DelaMotte H., Jönsson C., Lindgren C. (2018) Preparation of Viscose Fibres Stripped of Reactive Dyes and Wrinkle-Free Cross linked Cotton Textile Finish // Journal of Polymer sand the Environment. 6: 3603-3612. DOI:10.1007/s10924-018-1239-y (in Eng.).
- [6] Cui L., Shi S., Hou W., Yan Z., Dan J. (2018) Hydrolysis and carbonization mechanism of cotton fiber sin subcritical water // New Carbon Materials. 33: 245-251. DOI: 10.1016/s1872-5805(18)60337-3 (in Eng.).
- [7] Lv N., Wang X., Peng S., Luo L., Zhou, R. (2018) Super hydrophobic super ole o phallic cotton-oil absorbent: preparation and it supplication in oil-water separation. RSC Advances. 8: 30257-30264. DOI: 10.1039/c8ra05420g (in Eng.).
- [8] Gosudarstvennaya programma industrial'no-innovacionnogo razvitiya Respubliki Kazakhstana 2020 - 2025 gody': utverzhdena Postanovleniem Pravitel'stva Respubliki Kazakhstan 31 dekabrya, 2019, № 1050 // https://online.zakon.kz/Document/doc_id=32424143 (in Russ.).
- [9] Azhimetova G.N. (2011) Mirovoj opyt i obzor razvitiya hlopkovodstva v Kazahstane. Modern problems of science and education [Sovremennye problemy nauki i obrazovaniya] 1: 53-58 (in Russ.).
- [10] Ibrogimov H.I., Alimardonov K.M., Zul'fanov S.Z., Badalov A.B. (2007) Termodinamicheskie harakteristiki processa degidratacii hlopka-syrca // Textile industry technology [Tekhnologiya tekstil'noj promyshlennosti] 4: 19-22 (in Russ.).
- [11] Umirzakov R., Mukhiddinov D.N., Abdirova M., Ongar B. (2019) Influence on the mode of grain drying in the heat generator and combustion products // News of the national academy of sciences of the Republic of Kazakhstan. Series of geology and technical sciences. Vol. 1, N 433 (2019). P. 176-186. <https://doi.org/10.32014/2019.2518-170X.22>. ISSN 2518-170X (Online), ISSN 2224-5278 (Print) (in Eng.).
- [12] Abdizhapparova B.T., Khanzharov N.S., Ospanov B.O., Pankina I.A., Orymbetova G.E. (2019) A way of vacuum-atmospheric drying of jerusalem artichoke tubers // News of the national academy of sciences of the Republic of Kazakhstan. Series of geology and technical sciences. Vol. 6, N 438 (2019). P. 165-176. <https://doi.org/10.32014/2019.2518-170X.167>. ISSN 2518-170X (Online), ISSN 2224-5278 (Print) (in Eng.).
- [13] Abdizhapparova B.T., Khanzharov N.S., Ospanov B.O., Pankina I.A., Kumisbekov S., Islam K.S. (2019) Results of vacuum-atmospheric drying of large-dispersed food materials // News of the national academy of sciences of the Republic of Kazakhstan. Series chemistry and technology. Vol. 6, N 438 (2019). P. 61-69. <https://doi.org/10.32014/2019.2518-1491.75>. ISSN 2518-1491 (Online), ISSN 2224-5286 (Print) (in Eng.).
- [14] Atamanyuk V.M., Gumnic'kij Ya.M. (2013) Naukovi osnovi fil'tracijnogo sushinnya dispersnih materialiv. Vidavnictvo Nacional'nogo universitetu "Lviv'ska politekhnika", Lviv. ISBN: 978-617-607-397-0 (in Ukr.).
- [15] Atamanyuk V., Huzova I., Gnativ Z. (2018) Intensification of Drying Process During Activated Carbon Regeneration // Chemistry&Chemical Technology. N 2 (2018). P. 263-271. <https://doi.org/10.23939/chcht12.02.263> (in Eng.).
- [16] Khussanov A., Atamanyuk V., Janabayev D., Kaldybaeva B. (2019) Research of Properties of Raw Cotton –as the Object of Drying. 2 nd INTERNATIONAL Scientific Conference “Chemical Technology and Engineering”. 1: 223-224.
- [17] Aerov M.E., Todes O.M., Narinskij D.A. (1979) Apparaty so stacionarnym zernistym sloem: Gidravlicheskie i teplovye osnovy raboty. M.: Himiya. ISBN: 31402-097-79 (in Russ.).
- [18] Hanik Ya.M., Rimar T.I., Krekhovec'kij O.M. (2006) Gidrodinamika i kinetika procesu sushinnya glini u shchil'nomu shari pid chas ICH-nagrivannya. Scientific herald. Collection of scientific and technical works of NLTU [Naukovij visnik. Zbirnik naukovo-tehnichnih prac' NLTUU]. 16 (5): 74-78. (in Ukr.).
- [19] Arun S. Mujumdar (2015) Handbook of Industrial Drying Fourth Edition. LLC CRC Press is an imprint of Taylor & Francis Group, an Informa business, US. ISBN: 978-1-4665-9666-5 (in Eng.).
- [20] Belenkaya I.R., Golinskaya Ya.A. (2016) Technological aspects of production of the candied fruits from non-traditional raw material // Food science and technology, 10 (2): 50-57. DOI: <http://dx.doi.org/10.15673/fst.v10i2.156> (in Eng.).

**Publication Ethics and Publication Malpractice
in the journals of the National Academy of Sciences of the Republic of Kazakhstan**

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

[www:nauka–nanrk.kz](http://www.nauka-nanrk.kz)

ISSN 2518–1467 (Online), ISSN 1991–3494 (Print)

<http://www.bulletin-science.kz/index.php/en/>

Редакторы *М. С. Ахметова, Д. С. Аленов, А. Ахметова*
Верстка на компьютере *Д. А. Абдрахимовой*

Подписано в печать 14.08.2020.
Формат 60x881/8. Бумага офсетная. Печать – ризограф.
21,6 п.л. Тираж 500. Заказ 4.