ҚАЗАҚСТАН РЕСПУБЛИКАСЫ ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Д.В.Сокольский атындағы «Жанармай, катализ және электрохимия институты» АҚ

ХАБАРЛАРЫ

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК РЕСПУБЛИКИ КАЗАХСТАН АО «Институт топлива, катализа и электрохимии им. Д.В. Сокольского»

NEWS

OF THE ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN JSC «D.V. Sokolsky institute of fuel, catalysis and electrochemistry»

SERIES CHEMISTRY AND TECHNOLOGY

3 (435)

MAY - JUNE 2019

PUBLISHED SINCE JANUARY 1947

PUBLISHED 6 TIMES A YEAR



NAS RK is pleased to announce that News of NAS RK. Series of chemistry and technologies scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of chemistry and technologies in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of chemical sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Химия және технология сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруда. Webof Science зерттеушілер, авторлар, баспашылар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Химия және технология сериясы Етегдіпд Sources Citation Index-ке енуі біздің қоғамдастық үшін ең өзекті және беделді химиялық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия химии и технологий» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по химическим наукам для нашего сообщества.

Бас редакторы х.ғ.д., проф., ҚР ҰҒА академигі **М.Ж. Жұрынов**

Редакция алкасы:

Ағабеков В.Е. проф., академик (Белорус)

Волков С.В. проф., академик (Украина)

Воротынцев М.А. проф., академик (Ресей)

Газалиев А.М. проф., академик (Қазақстан)

Ергожин Е.Е. проф., академик (Қазақстан)

Жармағамбетова А.К. проф. (Қазақстан), бас ред. орынбасары

Жоробекова Ш.Ж. проф., академик (Қырғыстан)

Иткулова Ш.С. проф. (Қазақстан)

Манташян А.А. проф., академик (Армения)

Пралиев К.Д. проф., академик (Қазақстан)

Баешов А.Б. проф., академик (Қазақстан)

Бүркітбаев М.М. проф., академик (Қазақстан)

Джусипбеков У.Ж. проф. корр.-мүшесі (Қазақстан)

Молдахметов М.З. проф., академик (Қазақстан)

Мансуров З.А. проф. (Қазақстан)

Наурызбаев М.К. проф. (Қазақстан)

Рудик В. проф., академик (Молдова)

Рахимов К.Д. проф. академик (Қазақстан)

Стрельцов Е. проф. (Белорус)

Тәшімов Л.Т. проф., академик (Қазақстан)

Тодераш И. проф., академик (Молдова)

Халиков Д.Х. проф., академик (Тәжікстан)

Фарзалиев В. проф., академик (Әзірбайжан)

«ҚР ҰҒА Хабарлары. Химия және технология сериясы».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Меншіктенуші: «Қазақстан Республикасының Ұлттық ғылым академиясы» Республикалық қоғамдық бірлестігі (Алматы қ.)

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде 30.04.2010 ж. берілген №1089-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік

Мерзімділігі: жылына 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18, http://chemistry-technology.kz/index.php/en/arhiv

© Қазақстан Республикасының Ұлттық ғылым академиясы, 2019

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Главный редактор д.х.н., проф., академик НАН РК **М. Ж. Журинов**

Редакционная коллегия:

Агабеков В.Е. проф., академик (Беларусь)

Волков С.В. проф., академик (Украина)

Воротынцев М.А. проф., академик (Россия)

Газалиев А.М. проф., академик (Казахстан)

Ергожин Е.Е. проф., академик (Казахстан)

Жармагамбетова А.К. проф. (Казахстан), зам. гл. ред.

Жоробекова Ш.Ж. проф., академик (Кыргызстан)

Иткулова Ш.С. проф. (Казахстан)

Манташян А.А. проф., академик (Армения)

Пралиев К.Д. проф., академик (Казахстан)

Баешов А.Б. проф., академик (Казахстан)

Буркитбаев М.М. проф., академик (Казахстан)

Джусипбеков У.Ж. проф. чл.-корр. (Казахстан)

Мулдахметов М.З. проф., академик (Казахстан)

Мансуров З.А. проф. (Казахстан)

Наурызбаев М.К. проф. (Казахстан)

Рудик В. проф., академик (Молдова)

Рахимов К.Д. проф. академик (Казахстан)

Стрельцов Е. проф. (Беларусь)

Ташимов Л.Т. проф., академик (Казахстан)

Тодераш И. проф., академик (Молдова)

Халиков Д.Х. проф., академик (Таджикистан)

Фарзалиев В. проф., академик (Азербайджан)

«Известия НАН РК. Серия химии и технологии».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Собственник: Республиканское общественное объединение «Национальная академия наук Республики

Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10893-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел. 272-13-19, 272-13-18,

http://chemistry-technology.kz/index.php/en/arhiv

© Национальная академия наук Республики Казахстан, 2019

Адрес редакции: 050100, г. Алматы, ул. Кунаева, 142,

Институт органического катализа и электрохимии им. Д. В. Сокольского,

каб. 310, тел. 291-62-80, факс 291-57-22, e-mail:orgcat@nursat.kz

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

E ditor in chief doctor of chemistry, professor, academician of NAS RK **M.Zh. Zhurinov**

Editorial board:

Agabekov V.Ye. prof., academician (Belarus)

Volkov S.V. prof., academician (Ukraine)

Vorotyntsev M.A. prof., academician (Russia)

Gazaliyev A.M. prof., academician (Kazakhstan)

Yergozhin Ye.Ye. prof., academician (Kazakhstan)

Zharmagambetova A.K. prof. (Kazakhstan), deputy editor in chief

Zhorobekova Sh.Zh. prof., academician (Kyrgyzstan)

Itkulova Sh.S. prof. (Kazakhstan)

Mantashyan A.A. prof., academician (Armenia)

Praliyev K.D. prof., academician (Kazakhstan)

Bayeshov A.B. prof., academician (Kazakhstan)

Burkitbayev M.M. prof., academician (Kazakhstan)

Dzhusipbekov U.**Zh.** prof., corr. member (Kazakhstan)

Muldakhmetov M.Z. prof., academician (Kazakhstan)

Mansurov Z.A. prof. (Kazakhstan)

Nauryzbayev M.K. prof. (Kazakhstan)

Rudik V. prof., academician (Moldova)

Rakhimov K.D. prof., academician (Kazakhstan)

Streltsov Ye. prof. (Belarus)

Tashimov L.T. prof., academician (Kazakhstan)

Toderash I. prof., academician (Moldova)

Khalikov D.Kh. prof., academician (Tadjikistan)

Farzaliyev V. prof., academician (Azerbaijan)

News of the National Academy of Sciences of the Republic of Kazakhstan. Series of chemistry and technology. ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of Information and Archives of the Ministry of Culture and Information of the Republic of Kazakhstan N 10893-Ж, issued 30.04.2010

Periodicity: 6 times a year Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,

http://chemistry-technology.kz/index.php/en/arhiv

© National Academy of Sciences of the Republic of Kazakhstan, 2019

Editorial address: Institute of Organic Catalysis and Electrochemistry named after D. V. Sokolsky

142, Kunayev str., of. 310, Almaty, 050100, tel. 291-62-80, fax 291-57-22,

e-mail: orgcat@nursat.kz

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

____ 5 ____

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

SERIES CHEMISTRY AND TECHNOLOGY

ISSN 2224-5286

https://doi.org/10.32014/2019.2518-1491.27

Volume 3, Number 435 (2019), 38 – 43

UDC 544.478

B.K.Massalimova¹, D.T.Altynbekova, G.D.Jetpisbayeva, S.M.Nauruzkulova, E.E.Bakytzhan¹, Sapi A.K., V.A.Sadykov^{2,3}

¹M.Kh. Dulaty Taraz State University, Taraz, Kazakhstan;
² Novosibirsk State University, Novosibirsk, Russia;
3Institute of Catalysis named after G.K. Boreskov, Novosibirsk, Russia massalimoval5@mail.ru

LIQUEFIED PETROLEUM GAS AS RAW MATERIALS FOR THE PRODUCTION OF LIQUID OXYGEN-CONTAINING ORGANIC COMPOUNDS

Abstract. Studies on the air oxidative transformation of the propane-butane mixture to oxygen-containing compositions have been carried out. The optimum temperatures of the process, as well as the ratios of the initial components of the reaction mixture and the content of the active phase on the carrier and volumetric rates have been determined. Physical and chemical studies of the initial and treated catalysts under experimental conditions were carried out. When changing the content of the active component on the carrier from 1 to 10%, it was found that the most optimal is the catalyst 5% MoCrGa/TC, on which up to 22% acetone was obtained. As a result of varying the composition of the catalyst, the content of the active phase, the ratio of reactants, up to 35–40% of acetone was obtained. In addition, in some cases, CH3OH was obtained, with the maximum yield 22%, as well as 35% of methyl ethyl ketone. As a result of EM and XRD studies, it was shown that under reaction conditions a new Cr₂O₅ phase (corresponding to the Cr²⁺ and Cr³⁺ transition to Cr⁵⁺) is formed on the catalyst surface, as well as joint phases of Mo and Cr in various valence states, the physical meaning and role of which are to be determined.

Key words: natural clay, acetone.

Introduction. Natural and petroleum gases are the most important alternative sources of raw materials that can in the long run compete with oil. Of particular relevance for countries rich in this type of raw material is the problem of the rational use of alkanes in their composition [1-5]. Kazakhstan has significant oil and gas reserves. Unfortunately, there is currently no industrial organic synthesis based on alkanes in Kazakhstan, with the exception of gas processing plant in Zhanauzen, the nitrogen-fertilizer plant in Atyrau (which uses the low-profitable process of steam reforming of methane into synthesis gas) and ethylene production in Aktau (by non-catalytic pyrolysis of ethane with the addition of other hydrocarbons and petroleum fractions). Kazakhstan is entering a new era in hydrocarbon processing. Gas processing is the most promising direction of petrochemistry is. This sphere will help Kazakhstan to integrate faster in the world market. The partial oxidation of liquefied petroleum gas to ketones and aldehydes is relevant from the of ecological and economical point of view, since about 100 billion cubic meters of associated petroleum gas are burned annually and pollutant emissions to the atmosphere amount to thousands of tons [6-11]. The combustion process due to oxygen consumption and heat release contributes to the greenhouse effect. In addition, the economy is suffering losses due to the combustion of far from cheap petroleum gas, especially if we consider that it would be possible to get petrochemical products from the liquefied petroleum gas which are much more expensive than the original product.

A large number of studies have been carried out on the oxidation of propane and butane to unsaturated aldehydes and acids /12-16/, but there are few works on the production of ketones /17-20/.

Methods. This paper presents the results of oxidative transformation study of liquefied petroleum gas (propane-butane mixture) by air into oxygen-containing compositions in reaction mixtures with a propane-butane content 14- 80% and oxygen 4-18% at T = 300-600 °C and $W = 330\text{-}15000\text{h}^{-1}$. Polyoxide catalysts of different composition, containing 1-10% Mo, Ga, Cr in various proportions, deposited on natural Torgai clay (TC), having the structure of kaolinite (in some cases with the addition of hematite and α -quartz) were tested. Automated analysis of initial materials and reaction products were carried out on Agilent Technologies 6890N chromatograph. Physical and chemical studies of the initial and treated catalysts under experimental conditions (XRD, EM, elemental analysis, determination of acidity) were carried out [9-10].

It is established that the main reaction products are acetone, methanol, acetaldehyde, methyl ethyl ketone (MEK). The optimum process temperature is 350-400 °C. C₂H₄, H₂, CO, and CO₂ were detected in the reaction products when temperature increased. It was shown that the yield of oxygen-containing products on catalysts pretreated with 10% HCl exceeds similar yields on untreated catalysts. Acid treatment of sorbents contributed to the development of the surface and an increase in the pore radius, which led to an increase in oxygen-containing compounds in catalyzate [8-9]. Varying the reaction conditions on a number of catalysts (two-component - CrGa/TC and three-component - MoCrGa/TC) leads to a change in the content of the active phase and has a significant impact on the yield of the main products. When varying the content of the active component on the carrier from 1 to 10%, it was shown that the most optimal was 5% MoCrGa/TG catalyst, on which up to 22% acetone was obtained, the three-component catalyst being more active than the two-component catalyst (Figure 1).




Figure 1 - The effect of active phase content of the catalysts on the yield of acetone and acetaldehyde.

Tests of the above catalysts at space velocities from 330 to 15000 h^{-1} showed that for the synthesis of acetaldehyde and acetone on the 1% CrGa / TC catalyst, the optimal rate is W = 1200 h^{-1} , and for the 5% CrGa/TC catalyst - 9000 h^{-1} for acetaldehyde and 330 h^{-1} for acetone (acetone yield is 32%), Figure 2 and 3. Optimal space velocities were also determined for three-component MoCrGa/TC catalysts with different content of the active phase on the carrier. At W=1350 h^{-1} , up to 23% of acetone and 35% of methyl ethyl ketone on 5% MoCrGa/TC were produced, whereas 22% of acetone on 5% MoCrGa/TC catalysts was produced.




Figure 2 - The effect of space velocities on the yield of acetaldehyde on 1% -, 5% - and 10% CrGa/TC catalyst at 400 °C




Figure 3 -The effect of space velocities on the yield of acetone on 1% -, 5% - and 10% CrGa/TC catalyst at 400 °C

Studies on variation of the initial components ratio in the reaction mixture allowed to determine the most optimal compositions for the process implementation. By varying the concentration of O2 from 3.8 to 8.4% in the mixture, it was shown that when the content of O_2 is 5.3% and the propane-butane mixture is ~ 60 -66%, the yield of acetone is 23% and methanol is 22%. When the content of the propane-butane mixture is 33-36% with the same O_2 content, 31% acetone and 35% MEK are obtained. By varying the composition of the catalyst, the content of the active phase, the ratio of reactants up to 31% acetone and 35% MEK were produced. In addition, in some cases CH_3OH was produced with the maximum yield 22%.

The microstructure and morphology of the catalysts were determined by X-ray phase analysis and electronic microscopy (EM) [14].

Results and discussion. The experiment was carried out on the electron microscope EM-125K by single-stage coal replicas method with extraction, using microdiffraction, as well as the method of survey through the lumen (suspension preparations). The survey was carried out at different magnifications depending on the particle size []. The carrier was dissolved in concentrated HF. The X-ray phase analysis was performed on a DRON-4-07 X-ray diffractometer. EM method provides observation of electron diffraction on individual crystals and accumulation of particulate matter, while the XRD method gives the total diffractogram of all phases [8-9].

In addition, for the manifestation of the phase in XRD it must have a large enough size. Therefore, many phases detected by EM method may not be observed in X-ray phase analysis, but this does not mean their absence in the catalyst.

For microdiffraction in electron microscopy, the transparency of the material for the electron beam is important. Sometimes well crystallized phases stably observed in XRD may be not transparent to the EM.

Both methods complement each other and provide a more complete picture of the catalyst changes under the influence of the environment.

The presence of a large number of insoluble components that make it difficult to decipher the deposited phases is characteristic of the carrier (Torgai clay). For the original clay sample MoCrGa / Torg. large particles and aggregates of large dense particles are characteristic, the microdiffraction pattern of which is represented by individual rare reflexes attributed to Cr2O3 (JCPDS, 6-508) and CrO (JCPDS, 6-532), as well as translucent particles of lamellar type, the microdiffraction image from which reflexes, located on the hexagonal motif, referred to CrMoO4 (JCPDS, 34-474).

The phase related to Ga, were not detected. Mo-containing phase is characterized by dense large crystals of 500–1000 Å with signs of a rectangular motif of cut, corresponding to Mo4O11 (JCPDS, 13-142). For the Cr-containing phase, large semitransparent lamellar particles α -Cr2O3 (JCPDS, 6-503), small clusters made up of dispersed particles \sim 30 Å in size, referred to Cr2O5 (JCPDS, 36-1329), aggregates of translucent particles with minimal size 200-400Å and larger, characteristic for CrO2 (JCPDS, 9-332), a cluster of translucent lamellar particles Cr5O12 (JCPDS, 18-390) 300-600 Å in size with a rectangular cut motif.

Furthermore, we detected small clusters characteristic for joint phases consisting of particle 30-50Å in size and large plate-type particles. Microdiffraction is represented by a mixture of rings and individual reflexes. The rings correspond to the phase of disperse particles CrMoO4 (JCPDS, 29-452), and large plate crystals correspond to Cr2MoO6 (JCPDS, 33-401). Ga-containing phase is characterized by different phases of Ga oxidation up to the metal phase: α-Ga2O3 (JCPDS, 6-503), φ-Ga2O3 (JCPDS, 20-426), ε-Ga2O3 (JCPDS, 6-509) mixed with Ga (JCPDS, 31-539), Ga (JCPDS, 25-345).

Comparison with the EM pictures of the initial samples of catalysts allowed to state that as a result of their treatment under the reaction conditions, a new Cr2O5 phase appears, corresponding to the Cr2 + and Cr3 + transition to Cr5 +, as well as the combined Mo- Cr phases in different valence states, the physical meaning and role of which are to be determined

Conclusion. Source of research funding. Initiative project "Conversion of hydrocarbon raw materials of Kazakhstana" Department of "Chemistry and Chemical Technology" of M.Kh.Dulaty Taraz State University.

ƏOK 544.478

Б.К. Масалимова¹, Д.Т. Алтынбекова¹, Г.Д. Джетписбаева¹, С.М. Наурузкулова¹, АА. Атакожаева¹, А.К. Сапи¹, В.А. Садыков^{2,3}

¹М.Х. Дулати атындағы Тараз мемлекеттік университеті, Тараз, Қазақстан; ²Новосибирск мемлекеттік университеті, Новосибирск, Ресей; ³Г.К. Боресков атындағы катализ институты, Новосибирск, Ресей

СЫҒЫЛҒАН МҰНАЙ ГАЗЫ - СҰЙЫТЫЛҒАН ОТТЕКҚҰРАМДАС ОРГАНИКАЛЫҚ ҚОСЫЛЫСТАР ӨНДІРІСІ ҮШІН ШИКІЗАТ РЕТІНДЕ

Аннотация. Пропан-бутан қоспасының құрамында оттегі бар органикалық қосылыстарға каталитикалық тотығуы бойынша зерттеулер жүргізілді. Сондай-ақ үрдістің оптимальді технологиялық температуралары, бастапқы компоненттердің жәнетасымалдағыштың белсенді фаза құрамы жәнекөлемдік жылдамдықтары анықталды. Бастапқы және реакциядан кейінгі (өңделген) катализаторларға физика-химиялық зерттеулер жүргізілді. Зерттеулер нәтижесі бойынша тасымалдағыштағы белсенді компоненттердің құрамын 1% -дан 10% дейін өзгерту нәтижесінде ең тиімді катализатор 5% МоСгGа / ТСБ екені анықталып, 22% ацетон алынды. Катализатордың және тасымалдағыштағы белсенді заттардың құрамын, әрекеттесуші реагенттердің қатынасын өзгерту нәтижесінде 35-40% дейін ацетоналынды. Сонымен қатар, кейбір жағдайларда СН₃ОН максималды 22% шығымы және 35% метилэтилкетон алынды. ЭМ және РФА зерттеулерінің нәтижесінде реакция жағдайында катализатордың бетінде жаңа Cr_2O_5 фазасы $(Cr^{2+}$ және Cr^{3+} -ға Cr^{5+} -ге көшу), сондай-ақ әртүрлі валенттік күйлердегі Мо және Cr біріккен фазалары пайда болатыны анықталды.

Түйін сөздер: табиғи сазбалшық, ацетон, .

УДК 544.478

Б.К. Масалимова 1 , Д.Т. Алтынбекова 1 , Г.Д. Джетписбаева 1 , С.М. Наурузкулова 1 , Э.Е. Бақытжан 1 , А.К. Сапи 1 , В.А. Садыков 2,3

¹Таразский государственный университет им.М.Х. Дулати, Тараз, Казахстан; ²Новосибирский государственный университет, Новосибирск, Россия; ³Институт катализа им. Г.К.Борескова

СЖИЖЕННЫЙ НЕФТЯНОЙ ГАЗ КАК СЫРЬЕ ДЛЯ ПРОИЗВОДСТВА ЖИДКИХ КИСЛОРОДСОДЕРЖАЩИХ ОРГАНИЧЕСКИХ СОЕДИНЕНИЙ

Аннотация. Проведены исследования по окислительному превращению пропан-бутановой смеси в кислородсодержащие компоненты, а также определены оптимальные температуры, пропорции исходных компонентов, содержание активной фазы носителя и объемные скорости процесса. Были проведены физико-химические исследования исходных и обработанных катализаторов в условиях эксперимента. Было обнаружено, что при изменении содержание активных фаз в носителе от 1 до 10%, наиболее эффективным катализатором является 5% MoCrGa/TГ, при котором было получено 22% ацетона. В результате варьирования состава катализатора, содержания активной фазы, соотношения реагентов, было получено до 35-40% ацетона. Кроме того, в некоторых случаях были получены CH_3OH с максимальным выходом 22%, а также 35% метилэтилкетона. В результате исследований 3M и 2M и 2M было показано, что в условиях реакции на поверхности катализатора образуется новая фаза 2M0 (соответствующая переходу 2M1 и 2M2 в 2M3 и 2M3 гакже совместные фазы 2M4 и 2M5 в 2M5, а также совместные фазы 2M6 и 2M8 в 2M9 и 2M9

Ключевые слова: природная глина, ацетон.

Information about authors:

Massalimova Bakytgul Kabykenovna – candidate of chemical sciences, associated professor, manager of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz state university, e-mail: massalimova15@mail.ru ORCID ID https://orcid.org/0000-0003-0135-9712;

Altynbekova Dinara Tansykovna - PhD student of 6D060600- Chemistry of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz State University, e-mail: altynbekova.1985@inbox.ru;

Jetpisbayeva Gulim Danebaevna - PhD student of 6D060600- Chemistry of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz State University, e-mail: gulim_86@mail.ru;

Naurzkulova Symbat Muratbekovna- PhD student of 6D060600- Chemistry of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz State University, e-mail: simbat_3@mail.ru;

Bakytzhan Elbira Esengalikyzy – master student of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz State University. e-mail: ataqojaeva aigul@tarmpu.kz;

Sapi Aruzhan Kanatkyzy – 2nd year student of the department of "Chemistry and chemical technology", M.Kh. Dulaty Taraz state university. e-mail: sapievaaas@mail.ru;

Sadykov Vladislav Aleksandrovich - doctor of chemical sciences, professor, Novosibirsk State University, Institute of Catalysis named after G.Boreskov. E-mail: sadykov@catalysis.ru

REFERENCES

- [1] X.Li, J.Zhao, W.Ji, Zh.Zhang, Y.Chen et. al. (2006) Effect of vanadium substitution in the cesium salt of Keggin-type heteropolyacids on propane partial oxidation. J. Catal. .237:58-66.
- [2] J.Xu, B.L.Mojet, J.G.Ommen, and L.Lefferts. (2005) Effect of Brönsted acidity in the mechanism of selective oxidation of propane to acetone on CaY zeolite at room temperature. J. Catal. 232:411-423.
- [3] Zakarina N, Volkova L, Kim A, Akulova G, Chanysheva I, Latypov I, Grigorieva V. (2010) Industry of Kazakhstan, 6:83-85.
- [4] Tungatarova S.A., Xanthopoulou G., Kaumenova G.N., Zhumabek M., Baizhumanova T.S., Grigorieva V.P., Komashko L.V., Begimova G.U. (2018) Development of composite materials by combustion synthesis method for catalytic reforming of methane to synthesis gas. N E W sof the national academy of sciences of the republic of kazakhstan serieschemistry and technology ISSN 2224-5286 https://doi.org/10.32014/2018.2518-1491.20 Volume 6, Number 432 (2018), 6 15. (in Eng).

[5] Baizhumanova T.S., Tungatarova S.A., Xanthopoulou G., Zheksenbaeva Z.T., Kaumenova G.N., Erkibaeva M.K., Zhumabek M., Kassymkan K. (2018) Catalytic conversion of methane into olefins. N E W sof the national academy of sciences of the republic of kazakhstan serieschemistry and technology ISSN 2224-5286 https://doi.org/10.32014/2018.2518-1491.17 Volume 5, Number 431 (2018), 132 – 138542.973.7; 547.211. (in Eng).

- [6] N.A. Zakarina, N.A. Kornaukhova, R. Toktassyn. (2019) Pt- and Pd-catalysts on modified kaolinites in the reaction of n-hexane isomerization. N E W S of the national academy of sciences of the republic of kazakhstan series chemistry and technology. ISSN 2224-5286. https://doi.org/10.32014/2019.2518-1491.7. Volume 1, Number 433 (2019), 47 56. (in Eng).
- [7] A.K. Bayeshova, S.Molaigan, A.B. Bayeshov (2018) Hydrogen energetics current state and hydrogen production methods. N E W S of the national academy of sciences of the republic of kazakhstan series chemistry and technology. № 5. 2018 107 ISSN 2224-5286 https://doi.org/10.32014/2018.2518-1491.14. Volume 5, Number 431. P.107 116. (in Eng).
- [8] Dosumov K, Tungatarova SA, Kuzembaev KK, Masalimova BK (2005) Oxidative C3-C4 hydrocarbon conversion to olefins and oxygen-containing compounds in the presence of molybdenum and tungsten polyoxometalates, Petroleum Chemistry, 45:261-263. (in Eng).
 - [9] Massalimova B.K. (2019) Partial oxidation C3-C4 hydrocarbons. Kazakhstan. ISBN 978-601-7300-69-2. (in Kaz).
 - [10] Massalimova B.K. (2019) Partial oxidation C3-C4 hydrocarbons. Kazakhstan. ISBN 978-601-7300-69-2.
- [11] Tungatarova S.A., Xanthopoulou G., Kaumenova G.N., Zhumabek M., Baizhumanova T.S., Grigorieva V.P., Komashko L.V., Begimova G.U. (2018) Development of composite materials by combustion synthesis method for catalytic reforming of methane to synthesis gas. News of the NAS RK. Series chemistry and technology 432:6–15. https://doi.org/10.32014/2018.2518-1491.20 (in Eng)
- [12] Baizhumanova T.S., Tungatarova S.A., Xanthopoulou G., Zheksenbaeva Z.T., Kaumenova G.N., Erkibaeva M.K., Zhumabek M., Kassymkan K. (2018) Catalytic conversion of methane into olefins News of the NAS RK. Series chemistry and technology 431:132 138542.973.7; 547.211. https://doi.org/10.32014/2018.2518-1491.17 (in Eng)
- [13] Dosumov K., Tungatarova S.A., Kuzembaev K.K., Masalimova B.K. (2005) Oxidative C3-C4 hydrocarbon conversion to olefins and oxygen-containing compounds in the presence of molybdenum and tungsten polyoxometalates, Petroleum Chemistry, 45:261-263. (in Eng).
- [14] Massalimova B.K. (2016) Oxidative conversion of C3-C4 hydrocarbons over polycomponent oxide catalysts. XII International Conference on Reactors CHEMREACTOR-22, London, UK. PP.51. (In Eng.).
- [15] Arutyunov V.S., Strekova L.N. and Nikitin A.V. (2013). Partial Oxidation of Light Alkanes as a Base of New Generation of Gas Chemical Processes. Eurasian Chemico-Technological Journal15 (2013) 265-273.
- [16] Zakarina N, Volkova L, Kim A, Akulova G, Chanysheva I, Latypov I, Grigorieva V. (2010) Industry of Kazakhstan, 6:83-85
- [17] Tungatarova S.A, Xanthopoulou G, Kaumenova G.N, Zhumabek M, Baizhumanova T.S, Grigorieva V.P, Komashko L.V, Begimova G.U (2018) Development of composite materials by combustion synthesis method for catalytic reforming of methane to synthesis gas. News of the NAS RK. Series chemistry and technology, 432:6-15. https://doi.org/10.32014/2018.2518-1491.20 (in Eng).
- [18] Baizhumanova T.S, Tungatarova S.A, Xanthopoulou G, Zheksenbaeva Z.T, Kaumenova G.N, Erkibaeva M.K, Zhumabek M, Kassymkan K (2018) Catalytic conversion of methane into olefins. News of the NAS RK. Series chemistry and technology, 431:132–138542.973.7; 547.211. https://doi.org/10.32014/2018.2518-1491.17 (in Eng).
- [19] Zakarina N.A, Kornaukhova N.A, Toktassyn R (**2019**) Pt- and Pd-catalysts on modified kaolinites in the reaction of n-hexane isomerization. News of the NAS RK. Series chemistry and technology, 433:47-56. https://doi.org/10.32014/2019.2518-1491.7 (in Eng).
- [20] Bayeshova A.K, Molaigan S, Bayeshov A.B (2018) Hydrogen energetics current state and hydrogen production methods. News of the NAS RK. Series chemistry and technology, 431:107-116. https://doi.org/10.32014/2018.2518-1491.14 (in Fig.)

Publication Ethics and Publication Malpractice in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see http://www.elsevier.com/publishingethics and http://www.elsevier.com/journal-authors/ethics.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see http://www.elsevier.com/postingpolicy), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service http://www.elsevier.com/editors/plagdetect.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

www:nauka-nanrk.kz

http://chemistry-technology.kz/index.php/en/arhiv

ISSN 2518-1491 (Online), ISSN 2224-5286 (Print)

Редакторы: М. С. Ахметова, Т. А. Апендиев, Аленов Д.С. Верстка на компьютере А.М. Кульгинбаевой

Подписано в печать 05.06.2019. Формат 60х881/8. Бумага офсетная. Печать – ризограф. 5.7 п.л. Тираж 300. Заказ 3.