ҚАЗАҚСТАН РЕСПУБЛИКАСЫ ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Д.В.Сокольский атындағы «Жанармай, катализ және электрохимия институты» АҚ

ХАБАРЛАРЫ

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК РЕСПУБЛИКИ КАЗАХСТАН АО «Институт топлива, катализа и электрохимии им. Д.В. Сокольского»

NEWS

OF THE ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN JSC «D.V. Sokolsky institute of fuel, catalysis and electrochemistry»

SERIES CHEMISTRY AND TECHNOLOGY

6 (438)

NOVEMBER – DECEMBER 2019

PUBLISHED SINCE JANUARY 1947

PUBLISHED 6 TIMES A YEAR



NAS RK is pleased to announce that News of NAS RK. Series of chemistry and technologies scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of chemistry and technologies in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of chemical sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Химия және технология сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруда. Webof Science зерттеушілер, авторлар, баспашылар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Химия және технология сериясы Етегдіпд Sources Citation Index-ке енуі біздің қоғамдастық үшін ең өзекті және беделді химиялық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия химии и технологий» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по химическим наукам для нашего сообщества.

Бас редакторы х.ғ.д., проф., ҚР ҰҒА академигі **М.Ж. Жұрынов**

Редакция алкасы:

Ағабеков В.Е. проф., академик (Белорус)

Волков С.В. проф., академик (Украина)

Воротынцев М.А. проф., академик (Ресей)

Газалиев А.М. проф., академик (Қазақстан)

Ергожин Е.Е. проф., академик (Қазақстан)

Жармағамбетова А.К. проф. (Қазақстан), бас ред. орынбасары

Жоробекова Ш.Ж. проф., академик (Қырғыстан)

Иткулова Ш.С. проф. (Қазақстан)

Манташян А.А. проф., академик (Армения)

Пралиев К.Д. проф., академик (Қазақстан)

Баешов А.Б. проф., академик (Қазақстан)

Бүркітбаев М.М. проф., академик (Қазақстан)

Джусипбеков У.Ж. проф. корр.-мүшесі (Қазақстан)

Молдахметов М.З. проф., академик (Қазақстан)

Мансуров З.А. проф. (Қазақстан)

Наурызбаев М.К. проф. (Қазақстан)

Рудик В. проф., академик (Молдова)

Рахимов К.Д. проф. академик (Қазақстан)

Стрельцов Е. проф. (Белорус)

Тәшімов Л.Т. проф., академик (Қазақстан)

Тодераш И. проф., академик (Молдова)

Халиков Д.Х. проф., академик (Тәжікстан)

Фарзалиев В. проф., академик (Әзірбайжан)

«ҚР ҰҒА Хабарлары. Химия және технология сериясы».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Меншіктенуші: «Қазақстан Республикасының Ұлттық ғылым академиясы» Республикалық қоғамдық бірлестігі (Алматы қ.)

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде 30.04.2010 ж. берілген №1089-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік

Мерзімділігі: жылына 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18, http://chemistry-technology.kz/index.php/en/arhiv

© Қазақстан Республикасының Ұлттық ғылым академиясы, 2019

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Главный редактор д.х.н., проф., академик НАН РК **М. Ж. Журинов**

Редакционная коллегия:

Агабеков В.Е. проф., академик (Беларусь)

Волков С.В. проф., академик (Украина)

Воротынцев М.А. проф., академик (Россия)

Газалиев А.М. проф., академик (Казахстан)

Ергожин Е.Е. проф., академик (Казахстан)

Жармагамбетова А.К. проф. (Казахстан), зам. гл. ред.

Жоробекова Ш.Ж. проф., академик (Кыргызстан)

Иткулова Ш.С. проф. (Казахстан)

Манташян А.А. проф., академик (Армения)

Пралиев К.Д. проф., академик (Казахстан)

Баешов А.Б. проф., академик (Казахстан)

Буркитбаев М.М. проф., академик (Казахстан)

Джусипбеков У.Ж. проф. чл.-корр. (Казахстан)

Мулдахметов М.З. проф., академик (Казахстан)

Мансуров З.А. проф. (Казахстан)

Наурызбаев М.К. проф. (Казахстан)

Рудик В. проф., академик (Молдова)

Рахимов К.Д. проф. академик (Казахстан)

Стрельцов Е. проф. (Беларусь)

Ташимов Л.Т. проф., академик (Казахстан)

Тодераш И. проф., академик (Молдова)

Халиков Д.Х. проф., академик (Таджикистан)

Фарзалиев В. проф., академик (Азербайджан)

«Известия НАН РК. Серия химии и технологии».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Собственник: Республиканское общественное объединение «Национальная академия наук Республики

Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10893-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел. 272-13-19, 272-13-18,

http://chemistry-technology.kz/index.php/en/arhiv

© Национальная академия наук Республики Казахстан, 2019

Адрес редакции: 050100, г. Алматы, ул. Кунаева, 142,

Институт органического катализа и электрохимии им. Д. В. Сокольского,

каб. 310, тел. 291-62-80, факс 291-57-22, e-mail:orgcat@nursat.kz

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

SERIES CHEMISTRY AND TECHNOLOGY

ISSN 2224-5286

https://doi.org/10.32014/2019.2518-1491.78

Volume 6, Number 438 (2019), 86 – 98

UDC 550.42:004.89

R.Z. Safarov¹, Zh.K. Shomanova², R.Zh. Mukanova², Yu.G. Nossenko³, A. Ilies⁴, A.K. Sviderskii², N. Sarova⁵

¹L.N. Gumilyov Eurasian National University, Nur-Sultan, Kazakhstan;
 ²Pavlodar State Pedagogical University, Pavlodar, Kazakhstan;
 ³Innovative University of Eurasia, Pavlodar, Kazakhstan;
 ⁴University of Oradea, Oradea, Romania;
 ⁵ Kazakh National Medical University named after D. S. Asfendiyarov, Kazakhstan e-mail: ruslanbox@yandex.ru

DESIGN OF NEURAL NETWORK FOR FORECAST ANALYSIS OF ELEMENTS-CONTAMINANTS DISTRIBUTION ON STUDIED TERRITORIES (ON EXAMPLE OF PAVLODAR CITY, KAZAKHSTAN)

Abstract. In the article we are presenting results of development appropriate method including neural network for creating predictive map of elements-contaminants distribution (on example of Cr) on the territory of Pavlodar city (Kazakhstan). Obtained method allows to get widen data. The data from 15 points were spread out into 500 points. The average relative error at verification process was 9.45%. Architecture of well working model of neural network is perceptron with one input neuron, which takes values of distances between given point and several nearest points, 10 hidden neurons, and 1 output neuron, which gives value of element concentration in specified point. Obtained data were used in QGIS for creation of IDW interpolated map, which visualizes the information about concentration distribution.

Keywords: neural network, contaminants, distribution, forecasting, modelling, GIS, environmental.

1. Introduction

The search for ways of solving environmental problems and developing scientific methodological approaches to studying the complex consequences of the anthropogenic activities of enterprises involves the study of the ecological state of the region [1–3]. Environmental researches now have special significance because environmental safety and rational use of nature resources are the most important factors, determinant prospective of successful development of economics and social sphere.

The Pavlodar city is the large industrial city on the North of Kazakhstan. It is known, that the main sources of environment contamination of the city and Pavlodar region are different waste of chemical-technological processes [4]. These can be products of related processes and by-reactions not used in subsequent processes. Also, it can be intermediates of reactions and polymerization processes, filer materials, industrial waste water, not reacted gases (Cl₂, NH₃ etc.) [5, 6]. Moreover, environmental contamination occurs as a consequence of mechanical losses of raw material and products due to leakages from equipment and communications. Effect of every kind of contaminant directly depends on its physical-chemical properties. Many gaseous chemicals can react in atmosphere with water vapor, oxygen, as well be affected under radiation converting into other more toxic substances.

Finding of borders of studied territory and identification of danger sources leading to damage are an initial and important stage in the process of assessment of environmental risks. A new approach in this field is to assess impact of factors affecting the environment of region through analysis of territorial distribution of contaminants with creation of maps. Map allows visualizing of effects of contaminants, to understand origin sources of the contaminants, to predict ways of distribution and meanings for prevention of negative consequences from various factors.

In the article we are describing a new approach for creating such kinds of maps using methods of computer modelling, in particular neural network. New ways of data analysis allow to obtain new generated data and are often used for solving problems when it is required to expand weak analytical data and get on output full picture of demanded information [7–9].

Neural network receives input information and analyses it in the way analogous to our brain. During the analysis network is trained (generates some new knowledge) and gives a new output information based on previous experience [10–12]. The main task of analyst using neural network for solving some problem is to design the most effective architecture of network. Namely, correctly choose the sort of neural network, algorithm of training, number of neurons and kinds of relations between them. This work has no formalized procedures and requires deep understanding of different architectures of neural networks, it includes lots of research and analytical work and can take quite much time [13–15]. The most common usages of neural networks are:

- classification allocation of data by parameters;
- forecasting possibility to predict following steps;
- recognition determination of objects in a stack.

The computational item of neural network is neuron. It receives an information, makes simple calculations with it and pass it later. There are three types of neurons with specified functions – input, hidden and output. The principal scheme of simple neural network with two input neurons, two hidden and one output neuron is shown on the figure 1.




Figure 1 - The scheme of simple neural network

"W" on the figure are "weights", which are parameters of the network. They are adjusted during the training stage for the network could be able to give correct values. In our work we use neural network for forecasting of distribution of elements-contaminants on the studied territory. The forecast is based on the data obtained with x-ray spectral elemental analysis of the soil samples taken from given locations. The aim of the work was to design appropriate model of neural network for obtaining at least 500 predicted values of element concentrations in 500 given coordinates on the territory of Pavlodar city.

2. Methods and materials

2.1 Sampling of soil

Sampling was carried out for estimation of quality and quantity analysis of elemental content of soils on the territory of Pavlodar city. Sampling was carried out according to requirements of conventional documents "GOST 17.4.4.02-84. Nature protection. Soils. Methods for sampling and preparation of soil for chemical, bacteriological, helmintological analysis", "GOST 17.4.3.01-83. Nature protection. Soils. General requirements for sampling", "GOST 5180-84. Soils. Laboratory methods for determination of physical characteristics". The positions of sampling sites are shown on the figure 2 and specified in the table 1.




Figure 2 - Locations of sampling sites on the territory of Pavlodar city

Table 1 – Coordinates of positions of sampling sites

Number of sample	Name	X	Y
1	Lesozavod 1	76.919125	52.313194
2	Lesozavod 2	76.9083333333	52.307777778
3	Constitution square 1	76.9338888889	52.2966666667
4	Constitution square 2	76.9367	52.2989166667
5	CHP2 1 (TEC2 1)	76.9630916667	52.3196361111
6	CHP2 2 (TEC2 2)	76.9625833333	52.3125277778
7	Zhayau Musa str. 1	76.9673194444	52.249755556
8	Zhayau Musa str. 2	76.9707611111	52.2516555556
9	Railway Station 1	76.9552861111	52.3018861111
10	Railway Station 2	76.9570277778	52.235275
11	Narkodispancer 1	76.9926	52.2906138889
12	Narkodispancer 2	76.9894055556	52.290475
13	Gulliver TH 1	76.96925	52.2695777778
14	Gulliver TH 2	76.9688638889	52.27085
15	PNCP 1	76.9285722222	52.3449916667
16	PNCP 2	76.9279916667	52.3448638889
17	Usolka riv. 1	76.942475	52.250355556
18	Usolka riv. 2	76.9501694444	52.2471638889
19	Lermontov str. 1	76.9636111111	52.2913888889
20	Lermontov str. 2	76.9553111111	52.2911972222
21	PTP 1	76.9619861111	52.324255556
22	PTP 2	76.962475	52.3243888889
23	Satpayev str. 1	76.936725	52.292625
24	Satpayev str. 2	76.938175	52.3009916667
25	Naberezhnaya str. 1	76.9345222222	52.2815777778
26	Naberezhnaya str. 2	76.9375833333	52.2833
27	Mir str. 1	76.9444111111	52.2990027778
28	Mir str. 2	76.9447	52.2991111111
29	Toraigyrov str. 1	76.9552861111	52.2959166667
30	Toraigyrov str. 2	76.9594861111	52.2958333333

^{*} Coordinate system EPSG:4326 - WGS 84 - Geographic

2.2 Elemental analysis of soil samples

The catalyst samples were studied on a low-vacuum scanning electron microscope with a thermal emission cathode (LaB6) JSM-6610LV from JOEL. The device is equipped with an energy dispersive microanalysis system (EDM), a wave dispersive microanalysis system, a backscattered electron diffraction analysis system with a reflected electron detector, an Everhart-Thornley secondary electron detector, a low-vacuum secondary electron detector and sample preparation equipment. Elemental analysis was performed using energy dispersive x-ray fluorescence spectroscopy on an energy dispersive microanalysis system INCA Energy 450. Spectra were obtained three times with the calculation of the average value.

2.3 Neural network designing

For creation of neural network Brain.js library was used. Brain.js is an opened JavaScript library that allows implementation of neural networks with different architectures right in the browser or with using Node.js. Simple browser program was prepared for implementation of developed neural net. The program allows to input initial data for training, verification and forecasting from text file with data written in CSV-like manner, columns are divided with commas. Moreover, average relative divergence is calculated after verification process, as well diagram of convergence of forecast with original data is created automatically using the Graph.js library. Using neural network based on initial data about element concentration from 30 input points, 500 points were predicted after calculations. These 500 points were used for plotting on the map.

2.4 Creating of element distribution map

Free geographic information system with open code QGIS 3.8.3-Zanzibar was used. QGIS is an open source, user-friendly geographic information system (GIS) distributed under the GNU General Public License. QGIS is a project of the Open Source Geospatial Foundation (OSGeo). It works on Linux, Unix, Mac OSX, Windows and Android, supports many vector and raster formats, databases and has many features. Input data were added as a layer with coordinate system EPSG:4326 - WGS 84 – Geographic. For better visualization of information data analysis with IDW interpolation method has been implemented. In the IDW (Inverse Distance Weighting) interpolation method, the sample points are weighted during interpolation such that the influence of one point relative to another declines with distance from the unknown point you want to create [16, 17]. The figure 3 demonstrates the principle of the IDW method.




Figure 3. Inverse Distance Weighted interpolation based on weighted sample point distance (left).

Interpolated IDW surface from elevation vector points (right).

(Image Source: Mitas, L., Mitasova, H. (1999),

url: https://docs.qgis.org/2.18/en/docs/gentle gis introduction/spatial analysis interpolation.html)

Interpolation was visualized as a gradient of colors, monochannel pseudocolor mode of image was used. For map of chromium distribution following table of color distribution in dependence on concentration was assigned (table 2).

Table 2 – Distribution of colors in dependence on concentration in the method of interpolation visualization

Threshold concentration, %	Color	Color name	RGB color
0.00326683		blue	43,131,186
0.082261464		green	171,221,164
0.161256098		yellow	255,255,191
0.240250732		orange	253,174,97
0.319245366		red	215,25,28

3. Results and discussion

When we are describing distribution of concentrations of elements on the territory, practically we have to consider the data in three-dimensional space, where X and Y represent coordinates and Z is a third parameter – concentration in our case. Thus, we have to find the dependence between coordinates and concentration. First approach for creation of neural net, which could reveal that dependence is to give into input layer two parameters X and Y and get from output layer the value of concentration. In order to try the effectivity of developed neural network we have to find appropriate model with similar parameters. The convenient, simple and available model is some picture in gray scale. In this case a picture has its X and Y coordinates, when we are considering it as a matrix of pixels, and graduation of gray color is similar to concentration. Graduation of gray color lies in the range from 0 to 255 in RGB scheme [18].

So, the first picture we have chosen is quite simple and has dense relatively uniform sites of different shades of gray color (figure 4).



Figure 4 - Model image N = 1 for development of neural network

For this model we have taken 35 points as training data. The architecture of neural network included 2 neurons of input layer (X, Y coordinates), 3 hidden layers with 10, 20 and 4 neurons accordingly, 1 neuron on output layer (figure 5).




Figure 5 - Architecture of neural network model №1

Activation function was used sigmoid (1), because this function is widely used for neural networks aimed in prediction some values between 0 and 1 [19–22]. Graphical represent of the sigmoid function is showed on the figure 6.




Figure 6 - Curve of sigmoid function

Using neural network model №1 after training we have obtained forecast for 10 points with average relative error 13.35%. The diagram of convergence of predicted data with original data is presented on the figure 7.




Figure 7 - The diagram of convergence of predicted data with original data on the neural network model №1 (x axis – number of verify point, y axis – shade of gray color in RGB)

Thus, neural network model 1 has shown good results with the first picture, so we have tried to use it with the second picture, which is more complicated and more similar to landscape distribution of some parameter: height, depth or may be the concentration of some element (figure 8). This picture is in the gray scale as well.




Figure 8 - Model image №2 for development of neural network

With the second model picture and using the previous architecture of neural network we have obtained the value of average relative error 20.49%. The diagram of convergence of predicted data with original data is presented on the figure 9.




Figure 9 - The diagram of convergence of predicted data with original data on the neural network model №1 with picture 2 (x axis – number of verify point, y axis – shade of gray color in RGB)

On the diagram we can see that convergence in this case is much lover. Thus, it can be concluded, that the model No1 of neural network is appropriate just for simple characters of parameter distribution. That is why we are developed the second model of neural network and changed the approach for data analysis.

In the second model we used the interpolation method IDW for obtaining of demanded parameter value [23, 24]. But the calculations were made by neural network. This architecture has one neuron on input layer, which receives the values of distances between demanded point and each of 3 closest point. The distances were calculated by formula (2)

$$D = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}$$

$$= 92 = -$$

In accordance to this approach we have to get training data for each demanded point and train neural network for every point to prediction. However, taking into account the fact that training data contain only 3 input values it allows to simplify the model of neural network itself, so the second model of neural network has 1 neuron in input layer, 10 neurons in single hidden layer, and 1 output neuron. On the figure 10 we can see the convergence diagram for this case with picture $\mathbb{N}2$.




Figure 10 - The diagram of convergence of predicted data with original data on the neural network model №2 with picture 2 (x axis – number of verify point, y axis – shade of gray color in RGB)

In this situation we have obtained the value of average relative error 4.97% unless the picture was more complicated. Thus, this model of neural network was selected for using in analysis of concentration distribution of elements-contaminants on the studied territory.

Content of Cr in soils of studied territory was estimated using X-ray spectral microanalysis (table 3). These data were given into input of the neural network for training. On the figure 11 we can see the convergence diagram for verification process using model of neural network №2. The value of average relative error was 9.45%.

Number of samples	X	Y	C, %
1	76.919125	52.313194	0.71
2	76.9083333333	52.307777778	0.25
3	76.933888889	52.2966666667	0.25
4	76.9367	52.2989166667	0.19
5	76.9630916667	52.3196361111	0.13
6	76.9625833333	52.3125277778	0.3
7	76.9673194444	52.249755556	0.15
8	76.9707611111	52.2516555556	0.03
9	76.9552861111	52.3018861111	0.05
10	76.9570277778	52.235275	0.15
11	76.9926	52.2906138889	0.06
12	76.9894055556	52.290475	0.06
13	76.96925	52.2695777778	0.31
14	76.9688638889	52.27085	0.30
15	76.9285722222	52.3449916667	0.06

Table 3 – Data on Cr content in soils from sample sites 1-15 obtained using X-ray spectral microanalysis

^{*} Coordinate system EPSG:4326 - WGS 84 - Geographic




Figure 11 - The diagram of convergence of predicted data with original data on the neural network model №2 with data on Cr content in soils (x axis – number of verify point, y axis – concentration of Cr, %)

For prediction we have taken 500 points according to map represented on the figure 12. The batch process was performed with creation of prediction for every of 500 points. The obtained data with forecast of Cr distribution was plotted on the map in QGIS software. IDW interpolation was used in order to visualize the character of concentration distribution. The obtained interpolated map is represented on the figure 13. From the map it can be seen the large site with higher content of Cr. It is not necessary mean that the level exceeds the MPC level, but it gives the information about areas with higher and lower levels of the metal content. Control about MPC levels was not aimed in this research.



Figure 12 - Points where concentrations were calculated based on developed model of neural network



Figure 13 - Map of Cr concentration distribution in soils of Pavlodar city obtained on the basis of calculations of neural network model №2

Conclusion

Thus, during this work two models of neural network were developed. The method of calculating "point by point" using IDW approach and neural network №2 allows to predict complicatedly distributed data, which are usual when we are considering various geographical data: geochemistry, chemistry of environment, geology etc. That complexity is due to territorial distribution is influenced with many factors in very complex dependences. Using the developed method, it was possible to obtain 500 predicted points with values of chromium concentration on the different sites on the territory of Pavlodar city. The developed method allows to diminish level of error up to 9.45% (average relative error). The calculated data were inputted as a layer in QGIS. Based on the layer a new interpolated layer was created using IDW method. Thus, the colored map of chromium distribution on the territory of Pavlodar city was obtained in GIS. It allows to scale the map, get, print and save various views of the map.

Acknowledgments

The research work has been carried out in the frame of the project AP05134022 granted by Ministry of Education and Science of Republic of Kazakhstan.

УДК 550.42:004.89

Р.З. Сафаров¹, Ж.К. Шоманова², Р.Ж. Муканова², Ю.Г. Носенко³, А. Илиеш⁴, А.К. Свидерский², Н.Б. Сарова⁵

¹ Л.Н. Гумилев атындағы Еуразия ұлттық университеті, Нұрсұлтан, Қазақстан
 ²Павлодар мемлекеттік педагогикалық университеті, Павлодар, Қазақстан
 ³ Инновациялық Еуразия университеті, Павлодар, Қазақстан
 ⁴Орадя университеті, Орадя, Румыния
 ⁵С.Ж. Асфендияров атындағы Қазақ ұлттық медицина университеті, Қазақстан

ЗЕРТТЕЛЕТІН АУМАҚТАРДА ЛАСТАУШЫ ЭЛЕМЕНТТЕРДІҢ ТАРАЛУЫН БОЛЖАМДЫҚ ТАЛДАУ ҮШІН НЕЙРОНДЫҚ ЖЕЛІНІ ӘЗІРЛЕУ (ПАВЛОДАР ҚАЛАСЫ МЫСАЛЫНДА, ҚАЗАҚСТАН)

Аннотация: Осы мақалада біз Павлодар қаласының аумағында (Қазақстан) ластаушы элементтердің (мысалы, Ст) таралуының болжамдық картасын жасау үшін нейрондық желіні қолданудың тиімді әдісін жасау нәтижелерін ұсынамыз. Әзірленген әдіс кеңейтілген деректерді алуға мүмкіндік береді. 15 нүкте бойынша деректер 500 нүктеде масштабталды. Верификация процесінің орташа салыстырмалы қателігі 9,45% құрайды. Нейрондық желінің жұмыс моделінің архитектурасы берілген нүкте мен бірнеше жақын нүктелер арасындағы қашықтықтың мәндерін қабылдайтын бір кіріс нейронымен перцептронды, жасырын қабаттың 10 нейронын және берілген нүктеде элементтің концентрациясының мәнін беретін 1 шығыс нейронды білдіреді. Алынған деректер концентрацияның таралуы туралы ақпаратты бейнелейтін IDW интерполяцияланған картасын құру үшін QGIS-те қолданылды.

Түйін сөздер: нейрондық желі, ластағыштар, бөлу, болжау, модельдеу, ГАЖ, экологиялық.

УДК 550.42:004.89

Р.З. Сафаров¹, Ж.К. Шоманова², Р.Ж. Муканова², Ю.Г. Носенко³, А. Илиеш⁴, А.К. Свидерский², Н.Б. Сарова⁵

¹Евразийский национальный университет им. Л.Н. Гумилева, Нур-Султан, Казахстан ²Павлодарский государственный педагогический университет, Павлодар, Казахстан ³Инновационный Евразийский университет, Павлодар, Казахстан ⁴Орадя университет, Орадя, Румыния ⁵Казахский национальный медицинский университет им. С.Ж. Асфендиярова, Казахстан

РАЗРАБОТКА НЕЙРОННОЙ СЕТИ ДЛЯ ПРОГНОСТИЧЕСКОГО АНАЛИЗА РАСПРЕДЕЛЕНИЯ ЭЛЕМЕНТОВ-ЗАГРЯЗНИТЕЛЕЙ НА ИССЛЕДУЕМЫХ ТЕРРИТОРИЯХ (НА ПРИМЕРЕ ГОРОДА ПАВЛОДАР, КАЗАХСТАН)

Аннотация. В данной статье мы представляем результаты разработки эффективного метода с использованием нейронной сети для создания прогностической карты распределения элементов-загрязнителей (на примере Cr) на территории г. Павлодар (Казахстан). Разработанный метод позволяет получать расширенные данные. Данные по 15 точкам были масштабированы в 500 точек. Средняя относительная погрешность процесса верификации составляет 9,45

%. Архитектура рабочей модели нейронной сети представляет собой перцептрон с одним входным нейроном, который принимает значения расстояний между заданной точкой и несколькими ближайшими точками, 10 нейронов скрытого слоя и 1 выходной нейрон, который выдает значение концентрации элемента в заданной точке. Полученные данные использовались в QGIS для создания IDW интерполированной карты, которая визуализирует информацию о концентрационном распределении.

Ключевые слова: нейронная сеть, загрязнители, распределение, прогнозирование, моделирование, ГИС, экологический.

Information about authors:

Ruslan Zairovich Safarov – candidate of chemical sciences, Associate Professor of the Department of Management and Engineering in the field of environmental protection, L.N. Gumilyov Eurasian national university, ruslanbox@yandex.ru, https://orcid.org/0000-0003-2158-6330

Zhanat Kairollinovna Shomanova – doctor of technical sciences, professor of the Geography and chemistry department, Pavlodar state pedagogical university, zshoman@yandex.ru, https://orcid.org/0000-0001-8346-9688

Roza Zhumkenovna Mukanova - candidate of chemical sciences, Head of the Department of Geography and Chemistry, Pavlodar state pedagogical university, rozam14@mail.ru, https://orcid.org/0000-0001-9517-7359

Yuri Gennadievich Nossenko - candidate of chemical sciences, Innovative University of Eurasia, nosenko1980@yandex.ru, https://orcid.org/0000-0002-2491-7337

Alexandru Ilieş - Doctor of geography, professor, Dean of the Faculty of Geography, Tourism and Sport, University of Oradea, ilies@uoradea.ro, https://orcid.org/0000-0002-5920-5858

Aleksander Konstantinovich Sviderskiy - Doctor of Chemical Sciences, professor, Vice-rector for Research and International Relations, Pavlodar state pedagogical institute, katsostud@rambler.ru, https://orcid.org/0000-0001-5006-879X

Sarova Nurbanu – candidate of chemical sciences, Kazakh National Medical University named after D. S. Asfendiyarov, School of pharmacy. Lecturer, Department of Chemistry. nurbanu@mail.ru, https://orcid.org/0000-0002-7541-2224

REFERENCES

- [1] Ramazanova N, Berdenov ZG, Ramazanov S, Kazangapova N, Romanova S, Toksanbaeva S, Wendt J. (2019). Landscape-geochemical analysis of steppe zone basin Zhaiyk. News of National Academy of Sciences of the Republic of Kazakhstan, 4(436):33–41. DOI:10.32014/2019.2518-170x.95(in Eng)
- [2] Wu J, Lu J, Li L, Min X, Zhang Z, Luo Y. (2018). Distribution, pollution, and ecological risks of rare earth elements in soil of the northeastern Qinghai–Tibet Plateau. Human and Ecological Risk Assessment, 25(7):1–16. DOI:10.1080/10807039.2018.1475215 (in Eng)
- [3] Wu S, Liang Z, Liu Y. (2019). Quantifying the risk of irreversible degradation for ecosystems: A probabilistic method based on Bayesian inference. Ecological Indicators, 107:105621. DOI:10.1016/j.ecolind.2019.105621 (in Eng)
- [4] Mazhitova GZ, Janaleyeva KM, Berdenov ZG, Doskenova BB, Atasoy E. (2018). Assessment of the sustainability of landscapes of the North-Kazakhstan region to agricultural impact. News of The National Academy of Sciences of The Republic of Kazakhstan-Series of Geology and Technical Sciences, (3):90–95. (in Eng)
- [5] Shomanova ZK, Safarov RZ, Auezhanova A, Zhumakanova AS, Nosenko YG, Tleulesov AK, Larichkin VV. (2017). Study of Composite Catalysts Containing Sludge of Ferroalloy Production in the Process of Cyclohexane Oxidation. News of the National Academy of Sciences of the Republic of Kazakhstan, Series of Chemistry and Technology, 426(6):55–61. (in Eng)
- [6] Khodorov EI, Kvasha VB. (1996). Some problems in the quantitative estimation of the degree of no-waste production (cleanness) of chemical plants. Fibre Chemistry, 28(3):195–202. DOI:10.1007/BF01053569 (in Eng)
- [7] Suleymenov IE, Sedlakova ZZ, Kopishev EE. (2019). New Polymer Materials for Optical Sensor Systems. Journal of Inorganic and Organometallic Polymers and Materials, 29(3):758–764. DOI:10.1007/s10904-018-1049-7 (in Eng)
- [8] Herman GV, Ilies DC, Gaceu O, Ilies A, Mester C, Ilies M, ... Dumitru M. (2019). Some considerations concerning the quality of groundwater in the Natura 2000 Lunca Barcaului (Barcaului Meadow) site, Romania. Journal of Environmental Protection and Ecology, 20(3):1102–1109. (in Eng)
- [9] Ilieş DC, Oneţ A, Wendt JA, Ilieş M, Timar A, Ilieş A, ... Herman GV. (2018). Study on microbial and fungal contamination of air and wooden surfaces inside of a historical Church from Romania. Journal of Environmental Biology, 39:980–984. DOI:10.22438/jeb/39/6/MRN-658 (in Eng)
- [10] Li H, Hu M, Huang Y. (2019). Automatic Identification of Overpass Structures: A Method of Deep Learning. ISPRS International Journal of Geo-Information, 8(9):421. DOI:10.3390/ijgi8090421 (in Eng)
- [11] Tran M-N, Nguyen N, Nott D, Kohn R. (2019). Bayesian Deep Net GLM and GLMM. Journal of Computational and Graphical Statistics, :1–17. DOI:10.1080/10618600.2019.1637747 (in Eng)
 - [12] Alver A, Kazan Z. (2020). Prediction of full-scale filtration plant performance using artificial neural networks based

- on principal component analysis. Separation and Purification Technology, 230:115868. DOI:10.1016/j.seppur.2019.115868 (in Eng)
- [13] Gao C, Feng G, Ren Y, Liu L. (2019). Iris Segmentation Based on Improved U-Net Network Model. IEICE Transactions on Fundamentals of Electronics, Communications and Computer Sciences, E102.A(8):982–985. DOI:10.1587/transfun.e102.a.982 (in Eng)
- [14] Suleimenov IE, Mun GA, Pak IT, Kabdushev SB, Kenessova ZA, Kopishev EE. (2017). Redistribution of the concentrations in polyelectrolyte hydrogels contacts as the basis of new desalination technologies. News of the National Academy of Sciences of the Republic of Kazakhstan, Series of Geology and Technical Sciences, 423(3):198–205. (in Eng)
- [15] Fukuhara M, Fujiwara K, Maruyama Y, Itoh H. (2019). Feature visualization of Raman spectrum analysis with deep convolutional neural network. Analytica Chimica Acta, 1087:11–19. DOI:10.1016/j.aca.2019.08.064 (in Eng)
- [16] Golla V, Arveti N, Etikala B, Sreedhar Y, Narasimhlu K, Harish P. (2019). Data sets on spatial analysis of hydro geochemistry of Gudur area, SPSR Nellore district by using inverse distance weighted method in Arc GIS 10.1. Data in Brief, 22:1003–1011. DOI:10.1016/j.dib.2019.01.030 (in Eng)
- [17] Vural A. (2019). Evaluation of soil geochemistry data of Canca Area (Gümüşhane, Turkey) by means of Inverse Distance Weighting (IDW) and Kriging methods-preliminary findings. Bulletin of the Mineral Research and Exploration, 158:195–216. DOI:10.19111/bulletinofmre.430531 (in Eng)
- [18] Martínez MÁ, Etchebehere S, Valero EM, Nieves JL. (2019). Improving unsupervised saliency detection by migrating from RGB to multispectral images. Color Research & Application, 44(6):875–885. DOI:10.1002/col.22421 (in Eng)
- [19] Tallón-Ballesteros AJ. (2019). Metaheuristic algorithm to train product and sigmoid neural network classifiers. Expert Systems, 36(3):e12383. DOI:10.1111/exsy.12383 (in Eng)
- [20] Elfwing S, Uchibe E, Doya K. (2018). Sigmoid-weighted linear units for neural network function approximation in reinforcement learning. Neural Networks, 107:3–11. DOI:10.1016/j.neunet.2017.12.012 (in Eng)
- [21] Tallón-Ballesteros AJ. (2016). Contemporary training methodologies based on evolutionary artificial neural networks with product and sigmoid neurons for classification. AI Communications, 29(3):469–471. DOI:10.3233/AIC-150681 (in Eng)
- [22] Tsai CH, Chih YT, Wong WH, Lee CY. (2015). A Hardware-Efficient Sigmoid Function with Adjustable Precision for a Neural Network System. IEEE Transactions on Circuits and Systems II: Express Briefs, 62(11):1073–1077. DOI:10.1109/TCSII.2015.2456531 (in Eng)
- [23] Borges RC, Mahler CF, Caldas VG, da Silva AP, Bernedo AVB. (2018). Mapping of the concentration of natural radionuclides in the Fundão Island, RJ, Brazil supported by geoprocessing and IDW interpolation. Environmental Earth Sciences, 77(17):603. DOI:10.1007/s12665-018-7795-6 (in Eng)
- [24] Madhloom HM, Al-Ansari N, Laue J, Chabuk A. (2017, December 22). Modeling spatial distribution of some contamination within the lower reaches of Diyala river using IDW interpolation. Sustainability (Switzerland). DOI:10.3390/su10010022 (in Eng)

Publication Ethics and Publication Malpractice in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see http://www.elsevier.com/publishingethics and http://www.elsevier.com/journal-authors/ethics.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see http://www.elsevier.com/postingpolicy), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service http://www.elsevier.com/editors/plagdetect.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайте:

www:nauka-nanrk.kz

http://chemistry-technology.kz/index.php/en/arhiv

ISSN 2518-1491 (Online), ISSN 2224-5286 (Print)

Редакторы: *М. С. Ахметова, Т. А. Апендиев, Аленов Д.С.* Верстка на компьютере *А.М. Кульгинбаевой*

Подписано в печать 05.12.2019. Формат 60х881/8. Бумага офсетная. Печать – ризограф. 5,25 п.л. Тираж 300. Заказ 6.

Национальная академия наук РК 050010, Алматы, ул. Шевченко, 28, т. 272-13-18, 272-13-19