

ISSN 2518-1491 (Online),
ISSN 2224-5286 (Print)

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

Д.В.СОКОЛЬСКИЙ АТЫНДАҒЫ «ЖАНАРМАЙ,
КАТАЛИЗ ЖӘНЕ ЭЛЕКТРОХИМИЯ ИНСТИТУТЫ» АҚ

Х А Б А Р Л А Р Ы

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН

АО «ИНСТИТУТ ТОПЛИВА, КАТАЛИЗА И
ЭЛЕКТРОХИМИИ ИМ. Д.В. СОКОЛЬСКОГО»

NEWS

OF THE ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN

JSC «D.V. SOKOLSKY INSTITUTE OF FUEL,
CATALYSIS AND ELECTROCHEMISTRY»

ХИМИЯ ЖӘНЕ ТЕХНОЛОГИЯ СЕРИЯСЫ



СЕРИЯ ХИМИИ И ТЕХНОЛОГИИ



SERIES CHEMISTRY AND TECHNOLOGY

5 (431)

**ҚЫРКҮЙЕК – ҚАЗАН 2018 ж.
СЕНТЯБРЬ – ОКТЯБРЬ 2018 г.
SEPTEMBER – OCTOBER 2018**

1947 ЖЫЛДЫҢ ҚАҢТАР АЙЫНАН ШЫҒА БАСТАҒАН
ИЗДАЕТСЯ С ЯНВАРЯ 1947 ГОДА
PUBLISHED SINCE JANUARY 1947

ЖЫЛЫНА 6 РЕТ ШЫҒАДЫ
ВЫХОДИТ 6 РАЗ В ГОД
PUBLISHED 6 TIMES A YEAR

NAS RK is pleased to announce that News of NAS RK. Series of chemistry and technologies scientific journal has been accepted for indexing in the Emerging Sources Citation Index, a new edition of Web of Science. Content in this index is under consideration by Clarivate Analytics to be accepted in the Science Citation Index Expanded, the Social Sciences Citation Index, and the Arts & Humanities Citation Index. The quality and depth of content Web of Science offers to researchers, authors, publishers, and institutions sets it apart from other research databases. The inclusion of News of NAS RK. Series of chemistry and technologies in the Emerging Sources Citation Index demonstrates our dedication to providing the most relevant and influential content of chemical sciences to our community.

Қазақстан Республикасы Ұлттық ғылым академиясы "ҚР ҰҒА Хабарлары. Химия және технология сериясы" ғылыми журналының Web of Science-тің жаңаланған нұсқасы Emerging Sources Citation Index-те индекстелуге қабылданғанын хабарлайды. Бұл индекстелу барысында Clarivate Analytics компаниясы журналды одан әрі the Science Citation Index Expanded, the Social Sciences Citation Index және the Arts & Humanities Citation Index-ке қабылдау мәселесін қарастыруда. Web of Science зерттеушілер, авторлар, баспашылар мен мекемелерге контент тереңдігі мен сапасын ұсынады. ҚР ҰҒА Хабарлары. Химия және технология сериясы Emerging Sources Citation Index-ке енуі біздің қоғамдастық үшін ең өзекті және беделді химиялық ғылымдар бойынша контентке адалдығымызды білдіреді.

НАН РК сообщает, что научный журнал «Известия НАН РК. Серия химии и технологий» был принят для индексирования в Emerging Sources Citation Index, обновленной версии Web of Science. Содержание в этом индексировании находится в стадии рассмотрения компанией Clarivate Analytics для дальнейшего принятия журнала в the Science Citation Index Expanded, the Social Sciences Citation Index и the Arts & Humanities Citation Index. Web of Science предлагает качество и глубину контента для исследователей, авторов, издателей и учреждений. Включение Известия НАН РК в Emerging Sources Citation Index демонстрирует нашу приверженность к наиболее актуальному и влиятельному контенту по химическим наукам для нашего сообщества.

Б а с р е д а к т о р ы
х.ғ.д., проф., ҚР ҰҒА академигі **М.Ж. Жұрынов**

Р е д а к ц и я а л қ а с ы:

Ағабеков В.Е. проф., академик (Белорус)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Ресей)
Газалиев А.М. проф., академик (Қазақстан)
Ергожин Е.Е. проф., академик (Қазақстан)
Жармағамбетова А.К. проф. (Қазақстан), бас ред. орынбасары
Жоробекова Ш.Ж. проф., академик (Қырғыстан)
Иткулова Ш.С. проф. (Қазақстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Қазақстан)
Баешов А.Б. проф., академик (Қазақстан)
Бүркітбаев М.М. проф., академик (Қазақстан)
Джусипбеков У.Ж. проф. корр.-мүшесі (Қазақстан)
Молдахметов М.З. проф., академик (Қазақстан)
Мансуров З.А. проф. (Қазақстан)
Наурызбаев М.К. проф. (Қазақстан)
Рудик В. проф., академик (Молдова)
Рахимов К.Д. проф. академик (Қазақстан)
Стрельцов Е. проф. (Белорус)
Тәшімов Л.Т. проф., академик (Қазақстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Тәжікстан)
Фарзалиев В. проф., академик (Әзірбайжан)

«ҚР ҰҒА Хабарлары. Химия және технология сериясы».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Меншіктенуші: «Қазақстан Республикасының Ұлттық ғылым академиясы» Республикалық қоғамдық бірлестігі (Алматы қ.)

Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде 30.04.2010 ж. берілген №1089-Ж мерзімдік басылым тіркеуіне қойылу туралы куәлік

Мерзімділігі: жылына 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,
www.nauka-nanrk.kz / chemistry-technology.kz

© Қазақстан Республикасының Ұлттық ғылым академиясы, 2018

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Главный редактор
д.х.н., проф., академик НАН РК **М. Ж. Журинов**

Редакционная коллегия:

Агабеков В.Е. проф., академик (Беларусь)
Волков С.В. проф., академик (Украина)
Воротынцев М.А. проф., академик (Россия)
Газалиев А.М. проф., академик (Казахстан)
Ергожин Е.Е. проф., академик (Казахстан)
Жармагамбетова А.К. проф. (Казахстан), зам. гл. ред.
Жоробекова Ш.Ж. проф., академик (Кыргызстан)
Иткулова Ш.С. проф. (Казахстан)
Манташян А.А. проф., академик (Армения)
Пралиев К.Д. проф., академик (Казахстан)
Баешов А.Б. проф., академик (Казахстан)
Буркитбаев М.М. проф., академик (Казахстан)
Джусипбеков У.Ж. проф. чл.-корр. (Казахстан)
Мулдахметов М.З. проф., академик (Казахстан)
Мансуров З.А. проф. (Казахстан)
Наурызбаев М.К. проф. (Казахстан)
Рудик В. проф., академик (Молдова)
Рахимов К.Д. проф. академик (Казахстан)
Стрельцов Е. проф. (Беларусь)
Ташимов Л.Т. проф., академик (Казахстан)
Тодераш И. проф., академик (Молдова)
Халиков Д.Х. проф., академик (Гаджикистан)
Фарзалиев В. проф., академик (Азербайджан)

«Известия НАН РК. Серия химии и технологии».

ISSN 2518-1491 (Online),

ISSN 2224-5286 (Print)

Собственник: Республиканское общественное объединение «Национальная академия наук Республики Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №10893-Ж, выданное 30.04.2010 г.

Периодичность: 6 раз в год

Тираж: 300 экземпляров

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел. 272-13-19, 272-13-18,
<http://nauka-nanrk.kz / chemistry-technology.kz>

© Национальная академия наук Республики Казахстан, 2018

Адрес редакции: 050100, г. Алматы, ул. Кунаева, 142,
Институт органического катализа и электрохимии им. Д. В. Сокольского,
каб. 310, тел. 291-62-80, факс 291-57-22, e-mail: orgcat@nursat.kz

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75

E d i t o r i n c h i e f

doctor of chemistry, professor, academician of NAS RK **M.Zh. Zhurinov**

E d i t o r i a l b o a r d :

Agabekov V.Ye. prof., academician (Belarus)
Volkov S.V. prof., academician (Ukraine)
Vorotyntsev M.A. prof., academician (Russia)
Gazaliyev A.M. prof., academician (Kazakhstan)
Yergozhin Ye.Ye. prof., academician (Kazakhstan)
Zharmagambetova A.K. prof. (Kazakhstan), deputy editor in chief
Zhorobekova Sh.Zh. prof., academician (Kyrgyzstan)
Itkulova Sh.S. prof. (Kazakhstan)
Mantashyan A.A. prof., academician (Armenia)
Praliyev K.D. prof., academician (Kazakhstan)
Bayeshov A.B. prof., academician (Kazakhstan)
Burkitbayev M.M. prof., academician (Kazakhstan)
Dzhusipbekov U.Zh. prof., corr. member (Kazakhstan)
Muldakhmetov M.Z. prof., academician (Kazakhstan)
Mansurov Z.A. prof. (Kazakhstan)
Nauryzbayev M.K. prof. (Kazakhstan)
Rudik V. prof., academician (Moldova)
Rakhimov K.D. prof., academician (Kazakhstan)
Streltsov Ye. prof. (Belarus)
Tashimov L.T. prof., academician (Kazakhstan)
Toderash I. prof., academician (Moldova)
Khalikov D.Kh. prof., academician (Tadjikistan)
Farzaliyev V. prof., academician (Azerbaijan)

News of the National Academy of Sciences of the Republic of Kazakhstan. Series of chemistry and technology.
ISSN 2518-1491 (Online),
ISSN 2224-5286 (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of Information and Archives of the Ministry of Culture and Information of the Republic of Kazakhstan N 10893-Ж, issued 30.04.2010

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,
<http://nauka-nanrk.kz/chemistry-technology.kz>

© National Academy of Sciences of the Republic of Kazakhstan, 2018

Editorial address: Institute of Organic Catalysis and Electrochemistry named after D. V. Sokolsky
142, Kunayev str., of. 310, Almaty, 050100, tel. 291-62-80, fax 291-57-22,
e-mail: orgcat@nursat.kz

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

SERIES CHEMISTRY AND TECHNOLOGY

ISSN 2224-5286

<https://doi.org/10.32014/2018.2518-1491.9>

Volume 5, Number 431 (2018), 67 – 73

UDC 541.128.665

**B.T. Tuktin, N.N. Nurgaliev A.S. Tenizbaeva,
L.B. Shapovalova, L.V. Komashko**

JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", Almaty, Kazakhstan
E-mail: tuktin_balga@mail.ru

HYDROTREATING OF VARIOUS PETROL FRACTIONS OVER MODIFIED ALUMOCOBALTMOLYBDBDENIC CATALYSTS

Abstract. The paper presents the results of a study of hydrotreating of various gasoline fractions (straight-run gasoline, catalytic cracking gasoline, coking gasoline) on alumo-cobalt-molybdenum catalysts modified with additives of zeolites ZSM-5 and HY, phosphorus and rare earth elements: CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-18); CoO-MoO₃-La₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-20) и CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM-HY (KGO-16).

The results obtained during the hydroprocessing of various types of gasoline on the catalyst KGO-18 show that the highest amount of isoalkanes is observed during the processing of catalytic cracking gasoline. In the catalyst obtained on the catalyst KGO-18 at 320-380°C 40,3-48,1% of isoalkanes were found, whereas when processing straight-run and gasoline coking, the content of isoalkanes is 34,0-39,7% and 33,9-37%. The octane number after hydrofining of straight-run gasoline and catalytic cracking gasoline is almost the same and is 90,7 and 90,5 (RM), respectively. In the case of coking gasoline, the octane number of fuel produced is lower than when processing other types of gasoline – 83,1 (MM). When studying the process of hydroprocessing of various gasoline fractions over the catalyst KGO-18, it was found that the highest degree of hydrodesulfurization is observed when processing coking gasoline – 87,3%, straight-run gasoline – 81,3% and catalytic cracking gasoline – 75,4%. Modified zeolite-containing alumo-cobalt-molybdenum catalysts for hydroprocessing gasoline fractions in one stage conduct hydrotreating, hydroisomerization, hydrogenation and allow to obtain low-sulfur high-octane gasoline.

Key words: zeolite, straight run gasoline, catalytic cracking gasoline, coking gasoline, catalyst, hydrotreatment.

Introduction

Different gasoline fractions of oil contain a significant amount of linear alkanes, which are characterized by low detonation resistance, which does not allow them to be used directly as motor gasoline. In the world production of motor gasoline, there is a constant tendency to increase the content of isoparaffins with high octane numbers and better ecological characteristics in comparison with aromatic hydrocarbons, limitations on the content of aromatic hydrocarbons, especially benzene ($\leq 1\%$), olefins and sulfur are provided.

To obtain high-quality motor fuels from sulphurous, paraffinic oils, the use of catalytic hydroprocessing processes is necessary: hydrotreatment, hydroisomerization, and hydrogenation. In this regard, the process of hydroisomerization is one of the methods for improving the performance characteristics of light gasoline fractions.

Toughening the requirements for the quality of motor fuels leads to the need for significant changes in available technologies for processing low-grade gasoline fractions using new high-performance catalysts. It is very promising to create one-stage technologies that allow one-stage hydrotreating, hydroisomerization and hydrogenation processes. Existing industrial catalysts for processing petroleum fractions do not meet the increased requirements for the quality of motor fuels. In this regard, the creation of new catalysts for directed single-stage hydroprocessing of oil and its fractions in high-quality fuel will remain an urgent task now and in the near future [1-20]. In this paper, we present the results of a study of the hydroprocessing of various gasoline fractions (straight-run

gasoline, catalytic cracking gasoline, coking gasoline) on alumo-cobalt-molybdenum catalysts modified with additives of zeolites ZSM-5 and HY, phosphorus and rare earth elements.

Experimental part

Zeolite-containing alumina catalysts were prepared. impregnation of a mixture of aluminum hydroxide and zeolites with aqueous solutions of cobalt, molybdenum and modifying additives. After molding, the catalyst was dried at 150°C and calcined at 550°C for 5 hours. Catalysts of the following compositions were prepared: CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-18); CoO-MoO₃-La₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-20) and CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM-HY (KGO-16).

Synthesized modified zeolite-containing catalysts were used to study the hydroprocessing of various types of gasoline. The process was carried out in a high-pressure flow unit with a stationary catalyst bed at temperatures of 320-400°C, a pressure of 4,0 MPa and a space feed rate of 2h⁻¹. The hydrocarbon composition of the reaction products was analyzed on chromatographs "Chromatec-Crystal" and "Chrom-5". Analysis of sulfur content in feedstock and products was carried out in LLP "Oilsert International" (Almaty) and laboratory of physico-chemical methods of "D.V. SokolskyIFCE".

Results and discussion

On the catalyst KGO-18, the process of hydroprocessing various types of gasoline was studied. Hydrogen processing of straight-run gasoline on KGO-18 catalyst showed that in the temperature range 320-350°C, the resulting catalyst contains 39,7-38,2% of isoalkanes (Table 1). At higher temperatures, the yield of isoalkanes decreases to 34,4% at 400°C. The amount of aromatic hydrocarbons in the catalyst under these conditions increases from 15,2 to 24,8%, the yield of naphthenic hydrocarbons decreases from 26,1 to 24,0%. The concentration of olefinic hydrocarbons varies within the range of 4,6-7,6%. The yield of hydro-upgraded gasoline decreases from 70,7 to 60,5% with increasing temperature from 320 to 400°C. The octane number of hydrotreated gasoline is increased compared with the original from 78,9 to 90,7 (MM) and by the motor method from 60,9 to 71,7. The sulfur content of the catalyst decreased from 0,0080 (reference gasoline) to 0,0015% with an increase in temperature to 400°C.

Table 1 - Effect of temperature on the process of hydroprocessing of straight-run gasoline on the catalyst KGO-18

Products, %	T°C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	27,3	11,4	15,1	12,5	12,2
Isoalkanes	36,8	39,7	38,2	34,0	34,4
Oleffin	4,8	7,6	5,6	5,4	4,6
Aromatic hydrocarbons	9,2	15,2	18,7	20,9	24,8
Naphthenic hydrocarbons	21,9	26,1	22,3	27,2	24,0
Yield of the liquid phase	-	70,7	68,3	65,0	60,5
The octane number for research method	78,9	82,6	84,9	88,1	90,7
Octane number by motor method	60,9	67,8	67,7	68,5	71,7
Mass fraction of sulfur, %	0,0080	0,0049	0,0026	0,0030	0,0015

Note: P = 4.0MPa, V = 2.0 h⁻¹

The results of a study of the hydroprocessing of catalytic cracked gasoline using the catalyst KGO-18 showed that with an increase in temperature from 320 to 400°C, the yield of liquid catalyst varies from 80,0 to 68,5% (Table 2). When hydrolyzing catalytic cracked gasoline on the catalyst KGO-18 at 320-350°C, the amount of isoalkanes increases from 25,4 to 42,6-48,1% in comparison with the initial one. The content of aromatic and naphthenic hydrocarbons varies from 30.1 to 36,1%, from 7,0 to 10,4%, respectively. The amount of olefinic hydrocarbons under these conditions drops sharply from 31,2 to 4,3-3,3%. The octane number of the With an increase in temperature from 350 to 400°C, the content of isoalkanes decreases to 39,9% (400°C). The yield of naphthenic and olefinic hydrocarbons under these conditions also decreases to 6,7 and 2,9%, respectively, the amount of aromatic hydrocarbons increases to 43,1%.

The octane number of the refined gasoline obtained at 400°C is 90,5 (RM) and 83,4 (MM). It should be noted that in gasoline hydro-enriched on catalyst KGO-18 at 320°C, the sulfur content is 0,0110% (in the initial 0,0134%), and at 400°C – 0,0033%, which indicates a sufficiently high hydrodesulfurizing activity of this catalyst, produced gasoline practically does not change.

Table 2 - Effect of temperature on the process of hydroprocessing of catalytic cracking gasoline on catalyst KGO-18

Products, %	T, °C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	6,3	6,9	8,2	7,3	7,4
Isoalkanes	25,4	42,6	48,1	40,3	39,9
Oleffin	31,2	4,3	3,3	3,4	2,9
Aromatichydrocarbons	30,1	36,1	30,0	40,3	43,1
Naphthenichydrocarbons	7,0	10,1	10,4	8,7	6,7
Yield of the liquid phase	-	80,0	75,0	71,0	68,5
The octane number for research method	88,7	87,9	88,7	90,4	90,5
Octane number by motor method	80,1	80,9	83,2	82,5	83,4
Massfractionofsulfur, %	0,0134	0,0110	0,0077	0,0053	0,0033

Note: P = 4.0MPa, V = 2.0 h⁻¹

When hydrolyzing coking gasoline on the catalyst KGO-18 with an increase in temperature from 320 to 400°C, the content of isoalkanes increases from 23,6% (initial), reaching a maximum value of 39,7% at 380°C, slightly decreasing to 37,1% at 400°C. Under these conditions, the yield of aromatic hydrocarbons increases to 18,6% (400°C). The amount of olefins in the resulting product is significantly reduced compared to the initial (24,2%) and varies within the range of 6,5-9,0%. The octane number of the refined gasoline obtained at 400°C is 82,6 (RM) and 66,8 (MM). The yield of liquid catalyst is 75,5-82,6%. The sulfur content of the catalyst after hydroprocessing decreased from 0,7127 in the initial gasoline to 0,0906% (Table 3).

Table 3 - Effect of temperature on the process of hydroprocessing of coking gasoline on the catalyst KGO-18

Products, %	T, °C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	27,2	26,2	20,9	24,7	19,1
Isoalkanes	23,6	35,6	38,7	33,9	37,1
Oleffin	24,2	9,0	8,0	8,1	6,5
Aromatichydrocarbons	8,9	13,2	10,6	14,9	18,6
Naphthenichydrocarbons	16,2	16,0	21,8	18,4	18,7
Yield of the liquid phase	-	82,6	78,2	76,1	75,5
The octane number for research method	84,0	80,9	80,6	81,4	82,6
Octane number by motor method	64,7	65,2	64,4	65,0	66,8
Massfractionofsulfur, %	0,7127	0,0950	0,0930	0,0908	0,0906

Note: P = 4.0MPa, V = 2.0 h⁻¹

Analysis of the results obtained during the hydroprocessing of various types of gasoline on the catalyst KGO-18 shows that the highest amount of isoalkanes is observed during the processing of catalytic cracking gasoline. In the catalyst obtained at 320-380°C 40,3-48,1% of isoalkanes were found, whereas when processing straight-run and gasoline coking, their quantity is 34,0-39,7% and 33,9-38,7%, respectively. The octane number of gasoline after hydrofining of straight-run gasoline and catalytic cracking gasoline is almost the same and equal to 90,7 and 90,5 (RM), respectively. In the case of coking gasoline, the octane number of fuel produced is lower than when processing other types of gasoline – 83,1 (MM).

The results obtained by studying the process of hydroprocessing of various gasoline fractions on the catalyst KGO-18 show that the highest degree of hydrodesulfurization is observed during the processing

of coking gasoline and is 87,3%, whereas for straight-run gasoline and catalytic cracking gasoline this figure is lower – 81,3 % and 75,4% respectively.

The process of hydroprocessing straight-run gasoline was also investigated on the catalysts KGO-20 and KGO-16. Comparison of the composition of the initial gasoline and the resulting products of hydroprocessing of straight-run gasoline on the catalyst KGO-20 at 320°C shows that the content of isoalkanes increases from 36,8 to 39,3%, aromatic hydrocarbons from 9,2 to 14,9%, olefins from 4,8 to 6,8%, and naphthenes, from 21,9 to 24,5%. At the same time, there is a decrease in the number of paraffins from 27,3 to 14,5%. The octane number by the research method after hydrotreating the straight-run gasoline on the catalyst KGO-20 increased: according to the research method - from 78,9 to 81,4, on the motor - from 60,9 to 66,3. With an increase in temperature from 320 to 400°C, an insignificant decrease in the yield of isoalkanes to 36,2% is observed. The yield of aromatic hydrocarbons is increased to 20,1%. The content of olefins varies between 4,0-7,4%. Under these conditions, the octane number according to the research method after hydrotreating the straight-run gasoline reaches a maximum value of 89,3 for the motor one – 73,4 (Table 4).

Studies have shown that the residual sulfur content after hydroprocessing straight-run gasoline on the catalyst KGO-20 has decreased from 0,0080 in the initial gasoline to 0,0028% (Table 4).

Table 4 - Effect of temperature on the process of hydroprocessing of straight-run gasoline on the catalyst KGO-20.

Products,%	T,°C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	27,3	14,5	7,1	4,3	16,7
Isoalkanes	36,8	39,3	40,4	33,4	36,2
Oleffin	4,8	6,8	7,0	7,4	4,0
Aromatic hydrocarbons	9,2	14,9	17,8	23,1	20,1
Naphthenic hydrocarbons	21,9	24,5	27,7	31,8	23,0
Yield of the liquid phase	-	77,0	49,0	44,5	55,0
The octane number for research method	78,9	81,4	84,9	88,3	89,3
Octane number by motor method	60,9	66,3	69,4	69,2	73,4
Mass fraction of sulfur,%	0,0080	0,0072	0,0062	0,0056	0,0028

Note: P = 4.0MPa, V = 2.0 h⁻¹

Table 5 - Effect of temperature on the process of hydroprocessing straight-run gasoline on the catalyst KGO-16

Products,%	T°C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	27,5	17,0	12,7	12,8	14,2
Isoalkanes	39,8	41,3	40,0	36,9	39,8
Oleffin	5,8	5,6	6,3	5,6	6,2
Aromatic hydrocarbons	8,7	12,9	15,7	22,8	19,7
Naphthenic hydrocarbons	18,2	23,2	25,3	21,9	20,1
Yield of the liquid phase	-	77,0	67,0	65,0	60,0
The octane number for research method	79,2	84,0	86,4	85,2	87,3
Octane number by motor method	61,1	68,7	71,0	70,8	72,7
Mass fraction of sulfur,%	0,0080	0,0036	0,0027	0,0023	0,0016

Note: P = 4.0MPa, V = 2.0 h⁻¹

At P = 4.0 MPa, V = 2,0 h⁻¹, the process of hydroprocessing a straight-run gasoline fraction with a sulfur content of 0,0080% on a catalyst KGO-16 was studied (Table 5). The yield of the liquid phase decreases from 83.5 to 70.0% with increasing temperature from 320 to 400°C. When hydrolyzing gasoline on KGO-16 catalyst in the temperature range 320-400°C, the maximum isoalkane content in the resulting catalyst is observed at 320°C and is equal to 41,3%. It should be noted that the amount of isoalkanes in the catalyst obtained after hydroprocessing depends little on the process temperature and is equal to 36,9-41,3%, which is higher than in the original gasoline fraction. The amount of aromatic hydrocarbons rises

from 8.7 to 19.7% with an increase in the process temperature to 400°C. The amount of olefins slightly increases compared with the original from 5,8 to 6.2%. The amount of naphthenic hydrocarbons in the resulting catalyst varies between 20,1-25,3%. The octane number of enriched gasoline increases in comparison with the initial from 19,2 to 87,3 (IM) and from 61,1 to 72,7 (MM). The content of sulfur in the catalyst with an increase in temperature to 400°C decreased compared with the initial from 0,0080 to 0,0016%.

Comparison of the results obtained in the study of the process of hydroprocessing the straight-run gasoline fraction shows that the catalysts KGO-16 and KGO-18 possess the highest hydrodesulfurizing activity. The degree of hydrodesulfurization on the catalyst KGO-18 is 81,3%, for KGO-16 80,0%, for KGO-2065%.

When hydrotreating straight-run gasoline (octane number 79,2) on the catalysts KGO-16, KGO-18 and KGO-20, an increase in the octane number compared with the original: 87,3; 90,7 and 89,3 respectively. This is mainly due to the increase in the content of isoalkanes in hydro-upgraded gasoline.

When hydrolyzing catalyticcracked gasoline on KGO-16 catalyst with an increase in temperature to 320-350°C, the content of isoalkanes increases from 25,4 to 47,5% (Table 6). With a further increase in temperature, there is a decrease in the amountof isoalkanes formed to 40,3% (400°C). Under these conditions, the amount of aromatic hydrocarbons in the produced gasoline rises from 30,1 to 35,0%. The content of naphthenic hydrocarbons in the catalyst is small and varies between 6,1 and 8,3%. The content of olefins in the catalyst decreases from 31,2 to 8,0%. The yield of the liquid phase with an increase in temperature in the range 320-400°C varies in the range 95.0-100%. The octane number of catalyticcracked gasoline enriched at 400°C is 86,1 (RM) and 79,6 (MM). When hydrotreating gasoline catalytic cracking, the sulfur content in the final product is reduced from 0,0134% (reference gasoline) to 0,0029%.

Table 6 - Effect of temperature on the process of hydroprocessing of catalytic cracking gasoline on the catalyst KGO-16

Products, %	T°C				
	Source gasoline	320	350	380	400
Paraffin C ₅ -C ₆	6,3	8,8	9,2	10,6	8,1
Isoalkanes	25,4	47,5	47,3	43,0	40,3
Oleffin	31,2	12,1	7,6	5,0	8,0
Aromatic hydrocarbons	30,1	25,5	29,4	32,6	35,0
Naphthenic hydrocarbons	7,0	6,1	6,6	8,1	8,3
Yield of the liquid phase	-	100	97,5	95,5	95
The octane number for research method	88,7	86,2	85,2	85,4	86,1
Octane number by motor method	80,1	81,0	79,0	78,0	79,6
Mass fraction of sulfur, %	0,0134	0,0048	0,0047	0,0035	0,0029

Note: P = 4.0MPa, V = 2.0 h⁻¹

In the study of the process of hydroprocessing of catalytic cracking gasoline, it was shown that the catalysts of KGO have a sufficiently high hydrodesulfurizing activity. The degree of hydrodesulfurization on the catalyst KGO-18 is 75,4%, at KGO-16 – 78,4%. In the hydrotreating of catalytic cracking gasoline (octane number 88,7 (RM), a slight decrease in the octane number to 86,1 (RM) is observed on the catalyst KGO-16, while at the KGO-18 the octane number of the upgraded gasoline increases to 90,5 (RM).

We have previously shown that the activity of hydroprocessing catalysts of various petroleum fractions is related to the surface structure, phase composition and the state of the modifying additives [8]. An electron microscopic study was made of the structure and state of the active centers of the KGO catalysts promoted by Ce, Co, Mo, etc. Studies have shown that on the surface of these catalysts, there are several types of surface structures that differ significantly in both size and chemical state of the components.

According to electron microscopy, the thermodesorption of ammonia and X-ray diffraction catalysts are highly dispersed, the metal components of the active phase are predominantly in the oxidized state, forming cluster-associates on the surface whose dispersion and structure and state are determined by the nature of the catalyst components [8].

Conclusions. When hydroprocessing various types of gasoline on the catalyst KGO-18, the highest content of isoalkanes is observed during the processing of catalytic cracking gasoline. 40,3-48,1% of isoalkanes were found in the catalyst obtained on the catalyst KGO-18 at 320-380°C, whereas in the process of straight-run and gasoline coking, the content of isoalkanes is 34,0-39,7% and 33,9 – 38,7%. The octane number of gasoline after hydrofining of straight-run gasoline and catalytic cracking gasoline is almost the same and is 90,7 and 90,5 (RM), respectively. Modified zeolite-containing alumo-cobalt-molybdenum catalysts for hydroprocessing gasoline fractions in one stage conduct hydrotreating, hydroisomerization, hydrogenation and allow to obtain low-sulfur high-octane gasoline.

Source of research funding: The work is carried out in accordance with the scientific and technical program: No. BR05236739 "Creation of bases for the production of oil and gas products based on domestic technologies".

REFERENCES

- [1] Kashin O.N., Ermolenko A.D., *Neftepererabotkaineftechimia*. **2005**, 5, 32-38. (in Russ.)
- [2] Onoychenko S.N., Emelyanov V., Krylov I.F. *Chemistry and Technology of Fuels and oils*. **2003**, 6, 3-6 (in Russ.)
- [3] Konovalchik O.D., Melik- Ahnazarov T.H., Khavkin V.A., etc. *Neftepererabotkaineftechimia*. **2000**, 9, 12-16 (in Russ.)
- [4] Tomin N.N., Pimerzin A.A., Loginov L.N., Sharikhin M.A. *Neftehimiya*. -**2004**, V.44, 4, 274-277 (in Russ.)
- [5] Yasian Yiu. P., Kolesnikov A.G., Zavalinskii D.V., Zavalinskaya I.S. // *Chimiaitehnologiatoplivimasel*. **2003**, 5, 32-35.. (in Russ.)
- [6] Ishutenko D.I., Nikulshin P.V., Konavalov V.V., Pimerzin A.A. // *Kinetic and catalysis*. -**2015**, -6, -735-745 (in Russ.)
- [7] Havkin V.A., Gulyaeva L.A., Bychkova D.M., Loshenkova I.N., Krasilnikova L.A., Logionova S.A. // *Neftepererabotkaineftechimia*. -**2004**, 4, 29-34 (in Russ.)
- [8] Tuktin B., Shapovalova L.B., Chanysheva I.S. // *Chimicheskii jurnal Kazakhstana*. **2012**, - 4, -p.157-162. (in Russ.)
- [9] Ione K.G. *Multifunctional. catalysis on zeolites*. - Novosibirsk : Nauka, **1982**, - 2 (in Russ.)
- [10] Toledo-Antonio J.A., Cortés-Jácome M.A., Angeles-Chávez C., Escobar J., Barrera M.C., López-Salinas E. // *Appl. Catal.*, B, **2009**, 90, 213-223.
- [11] Dumond F., Marceau E., Che M., A. // *Revista de Chimie*, **2007**, 67, 1523-1528.
- [12] Plantenga F.L., Leliveld R.G. // *Appl. Catal. A: General*. **2003**, 248, 1-7.
- [13] Morales-Ortuño J.C., Klimova T.E. // *Fuel*. **2005**, 198, 99-109.
- [14] Deldari H. // *Appl. Catal. A: General*. **2017**, 293, 1-10.
- [15] Gonzalez-Cortesa S.L., Rugmini S., Xiao T., Green M.L.N., Rodulfo-Baechler S.M., Imbert F.E. // *Appl. Catal. A: General*, **2014**, 270-281.
- [16] Besenbacher F., Bronson M., Clausen B., Helveg S., Hinnemann B., Kibsgaard J., Lauritsen J., Moses P., Nørskov J., Topsøe H. // *Catal. Today*. **2008**, 130, 86-96.
- [17] Babich I.V., Mouljin J.V. // *Fuel*. -**2003**, 111, 4780-4789.
- [18] Qiherim, Li. H., Yuan H., Zhang Y., Xu G. // *Chin. J. Catal*. **2011**, 32, 240-249.
- [19] Smirnov V.K., Irisova K.N., Talisman E.L. // *Catalysis in industry*. 2003.-No. 2. P.30-36. (in Russ.)
- [20] Khavkin V.A., Chernysheva E.A., Gulyaeva L.L. *Hydrogenation processes of obtaining motor fuels* - Ufa. -2013. - 259. (in Russ.)

Б.Т. Туктин, Н.Н. Нурғалиев, А.С.Тенизбаева, Л.Б. Шаповалова, Л.В. Комашко

«Д.В. Сокольский атындағы Жанармай, катализ және электрохимия институты» АҚ, Алматы, Қазақстан

БЕНЗИННІҢ ӘРТҮРЛІ ФРАКЦИЯЛАРЫН МОДИФИЦИРЛЕНГЕН АЛЮМОКОБАЛЬТМОЛИБДЕН КАТАЛИЗАТОРАЛАРЫНДА ГИДРОЖАҚСАРТУ

Аннотация. Жұмыста ZSM-5 және HҮ цеолит қоспалары, фосфор мен сирек кездесетін элементтермен модифицирленген алюмокобальтмолибден катализаторларында: CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-18); CoO-MoO₃-La₂O₃-P₂O₅-Al₂O₃-ZSM (KGO-20) және CoO-MoO₃-Ce₂O₃-P₂O₅-Al₂O₃-ZSM-HҮ (KGO-16) бензиннің әртүрлі фракцияларын (тура айдалған бензин, каталитикалық крекинг бензині және кокстеу бензині) гидроөңдеу зерттеулерінің нәтижелері берілген.

KGO-18 катализаторында бензиннің әртүрлі фракцияларын гидроөңдеуден алынған нәтижелері көрсеткендей, изоалкандардың ең жоғары үлесі каталитикалық крекинг бензинін өндегенде байқалды. KGO-18 катализаторындағы 320-380°C-та алынған катализаттағы изоалкандар мөлшері 40,3-48,1% болса, ал тура айдалған бензин мен кокстеу бензиндерін өндегенде алынған изоалкандар 34,0-39,7% және 33,9-38,7%-ды құрады. Тура айдалған бензин мен каталитикалық крекинг бензинін гидрожақсартудан соң октан саны іс жүзінде бірдей, яғни 90,7 мен 90,5-ке (ЗӨ) тең. Ал өңделген кокстеу бензинінің октан саны басқа өңделген бензин фракцияларынан қарағанда төмен, яғни 83,1-ге тең (ЗӨ). KGO-18 катализаторында бензиннің әртүрлі

фракцияларын гидроөңдеу процесінің зерттеулері байқатқандай, ең жоғары гидрокүкіртсіздендіру кокстеу бензинін өндеуде жүзеге асты, яғни 87,3%-ға тең болды. Ал тура айдалған бензинде 81,3% болса, каталитикалық крекинг бензинінде 75,4%-ды құрады.

Түйін сөздер: цеолит, тура айдалған бензин, каталитикалық крекинг бензині, кокстеу бензині, катализатор, гидротазалау

Б.Т. Туктин, Н.Н. Нургалиев А.С. Тенизбаева, Л.Б. Шаповалова, Л.В. Комашко

АО "Институт топлива, катализа и электрохимии им. Д.В. Сокольского", Алматы, Казахстан

ГИДРООБЛАГОРАЖИВАНИЕ РАЗЛИЧНЫХ БЕНЗИНОВЫХ ФРАКЦИЙ НА МОДИФИЦИРОВАННЫХ АЛЮМОКОБАЛЬТМОЛИБДЕНОВЫХ КАТАЛИЗАТОРАХ

Аннотация. В работе приведены результаты исследования гидропереработки различных бензиновых фракций (прямогонный бензин, бензин каталитического крекинга, бензин коксования) на алюмокобальтмолибденовых катализаторах, модифицированных добавками цеолитов ZSM-5 и HY, фосфора и редкоземельных элементов: $\text{CoO-MoO}_3\text{-Ce}_2\text{O}_3\text{-P}_2\text{O}_5\text{-Al}_2\text{O}_3\text{-ZSM}$ (КГО-18); $\text{CoO-MoO}_3\text{-La}_2\text{O}_3\text{-P}_2\text{O}_5\text{-Al}_2\text{O}_3\text{-ZSM}$ (КГО-20) и $\text{CoO-MoO}_3\text{-Ce}_2\text{O}_3\text{-P}_2\text{O}_5\text{-Al}_2\text{O}_3\text{-ZSM-HY}$ (КГО-16).

Результаты, полученные при гидропереработке различных видов бензина на катализаторе КГО-18, показывают, что наиболее высокое количество изоалканов наблюдается при переработке бензина каталитического крекинга. В катализате, полученном на катализаторе КГО-18 при 320-380°C обнаружено 40,3-48,1% изоалканов, тогда как при переработке прямогонного и бензина коксования содержание изоалканов составляет 34,0-39,7% и 33,9 - 38,7%. Октановое число после гидрооблагораживания прямогонного бензина и бензина каталитического крекинга практически одинаково и составляет 90,7 и 90,5 (ИМ) соответственно. В случае бензина коксования октановое число получаемого топлива ниже, чем при переработке других видов бензинов - 83,1 (ИМ). При исследовании процесса гидропереработки различных бензиновых фракций на катализаторе КГО-18 установлено, что наиболее высокая степень гидрообессеривания наблюдается при переработке бензина коксования - 87,3%, прямогонного бензина - 81,3% и бензина каталитического крекинга - 75,4%. Бензин фракцияларын гидроөңдеуде модифицирленген цеолит құрамды алюмокобальтмолибден катализаторлары бір сатыда гидротазалау, гидроизомерлеу, гидрлеу реакцияларын жүргізіп, аз күкіртті жоғары октанды бензин алуға мүмкіндік береді.

Ключевые слова: цеолит, прямогонный бензин, бензин каталитического крекинга, бензин коксования, катализатор, гидроочистка

Information about the authors:

Tuktin Balga Tuctievich - Head of the laboratory of motor fuels, doctor of chemical science, JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", e-mail: tuktin_balga@mail.ru, w.ph. 8-727-2916826, mob.ph. 87026413597;

Nurgaliyev Nurzhan Nurlybekovich - Junior researcher of the laboratory of motor fuels, PhD, JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", e-mail: n.nurgaliyev@ifce.kz, mob.ph. 87013551823;

Tenizbayeva Aliya Serikovna - Lead engineer of the laboratory of motor fuels, JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", e-mail: aliya.85@mail.ru, mob.ph. 87772626004;

Shapovalova Larisa Borisovna - Chief researcher of the laboratory of motor fuels, doctor of chemical science, professor, JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", e-mail: larachemistry@mail.ru, mob.ph. 8-727-2916826;

Komashko Larisa Vladimirovna - Senior researcher of the laboratories of physical research methods, JSC "DV Sokolsky Institute of Fuel, Catalysis and Electrochemistry", e-mail: Komashko535@mail.ru, w.ph. 8-727-290-79-19, mob.ph. 8-777-398-70-77

МАЗМҰНЫ

<i>Кантуреева Г.О., Defrancesco E., Алибеков Р.С., Уразбаева К.А., Ефимова И.Е.</i> Қазақстанның дәстүрлі азық-түлік өнімдерді сәйкестендіру жаңа тенденциялары	6
<i>Туктин Б.Т., Теңізбаева А.С., Нұрғалиев Н.Н., Шаповалова Л.Б., Яскевич В.И.</i> Модифицирленген Ni(Co)-Mo- Al ₂ O ₃ катализаторларында тура айдалған бензин фракциясын гидроизомерлеу және гидроөңдеу	13
<i>Ахметалимова А.М., Ивасенко С.А., Марченко А.Б., Ишмуратова М.Ю., Полезчак Э., Людвичук А., Посева И.В.</i> Қарағанды өңіріндегі <i>THYMUS EREMITA</i> KLOK. және <i>THYMUS RASITATUS</i> KLOK. өсімдіктерінің химиялық құрамын зерттеу.....	20
<i>Фазылов С.Д., Нұркенов О.А., Журинов М.Ж., Әрінова А.Е., Туктаров А.Р., Исәева А.Ж., Шаихова Б.К.</i> С ₆₀ фуллеренге гидразондардың палладий комплекстерімен катализденетін циклооксидің синтезі	26
<i>Опимах Е.В., Левданский А.Э., Голубев В.Г., Корганбаев Б.Н., Сарсенбекулы Д.</i> Ұсақтау барысындағы меншікті энергия шығындарын төмендетудің келешекті бағыттары	32
<i>Қапсәмет М.Ж., Тәжібаева С.М., Уракаев Ф.Х., Уралбеков Б.М., Бүркімбаев М.М., Бачилова Н.В.</i> Нанокүкіртті алу және тұрақтандыру	41
<i>Байсанов С.О., Толоконникова В.В., Нарикбаева Г.И., Корсукова И.Я., Жучков В.И.</i> Күй диаграммасына талдау жасау негізінде марганецті және хромды феррокорытпаларды балқытуға термодинамикалық бағалау.....	47
<i>Құлекеев Ж.Ә., Нұртаева Г.Қ., Мұстафин Е.С., Айнабаев А.А., Мұстафин Т.Е., Борсынбаев А.С., Жарикесов Ф.А.</i> Теңізге төгілген мұнайды жоюда хердерлерді пайдаланудың мүмкіндіктері	58
<i>Туктин Б.Т., Нурғалиев Н.Н., Тенизбаева А.С., Шаповалова Л.Б., Комашко Л.В.</i> Бензиннің әртүрлі фракцияларын модифицирленген алюмокобальтмолибден катализаторларында гидрожақсарту	67
<i>Қалдыбекова А.Ж., Амангазиева А.Т., Халменова З.Б., Үмбетова А.К.</i> <i>Harporhyllum</i> A. Juss шөбінен биологиялық белсенді заттардың кешенді бөліну технологиясын дамыту	74
<i>Опимах Е.В., Левданский А.Э., Волненко А.А., Жумадуллаев Д.К.</i> Флотациялық процесстерді жүргізу әдістері	82
<i>Чиркун Д. И., Левданский А. Э., Волненко А.А., Сарсенбекулы Д.</i> Соккылы-ортдан тепкіш диірмендердегі бөлшектердің динамикасын зерттеу	92
<i>Баймұқашева Г.К., Қалауова А.С., Құспанова Б.К., Насиров Р.Н.</i> Үшфенилфосфиннің анион-радикалы.....	102
<i>Баешова А.К., Молайган С., Баешов А.Б.</i> Суутектік энергетиканың қазіргі замандағы жағдайы және суутекті алу әдістері	107
<i>Закарина Н.А., Дәлелханұлы О., Жумадуллаев Д.А., Ақурпекова А.К., Джумабаева Л.С.</i> Al, AlZr және Ti-мен пилларирленген Na- және Ca-формалы монтмориллонитке енгізілген Pt- және Pd-катализаторларындағы тікелей айдалған бензиннің жеңіл фракциясының изомеризациясы.....	117
<i>Нәсіров Р.Н.</i> ЭПР спектроскопия көмегімен каспий маңындағы мұнайлардағы ванадийді анықтау.....	125
<i>Байжуманова Т.С., Тунгатарова С.А., Xanthopoulou G., Жексенбаева З.Т., Кауменова Г.Н., Еркибаева М.К., Жумабек М., Касымхан К.</i> Метанның олефиндерге дейін каталитикалық конверсиясы.....	132
<i>Калимукашева А.Д., Калиманова Д.Ж., Иманкулова З.А.</i> Формативті бағалау-химия сабақтарында оқыту процесінің ажырамас бөлігі.....	139
<i>Масенова А.Т., Калыкбердиев М.К., Сасс А.С., Кензин Н.Р., Канатбаев Е.Т., Цыганков В.П.</i> Бензин фракцияларындағы хош иісті көмірсутектерді жоғары қысымда отырғызылғын катализаторларды қолдану арқылы суутектендіру.....	146

СОДЕРЖАНИЕ

<i>Кантуреева Г.О., Defrancesco E., Алибеков Р.С., Уразбаева К.А., Ефимова И.Е.</i> Новые тенденции в идентификации традиционной пищевой продукции Казахстана	6
<i>Туктин Б.Т., Тенизбаева А.С., Нурғалиев Н.Н., Шаповалова Л.Б., Яскевич В.И.</i> Исследование гидроочистки и гидроизомеризации прямогонной бензиновой фракции на модифицированных Ni(Co)-Mo- Al ₂ O ₃ - катализаторах	13
<i>Ахметалимова А.М., Ивасенко С.А., Марченко А.Б., Ишмуратова М.Ю., Полезчак Э., Людвичук А., Лосева И.В.</i> Исследование химического состава <i>THYMUS EREMITA KLOK.</i> и <i>THYMUS RASITATUS KLOK.</i> Карагандинского региона	20
<i>Фазылов С.Д., Нуркенов О.А., Журинов М.Ж., Аринова А.Е., Туктаров А.Р., Исаева А.Ж., Шахова Б.К.</i> Катализируемое комплексами палладияциклоприсоединение гидразонов к фуллерену C ₆₀	26
<i>Опимах Е.В., Левданский А.Э., Голубев В.Г., Корганбаев Б.Н., Сарсенбекулы Д.</i> Перспективные направления снижения удельных энергозатрат при измельчении	32
<i>Кансамет М.Ж., Тажибаева С.М., Уракаев Ф.Х., Уралбеков Б.М., Буркитбаев М.М., Бачилова Н.В.</i> Получение и стабилизация наносеры	41
<i>Байсанов С.О., Толоконникова В.В., Нарикбаева Г.И., Корсукова И.Я., Жучков В.И.</i> Термодинамическая оценка выплавки марганцевых и хромистых ферросплавов на основе анализа их диаграмм состояния	47
<i>Кулекеев Ж.А., Нуртаева Г.К., Мустафин Е.С., Айнабаев А.А., Мустафин Т.Е., Борсынбаев А.С., Жарикесов Г.А.</i> Возможности использования хердеров при ликвидации разливов нефти на море	58
<i>Туктин Б.Т., Нурғалиев Н.Н., Тенизбаева А.С., Шаповалова Л.Б., Комашко Л.В.</i> Гидрооблагораживание различных бензиновых фракций на модифицированных алюмокобальтмолибденовых катализаторах	67
<i>Калдыбекова А.Ж., Амангазиева А.Т., Халменова З.Б., Умбетова А.К.</i> Разработка технологии комплексного выделения биологических активных веществ из растений рода <i>Naplophyllum</i> A. Juss	74
<i>Опимах Е.В., Левданский А.Э., Волненко А.А., Жумадуллаев Д.К.</i> Методы проведения флотационных процессов	82
<i>Чиркун Д. И., Левданский А. Э., Волненко А.А., Сарсенбекулы Д.</i> Исследование динамики частиц в ударно-центробежных мельницах	92
<i>Баймукашева Г.К., Калауова А.С., Куспанова Б.К., Насиров Р.Н.</i> Анион-радикал трифенил-фосфина	102
<i>Баешова А.К., Молайган С., Баешов А.Б.</i> Современное состояние водородной энергетики и способы получения водорода	107
<i>Закарина Н.А., Дәлелханұлы О., Жумадуллаев Д.А., Акурпекова А.К., Джумабаева Л.С.</i> Изомеризация легкой фракции прямогонного бензина на Pt- и Pd-катализаторах, нанесенных на пилларированный Al, AlZr и Ti монтмориллонит в Na- и Ca-формах	117
<i>Насиров Р.Н.</i> Определение ванадия в нефтях прикаспийского региона методом ЭПР-спектроскопии	125
<i>Байжуманова Т.С., Тунгатарова С.А., Xanthoroulou G., Жексенбаева З.Т., Кауменова Г.Н., Еркибаева М.К., Жумабек М., Касымхан К.</i> Каталитическая конверсия метана в олефины	132
<i>Калимукашева А.Д., Калиманова Д.Ж., Иманкулова З.А.</i> Формативное оценивание - неотъемлемая часть процесса обучения на уроках химии	139
<i>Масенова А.Т., Калыкбердиев М.К., Сасс А.С., Кензин Н.Р., Канатбаев Е.Т., Цыганков В.П.</i> Гидрирование ароматических углеводородов в бензиновых фракциях на нанесенных катализаторах под давлением	146

CONTENTS

<i>Kantureeva G.O., Defrancesco E., Alibekov R.S., Urazbayeva K.A., Efimova I.E.</i> New trends in the identification of the traditional food products of Kazakhstan	6
<i>Tuktin B.T., Tenizbaeva A.S., Nurgaliyev N.N., Shapovalova L.B., Yaskevich V.I.</i> Study of hydro purification and hydroisomerization straight-run gasoline fraction over modified Ni(Co)-Mo- Al ₂ O ₃ - catalysts	13
<i>Akhmetlimova A.M., Ivashenko S.A., Marchenko A.B., Ishmuratova M.Yu., Poleszak E., Ludwiczuk A., Loseva I.V.</i> The study of the chemical composition of <i>THYMUS EREMITA</i> KLOK. and <i>THYMUS RASITATUS</i> KLOK. from the Karaganda region	20
<i>Fazylov S.D., Nurkenov O.A., Zhurinov M.Zh., Arinova A.E., Tuktarov A.R., Issayeva A.Zh., Shaihova B.K.</i> Catalyzed by palladium complexes the cycloaddition of hydrazones to fullerene C ₆₀ (in English).....	26
<i>Apimakh Ye.V., Leudanski A.E., Golubev V.G., Korganbayev B.N., Sarsenbekuly D.</i> Promising directions of reducing specific energy costs in grinding (in English).....	32
<i>Kapsamet M.Zh., Tazhibayeva S.M., Urakaev F.Kh., Uralbekov B.M., Burkitbayev M.M., Bachilova N.V.</i> Obtaining and stabilization of nanosulfur	41
<i>Baisanov S.O., Tolokonnikova V.V., Narikbayeva G.I., Korsukova I.Ya., Zhuchkov V.I.</i> Thermodynamic assessment of smelting of manganese and chromium ferroalloys based on the analysis of their state diagrams	47
<i>Kulekeyev Zh.A., Nurtayeva G.K., Mustafin E.S., Ainabayev A.A., Mustafin T.E., Borsynbayev A.S., Zharikessov G.A.</i> Using herders for oil spill response in the sea	58
<i>Tuktin B.T., Nurgaliyev N.N., Tenizbaeva A.S., Shapovalova L.B., Komashko L.V.</i> Hydrotreating of various petrol fractions over modified alumocobaltmolybdenic catalysts	67
<i>Kaldybekova A.Zh., Amangazyeva A.T., Halmenova Z.B., Umbetova A.K.</i> Development of technology for the complex isolation of biological active substances from plants of the genus <i>Haplophyllum</i> A. Juss	74
<i>Apimakh Ye.V., Leudanski A.E., Volnenko A.A., Zhumadullaev D.K.</i> Methods of carrying out flotation processes	82
<i>Chyrkun D.I., Levdanskiy A.E., Volnenko A.A., Sarsenbekuly D.</i> Study of the particle dynamics in impact-centrifugal mills (in English).....	92
<i>Baymukasheva G.K., Kalauova A.S., Kuspanova B., Nasirov R.N.</i> Triphenylphosphine anion radical.....	102
<i>Bayeshova A.K., Molaigan S., Bayeshov A.B.</i> Hydrogen energetics current state and hydrogen production methods.....	107
<i>Zakarina N.A., Dolekhanuly O., Jumadullaev D.A., Akurpekova A.K., Djumabaeva L.S.</i> Isomerization of light fraction of straight-run gasoline on Pt- and Pd-catalysts supported on pillared by Al, AlZr and Ti montmorillonite in Na- and Ca-forms.	117
<i>Nasirov R.N.</i> Determination of vanadium in the precaspian region's oil by the EPR-spectroscopy method.....	125
<i>Baizhumanova T.S., Tungatarova S.A., Xanthopoulou G., Zheksenbaeva Z.T., Kaumenova G.N., Erkibaeva M.K., Zhumabek M., Kassymkan K.</i> Catalytic conversion of methane into olefins.....	132
<i>Kalimukasheva A.D., Kalimanova D.Z., Imankulova Z.A.</i> Formative evaluation is an uninterrupted part of the training process on lessons of chemistry.....	139
<i>Massenova A.T., Kalykberdiyev M.K., Sass A.S., Kenzin N.R., Kanatbayev E.T., Tsygankov V.P.</i> Hydrogenation of aromatic hydrocarbons in gasoline fractions over supported catalysts under pressure.....	146

**Publication Ethics and Publication Malpractice
in the journals of the National Academy of Sciences of the Republic of Kazakhstan**

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации
в журнале смотреть на сайте:

[www:nauka-nanrk.kz](http://www.nauka-nanrk.kz)

<http://www.chemistry-technology.kz/index.php/ru/>

ISSN 2518-1491 (Online), ISSN 2224-5286 (Print)

Редакторы: *М. С. Ахметова, Т. А. Апендиев, Аленов Д.С.*
Верстка на компьютере *А.М. Кульгинбаевой*

Подписано в печать 11.10.2018.
Формат 60x881/8. Бумага офсетная. Печать – ризограф.
9,8 п.л. Тираж 300. Заказ 5.