

**ISSN 2518-1726 (Online),
ISSN 1991-346X (Print)**

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

ӘЛЬ-ФАРАБИ АТЫНДАҒЫ
ҚАЗАҚ ҰЛТТЫҚ УНИВЕРСИТЕТИНІҢ

Х А Б А Р Л А Р Ы

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН

КАЗАХСКИЙ НАЦИОНАЛЬНЫЙ
УНИВЕРСИТЕТ ИМЕНИ АЛЬ-ФАРАБИ

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES
OF THE REPUBLIC OF KAZAKHSTAN

AL-FARABI KAZAKH
NATIONAL UNIVERSITY

ФИЗИКА-МАТЕМАТИКА СЕРИЯСЫ

СЕРИЯ ФИЗИКО-МАТЕМАТИЧЕСКАЯ

PHYSICO-MATHEMATICAL SERIES

6 (322)

ҚАРАША – ЖЕЛТОҚСАН 2018 ж.

НОЯБРЬ – ДЕКАБРЬ 2018 г.

NOVEMBER – DECEMBER 2018

1963 ЖЫЛДЫҢ ҚАҢТАР АЙЫНАН ШЫҒА БАСТАҒАН
ИЗДАЕТСЯ С ЯНВАРЯ 1963 ГОДА
PUBLISHED SINCE JANUARY 1963

ЖЫЛЫНА 6 РЕТ ШЫҒАДЫ
ВЫХОДИТ 6 РАЗ В ГОД
PUBLISHED 6 TIMES A YEAR

Бас редакторы
ф.-м.ғ.д., проф., КР ҮФА академигі **F.M. Мұтанов**

Редакция алқасы:

Жұмаділдаев А.С. проф., академик (Қазақстан)
Кальменов Т.Ш. проф., академик (Қазақстан)
Жантаев Ж.Ш. проф., корр.-мүшесі (Қазақстан)
Өмірбаев Ү.Ү. проф. корр.-мүшесі (Қазақстан)
Жусіпов М.А. проф. (Қазақстан)
Жұмабаев Д.С. проф. (Қазақстан)
Асанова А.Т. проф. (Қазақстан)
Бошкаев К.А. PhD докторы (Қазақстан)
Сұраған Ә. корр.-мүшесі (Қазақстан)
Quevedo Hernando проф. (Мексика),
Джунушалиев В.Д. проф. (Қыргызстан)
Вишневский И.Н. проф., академик (Украина)
Ковалев А.М. проф., академик (Украина)
Михалевич А.А. проф., академик (Белорус)
Пашаев А. проф., академик (Әзірбайжан)
Такибаев Н.Ж. проф., академик (Қазақстан), бас ред. орынбасары
Тигиняну И. проф., академик (Молдова)

«КР ҮФА Хабарлары. Физика-математикалық сериясы».

ISSN 2518-1726 (Online), ISSN 1991-346X (Print)

Меншіктенуші: «Қазақстан Республикасының Үлттық ғылым академиясы» РКБ (Алматы қ.)
Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде
01.06.2006 ж. берілген №5543-Ж мерзімдік басылым тіркеуіне қойылу туралы қуәлік

Мерзімділігі: жылдана 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,
www.nauka-nanrk.kz / physics-mathematics.kz

© Қазақстан Республикасының Үлттық ғылым академиясы, 2018

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Г л а в н ы й р е д а к т о р
д.ф.-м.н., проф. академик НАН РК **Г.М. Мутанов**

Р е д а к ц и о н на я кол л е г и я:

Джумадильдаев А.С. проф., академик (Казахстан)
Кальменов Т.Ш. проф., академик (Казахстан)
Жантаев Ж.Ш. проф., чл.-корр. (Казахстан)
Умирбаев У.У. проф. чл.-корр. (Казахстан)
Жусупов М.А. проф. (Казахстан)
Джумабаев Д.С. проф. (Казахстан)
Асанова А.Т. проф. (Казахстан)
Бошкаев К.А. доктор PhD (Казахстан)
Сураган Д. чл.-корр. (Казахстан)
Quevedo Hernando проф. (Мексика),
Джунушалиев В.Д. проф. (Кыргызстан)
Вишневский И.Н. проф., академик (Украина)
Ковалев А.М. проф., академик (Украина)
Михалевич А.А. проф., академик (Беларусь)
Пашаев А. проф., академик (Азербайджан)
Такибаев Н.Ж. проф., академик (Казахстан), зам. гл. ред.
Тигиняну И. проф., академик (Молдова)

«Известия НАН РК. Серия физико-математическая».

ISSN 2518-1726 (Online), ISSN 1991-346X (Print)

Собственник: РОО «Национальная академия наук Республики Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №5543-Ж, выданное 01.06.2006 г.

Периодичность: 6 раз в год.

Тираж: 300 экземпляров.

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел.: 272-13-19, 272-13-18,
www.nauka-nanrk.kz / physics-mathematics.kz

© Национальная академия наук Республики Казахстан, 2018

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75.

Editor in chief
doctor of physics and mathematics, professor, academician of NAS RK **G.M. Mutanov**

Editorial board:

Dzhumadildayev A.S. prof., academician (Kazakhstan)
Kalmenov T.Sh. prof., academician (Kazakhstan)
Zhantayev Zh.Sh. prof., corr. member. (Kazakhstan)
Umirbayev U.U. prof. corr. member. (Kazakhstan)
Zhusupov M.A. prof. (Kazakhstan)
Dzhumabayev D.S. prof. (Kazakhstan)
Asanova A.T. prof. (Kazakhstan)
Boshkayev K.A. PhD (Kazakhstan)
Suragan D. corr. member. (Kazakhstan)
Quevedo Hernando prof. (Mexico),
Dzhunushaliyev V.D. prof. (Kyrgyzstan)
Vishnevskyi I.N. prof., academician (Ukraine)
Kovalev A.M. prof., academician (Ukraine)
Mikhalevich A.A. prof., academician (Belarus)
Pashayev A. prof., academician (Azerbaijan)
Takibayev N.Zh. prof., academician (Kazakhstan), deputy editor in chief.
Tiginyanu I. prof., academician (Moldova)

News of the National Academy of Sciences of the Republic of Kazakhstan. Physical-mathematical series.

ISSN 2518-1726 (Online), ISSN 1991-346X (Print)

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)
The certificate of registration of a periodic printed publication in the Committee of information and archives of the Ministry of culture and information of the Republic of Kazakhstan N 5543-Ж, issued 01.06.2006

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,
www.nauka-nanrk.kz / physics-mathematics.kz

© National Academy of Sciences of the Republic of Kazakhstan, 2018

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

NEWS

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

PHYSICO-MATHEMATICAL SERIES

ISSN 1991-346X

<https://doi.org/10.32014/2018.2518-1726.18>

Volume 6, Number 322 (2018), 54 – 70

UDC 532.516

K. B. Jakupov

Kazak National University named after Al-Farabi
E-mail: jakupovKB@mail.ru

**NATURAL FILTRATION EQUATIONS.
FIASCO "OF DARCY'S LAW"**

Abstract. The theory of natural filtration equations is given. The naturalness of the new filtration equations is that they are the exact consequences of the fundamental laws of physics, directly take into account the density and porosity of the soil, the viscosity and density of the filtration fluid, drainage, the influence of gravity, etc. the falsity of the traditional continuity equation in the filtration theory is established. New filtration equations are derived from the equation of continuum dynamics in stresses, including the density and viscosity of the liquid and the porosity of the soil. Inadequacy of the modeling filter equations with the friction law of Newton. The efficiency of simulation of filtration by Jakupova equations based on the power laws of friction with odd exponents is numerically confirmed, with the use of which the calculations of filtration in the well, drainage under the influence of gravity, displacement of oil by water from the underground area through two symmetrically located pits are carried out.

Keywords: filtration, pressure, velocity, acceleration, equations.

Falsifications and contradictions of Darcy's law equations»

$$k\mathbf{v} = -grad p + \rho\mathbf{F}, \quad div\mathbf{v} = 0$$

with the fundamental laws of physics detailed in [1] and [13]. There is also considered the non-representativeness of the application of "Darcy's law" in the theory of spatial filtration. It shows the contradictions of equations "Darcy's law" law of friction and the second law of Newton. It is found that the spatial equations of "Darcy's law" correspond to potential flows, which contradicts the theory of viscous fluid. The equations of the "Darcy's law" do not comply with the law of conservation of energy. Based on the fact that the equations of the "Darcy's law" are composed of derivatives of the 1st order, contradictory problems of setting boundary conditions are revealed.

The equations of the Forchheimer model also contradict the laws of physics:

$$\rho_f \frac{\partial \mathbf{v}}{\partial t} = -\varphi [grad(p + \rho_f g z) + \rho_f \frac{\nu}{K} \mathbf{v} + \rho_f c_f K^{-\frac{1}{2}} |\mathbf{v}| \mathbf{v}], \quad div\mathbf{v} = 0,$$

φ -coefficient of porosity of the medium, K – coefficient of permeability, ρ_f -is the fluid density, c_f - is the dimensionless coefficient of friction of Forchheimer. The viscosity of the liquid is also included ν .

The Forchheimer dynamics equation contains only local acceleration, but there is no transfer of medium particles $(\mathbf{v} \cdot \nabla) \mathbf{v}$, which is a *gross error*.

Numeroff C.H. as early as 1968 paid attention to necessity of account acceleration (forces of inertia) in basic equalizations of theory of filtration and offered in [10] to use the next system of equalizations:

$$\frac{1}{g\sigma} \frac{\partial \mathbf{v}}{\partial t} + \frac{1}{(g\sigma)^2} (\mathbf{v} \cdot \nabla) \mathbf{v} + grad h + f(\mathbf{v}) \mathbf{v} = 0, \quad div \mathbf{v} = 0$$

The same Numeroff first specified on impermissibility of breaches of the second Newton's law, that says of : "mass on an acceleration equal to force". If an acceleration is equal to the zero, then on the first Newton's law a body accomplishes rectilineal motion with permanent speed or reposes. In the model of Нумерова, as well as in the model of Forchheimer the first derivatives enter from the sought after functions, consequently, there is a problem of raising of regional terms.

1. Falseness of traditional equalization of indissolubility with the coefficient of porosity in the theory of filtration

In [3-5] and other in equalization of indissolubility is plug porosity

$$\frac{\partial s\rho}{\partial t} + div \rho \mathbf{v} = 0$$

(In Wikipedia given in a form $\frac{\partial m\rho}{\partial t} + div \rho \mathbf{v} = 0$). We will prove falsity of this equalization of indissolubility.

We will proceed from the fact that the elementary volume of the continuous medium is represented by the sum of the individual volumes of soil $\delta\tau_g$ and to the leakliquid $\delta\tau_f$: $\delta\tau = \delta\tau_g + \delta\tau_f$. Mass $\delta\tau$ is equal to the sum of the masses of soil and liquid $\delta m = \delta m_g + \delta m_f$, $\delta m_g = \rho_g \delta\tau_g$, $\delta m_f = \rho_f \delta\tau_f$.

Complete porosity is entered by attitude of volume $\delta\tau_f$ of pores toward a volume $\delta\tau$:

$$m_0 = \delta\tau_f / \delta\tau = \delta\tau_f / (\delta\tau_g + \delta\tau_f)$$


Effective porosity [3-5] there is a relation $s = \delta\tau_f / \delta\tau_g$.

1^o. Sources, flows are contained in the volume of liquid $\delta\tau_f$.

Law of maintenance of mass taking into account by volume intensity J of flows and sources of liquid $\frac{d\delta m}{dt} = \delta m_f J$ we will present through the masses of soil and liquid (on a picture the elements of soil are drawn by a black):

$$\frac{d(\delta m_g + \delta m_f)}{dt} = \delta m_f J \tag{1}$$

Soil, a liquid flows through the pores of that, is immobile and mass of him is ^{permanent}
 $\delta m_g = \rho_g \delta\tau_g = const$. Therefore $\frac{d\delta m_g}{dt} = 0$.



Consequently, from equalization (1) for a liquid it will be

$$\frac{d\delta m_f}{dt} = \delta m_f J, \quad \frac{d\rho_f \delta\tau_f}{dt} = \rho_f \delta\tau_f J, \quad \rho_f \frac{d\delta\tau_f}{dt} + \delta\tau_f \frac{d\rho_f}{dt} = \rho_f \delta\tau_f J$$

For locomotive \mathbf{V} a formula takes place at a speed of liquid

$$\frac{d\delta\tau_f}{dt} = \delta\tau_f \operatorname{div} \mathbf{v}. \text{ Turns out } \rho_f \delta\tau_f \operatorname{div} \mathbf{v} + \delta\tau_f \frac{d\rho_f}{dt} = \rho_f \delta\tau_f J.$$

From where equalization of indissolubility flows out with the intensity of sources and flows, being in a liquid

$$\rho_f \operatorname{div} \mathbf{v} + \frac{d\rho_f}{dt} = \rho_f J$$

This equalization of indissolubility does not contain the coefficient of porosity, consequently, **does not coincide with equalizations of type**

$$\frac{\partial s\rho}{\partial t} + \operatorname{div} \rho \mathbf{v} = 0$$

2º. Sources and flows are contained in soil.

We have in this case

$$\begin{aligned} \frac{d\delta m}{dt} &= \delta m_g J, \quad \frac{d(\delta m_g + \delta m_g)}{dt} = \delta m_g J, \quad \frac{d\delta m_g}{dt} = 0, \\ \frac{d\delta m_f}{dt} &= \delta m_g J, \quad \delta\tau_f (\rho_f \operatorname{div} \mathbf{v} + \frac{d\rho_f}{dt}) = \rho_g \delta\tau_g J \end{aligned}$$

Attributing both parts to the volume $\delta\tau_{gr}$ and using the effective coefficient of porosity, we get common equalization of indissolubility

$$\frac{d\rho_f}{dt} + \rho_f \operatorname{div} \mathbf{v} = \frac{\rho_g J}{s}$$

For an incompressible liquid $\rho_f \operatorname{div} \mathbf{v} = \frac{\rho_g J}{s}$, $\operatorname{div} \mathbf{v} = \frac{\rho_g J}{s \rho_f}$.

Further passing to denotation $\rho_f \equiv \rho$, therefore $\operatorname{div} \mathbf{v} = \frac{\rho_g J}{s \rho}$.

2.Natural equation of filtration in the soil

We will appeal to equalization of dynamics of individual volume of continuous environment in tensions [13]:

$$\frac{d}{dt}(\mathbf{v} \rho \delta\tau) = \mathbf{F} \rho \delta\tau + \left(\frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z} \right) \delta\tau$$

In a volume $\delta\tau = \delta\tau_g + \delta\tau_f$ soil is immobile, mass force only on motion of liquid $\mathbf{F} \rho \delta\tau \Rightarrow \mathbf{F} \rho \delta\tau_f$, turns out therefore

$$\frac{d}{dt}[\mathbf{v} \rho (\delta\tau_g + \delta\tau_f)] = \mathbf{F} \rho \delta\tau_f + \left(\frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z} \right) \delta\tau$$

Soil is immobile $\frac{d}{dt}[\mathbf{v} \rho \delta\tau_g] = 0$. Equalization assumes an air

$$\rho \delta\tau_f \frac{d\mathbf{v}}{dt} + \mathbf{v} \frac{d\rho \delta\tau_f}{dt} = \mathbf{F} \rho \delta\tau_f + \left(\frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z} \right) \delta\tau,$$

$$\rho \delta\tau_f \frac{d\mathbf{v}}{dt} + \mathbf{v} \left(\delta\tau_f \frac{d\rho}{dt} + \rho \frac{d\delta\tau_f}{dt} \right) = \mathbf{F} \rho \delta\tau_f + \left(\frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z} \right) \delta\tau,$$

where $\frac{d\delta\tau_f}{dt} = \delta\tau_f \operatorname{div} \mathbf{v}$. Taking to $\delta\tau = \delta\tau_g + \delta\tau_f$, we get equalization of dynamics of liquid

(filtrations) in soil in a general view

$$\frac{\delta\tau_f}{\delta\tau} \left[\rho \frac{d\mathbf{v}}{dt} + \mathbf{v} \left(\frac{d\rho}{dt} + \rho \operatorname{div} \mathbf{v} \right) \right] = \mathbf{F} \rho \frac{\delta\tau_f}{\delta\tau} + \left(\frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z} \right),$$

In equalization complete porosity is included in **natural way** " m_0 ":

$$m_0 = \delta\tau_f / \delta\tau = \delta\tau_f / (\delta\tau_g + \delta\tau_f), \quad 0 \leq m_0 \leq 1,$$

$$m_0 \left[\rho \frac{d\mathbf{v}}{dt} + \mathbf{v} \left(\frac{d\rho}{dt} + \rho \operatorname{div} \mathbf{v} \right) \right] = m_0 \rho \mathbf{F} + \frac{\partial \mathbf{p}_x}{\partial x} + \frac{\partial \mathbf{p}_y}{\partial y} + \frac{\partial \mathbf{p}_z}{\partial z}$$

The particles of liquid at motion in soil test braking from contiguity with the particulate matters of soil, that increases force of friction considerably $\mathbf{F}_{mpi} = -\frac{k}{s}\mathbf{v}_i$, $s = \frac{\delta\tau_f}{\delta\tau_g}$ – coefficient of porosity.

(Blowing air or liquid through a millimeter-diameter tube requires a lot of effort compared to a centimeter-diameter tube.)

The theorem on the asymmetry of the stress tensor of a continuous medium, proved in [2-13], makes it possible to construct a wide spectrum of new rheological laws, from which it is possible to choose suitable models according to the flow velocity and the physical properties of the medium.

Let $u > 0$ and consider the frictional force proportional to the degree of velocity: $\mathbf{F}_{mp} = -\frac{k_u}{s}u^{m_u}\mathbf{i} - \frac{k_v}{s}v^{m_v}\mathbf{j} - \frac{k_w}{s}w^{m_w}\mathbf{k}$, whose projections on the x axis are equal to:

$$\mathbf{F}_1 = -\frac{k_u}{s}u_1^{m_u}\mathbf{i} \text{ on the plane } \mathcal{Y}_1, \text{ and } \mathbf{F}_2 = -\frac{k_u}{s}u_2^{m_u}\mathbf{i} \text{ on a plane } \mathcal{Y}_2.$$

The increases of force and speed appear between layers:

$$\delta\mathbf{F} = \mathbf{F}_2 - \mathbf{F}_1, \quad \delta\mathbf{F} = -\frac{k_{m_u}}{s}\delta u^{m_u}\mathbf{i}, \quad \delta u^{m_u} = u_2^{m_u} - u_1^{m_u} > 0,$$

thus $\delta\mathbf{F} \uparrow\downarrow \mathbf{i}$. The linear closeness of force is entered $\delta\mathbf{F}$ through a relation

$\mathbf{f} = \frac{\delta\mathbf{F}}{\delta y}$, $\delta\mathbf{F} = \delta y\mathbf{f}$. There is a vector on determination $\mathbf{p}_{yxcp} = \frac{\delta\mathbf{F}}{\delta x\delta z}$ tangent tension parallel and identically directed with forces of friction

$$\mathbf{p}_{yxcp} \uparrow\uparrow \delta\mathbf{F}, \quad \mathbf{p}_{yxcp} \uparrow\uparrow \mathbf{f}.$$

Through the coefficient of proportion we have equalities $\mathbf{f} = k'\mathbf{p}_{yxcp}$, $k' > 0$, $\mathbf{p}_{yxcp} \uparrow\downarrow \mathbf{i}$.

$$k'\mathbf{p}_{yxcp}\delta y = -\frac{k_{m_u}}{s}\delta u^{m_u}\mathbf{i}.$$

This expression is multiplied by a third \mathbf{i} :

$$k'\delta y\mathbf{p}_{yxcp} \cdot \mathbf{i} = -\frac{k_{m_u}}{s}\delta u^{m_u}\mathbf{i} \cdot \mathbf{i}.$$


As a result $k'\mathbf{p}_{yxcp} \cdot \mathbf{i} \delta y = k'|\mathbf{p}_{yxcp}| |\mathbf{i}| \delta y \cos 180^\circ = k' p_{yxcp} \cdot 1 \cdot \delta y \cdot (-1) = -k' p_{yxcp} \delta y$,

$$-\frac{k_{m_u}}{s}\delta u^{m_u}\mathbf{i} \cdot \mathbf{i} = -\frac{k_{m_u}}{s}\delta u^{m_u} |\mathbf{i}| |\mathbf{i}| \cos 0^\circ = -\frac{k_{m_u}}{s}\delta u^{m_u} \cdot 1 \cdot 1 \cdot 1 = -\frac{k_{m_u}}{s}\delta u^{m_u}$$

Equalities $-k'\delta y p_{yxcp} = -\frac{k_{m_u}}{s}\delta u^{m_u}$, $p_{yxcp} = \frac{k_{m_u}}{sk'} \frac{\delta u^{m_u}}{\delta y}$, in a limit give

tangent tension


$$p_{yx} = \lim_{\delta y \rightarrow 0} p_{yxcp}, \quad p_{yx} = \lim_{\delta y \rightarrow 0} \frac{k_{m_u}}{sk'} \frac{\delta u^{m_u}}{\delta y} = \frac{\mu_{m_u}}{s} \frac{\partial u^{m_u}}{\partial y}, \quad \mu_{m_u} = \frac{k_{m_u}}{k'}$$



Generalizations of the got formula by transpositions of lower indexes give corresponding tangent tensions

$$p_{xy} = \frac{\mu_{m_v}}{s} \frac{\partial V^{m_v}}{\partial x}, p_{xz} = \frac{\mu_{m_w}}{s} \frac{\partial W^{m_w}}{\partial x}, p_{zx} = \frac{\mu_{m_u}}{s} \frac{\partial U^{m_u}}{\partial z}, p_{yz} = \frac{\mu_{m_w}}{s} \frac{\partial W^{m_w}}{\partial y}, p_{zy} = \frac{\mu_{m_v}}{s} \frac{\partial V^{m_v}}{\partial z}$$

Formulas are shown out, for the sake of simplicity, for $u > 0, v > 0, w > 0$ and odd number indexes of degree $m = 1; 3; 5; 7; 9 \dots$. The same result turns out for an odd number m if $u \leq 0, v \leq 0, w \leq 0$.



If m - even and $u < 0, v < 0, w < 0$, force of friction is equal

$$\mathbf{F}_{mp} = \frac{k_u}{s} u^{m_u} \mathbf{i} + \frac{k_v}{s} v^{m_v} \mathbf{j} + \frac{k_w}{s} w^{m_w} \mathbf{k} \quad (\text{look a picture}), \text{ projections of that on an axis equal:}$$

$$\mathbf{F}_1 = \frac{k_u}{s} u_1^{m_u} \mathbf{i} \text{ on a plane } y_1 \text{ and } \mathbf{F}_2 = \frac{k_u}{s} u_2^{m_u} \mathbf{i} \text{ on a plane } y_2.$$

The increases of force and speed appear between layers:

$$\delta \mathbf{F} = \mathbf{F}_2 - \mathbf{F}_1, \quad \delta \mathbf{F} = \frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i}, \quad \delta u^{m_u} = u_2^{m_u} - u_1^{m_u} > 0, \text{ thus}$$

$\delta \mathbf{F} \uparrow\uparrow \mathbf{i}$. The linear closeness of force is entered $\delta \mathbf{F}$ as a relation

$$\mathbf{f} = \frac{\delta \mathbf{F}}{\delta y}, \quad \delta \mathbf{F} = \delta y \mathbf{f}. \quad \text{There is a vector of tangent tension on determination}$$

$$\mathbf{p}_{yxcp} = \frac{\delta \mathbf{F}}{\delta x \delta z} \quad \text{parallel and identically directed with forces of friction}$$

$$\mathbf{p}_{yxcp} \uparrow\uparrow \delta \mathbf{F}, \quad \mathbf{p}_{yxcp} \uparrow\uparrow \mathbf{f}.$$

The coefficient of proportion gives equalities $\mathbf{f} = k' \mathbf{p}_{yxcp}$, $k' > 0$, $\mathbf{p}_{yxcp} \uparrow\uparrow \mathbf{i}$,

$$k' \mathbf{p}_{yxcp} \delta y = \frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i}.$$

$$\text{This expression is multiplied by a thirl } \mathbf{i} : k' \delta y \mathbf{p}_{yxcp} \cdot \mathbf{i} = \frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i} \cdot \mathbf{i}.$$

$$\text{As a result } k' \mathbf{p}_{yxcp} \cdot \mathbf{i} \delta y = k' |\mathbf{p}_{yxcp}| |\mathbf{i}| \delta y \cos 0^\circ = k' p_{yxcp} \cdot 1 \cdot \delta y \cdot (1) = k' p_{yxcp} \delta y,$$

$$\frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i} \cdot \mathbf{i} = \frac{k_{m_u}}{S} \delta u^{m_u} |\mathbf{i}| |\mathbf{i}| \cdot \cos 0^\circ = \frac{k_{m_u}}{S} \delta u^{m_u} \cdot 1 \cdot 1 \cdot 1 = \frac{k_{m_u}}{S} \delta u^{m_u}$$

$$\text{Equalities } k' \delta y p_{yxcp} = \frac{k_{m_u}}{S} \delta u^{m_u}, \quad p_{yxcp} = \frac{k_{m_u}}{sk'} \frac{\delta u^{m_u}}{\delta y},$$

in a limit give tangent tension

$$p_{yx} = \lim_{\delta y \rightarrow 0} \frac{k_{m_u}}{k'} \frac{\delta u^{m_u}}{\delta y} = \mu_{m_u} \frac{\partial u^{m_u}}{\partial y}, \quad \mu_{m_u} = \frac{k_{m_u}}{k'}$$

Id est the same result turns out.

Conclusion of viscous constituents of normal tensions

The analogical reasoning is set the formula of constituent \mathbf{p}_{xx}^0 normal tension $\mathbf{p}_{xx} = -p \mathbf{i} + \mathbf{p}_{xx}^0$.

Let forces of friction be equal: $\mathbf{F}_1 = -\frac{k_u}{S} u_1^{m_u} \mathbf{i}$ on a planex₁ и $\mathbf{F}_2 = -\frac{k_u}{S} u_2^{m_u} \mathbf{i}$ on a plane


$$x_2 = x_1 + \delta x, \quad \delta \mathbf{F} = \mathbf{F}_2 - \mathbf{F}_1, \quad \delta \mathbf{F} = -\frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i}, \quad \delta u^{m_u} = u_2^{m_u} - u_1^{m_u} > 0, \text{ thus } \delta \mathbf{F} \uparrow\downarrow \mathbf{i}.$$

$$\text{The linear closeness of force is equal: } \mathbf{f} = \frac{\delta \mathbf{F}}{\delta x}, \quad \delta \mathbf{F} = \delta x \mathbf{f}.$$

There is a vector of normal viscous tension on determination

$$\mathbf{p}_{xxcp}^0 = \frac{\delta \mathbf{F}}{\delta y \delta z} \text{ parallel and identically directed with forces of friction } \mathbf{p}_{xxcp}^0 \uparrow\uparrow \delta \mathbf{F}, \mathbf{p}_{xxcp}^0 \uparrow\uparrow \mathbf{f}.$$

The coefficient of proportion results in equalities $\mathbf{f} = k'' \mathbf{p}_{xxcp}^0, k'' > 0,$



$$\text{This expression is multiplied by a third } \mathbf{i} : k' \delta x \mathbf{p}_{xxcp}^0 \cdot \mathbf{i} = -\frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i} \cdot \mathbf{i}.$$

$$\text{As a result } k' \mathbf{p}_{xxcp}^0 \cdot \mathbf{i} \delta x = k' |\mathbf{p}_{xxcp}^0| |\mathbf{i}| \delta x \cos 180^\circ = k' p_{xxcp}^0 \cdot 1 \cdot \delta x \cdot (-1) = -k' p_{xxcp}^0 \delta x,$$

$$\frac{k_{m_u}}{S} \delta u^{m_u} \mathbf{i} \cdot \mathbf{i} = -\frac{k_{m_u}}{S} \delta u^{m_u} |\mathbf{i}| |\mathbf{i}| \cos 0^\circ = -\frac{k_{m_u}}{S} \delta u^{m_u} \cdot 1 \cdot 1 \cdot 1 = -\frac{k_{m_u}}{S} \delta u^{m_u} \text{ Equalities}$$

$$-k' \delta x p_{xxcp}^0 = -\frac{k_{m_u}}{S} \delta u^{m_u}, \quad p_{xxcp}^0 = \frac{k_{m_u}}{sk''} \frac{\delta u^{m_u}}{\delta x},$$

in a limit give viscous member of normal tension

$$p_{xx}^o = \lim_{\delta x \rightarrow 0} \frac{k_{m_u}}{sk''} \frac{\delta u^{m_u}}{\delta x} = \frac{\mu_{m_u}}{s} \frac{\partial u^{m_u}}{\partial x}, \quad \mu_{m_u} = \frac{k_{m_u}}{k''} > 0$$

Generalizations of the got formula by transpositions of lower indexes give corresponding tensions

$$p_{yy}^o = \frac{\mu_{m_v}}{s} \frac{\partial v^{m_v}}{\partial y}, \quad p_{zz}^o = \frac{\mu_{m_w}}{s} \frac{\partial w^{m_w}}{\partial z}$$

Obviously, complete normal tensions are the sum of hydrodynamic pressure and viscous constituents

$$p_{xx} = -p + p_{xx}^o = -p + \frac{\mu_{m_u}}{s} \frac{\partial u^{m_u}}{\partial y}, \quad p_{yy} = -p + p_{yy}^o = -p + \frac{\mu_{m_v}}{s} \frac{\partial v^{m_v}}{\partial y},$$

$$p_{zz} = -p + p_{zz}^o = -p + \frac{\mu_{m_w}}{s} \frac{\partial w^{m_w}}{\partial z} \quad \text{Single values of indexes of degrees}$$

$m_u = 1, m_v = 1, m_w = 1$ correspond to the law of friction law of Newton.

All exponents must be odd integers [2]. The filtration equations for an incompressible fluid according to Newton's law of friction with coefficients of porosities in a gravity field have the form ($x_3 = z$):

$$m_0 [\rho \left(\frac{\partial v_i}{\partial t} + \sum_{j=1}^3 v_j \frac{\partial v_i}{\partial x_j} \right) + v_i \rho \operatorname{div} \mathbf{v}] + \frac{\partial}{\partial x_i} (p + m_0 \rho g z) = \frac{\mu}{s} \sum_{j=1}^3 \frac{\partial^2 v_i}{\partial x_j^2}, i = 1, 2, 3, \quad \text{relating to}$$

$\rho = \text{const}$ we find

$$m_0 \left[\frac{dv_i}{dt} + v_i \frac{\rho_g J}{s\rho} \right] = - \frac{\partial H}{\partial x_i} + \frac{\mu}{s\rho} \Delta v_i, i = 1, 2, 3, \quad H = \frac{p}{\rho} + m_0 g z$$

The equations in dimensionless variables (with strokes) with the effective porosity coefficient in the continuity equation:

$$\begin{aligned} m_0 \left[\frac{dv'_i}{dt'} + v'_i \frac{\rho_g JL}{s\rho U} \right] &= - \frac{\partial h'}{\partial x'_i} + \frac{\nu}{sUL} \Delta v'_i, i = 1, 2, 3, \\ \operatorname{div} \mathbf{v}' &= \frac{\rho_g JL}{s\rho U} \end{aligned} \quad (2)$$

Thus, the equations include the density ρ_g soil and porosity coefficients, which emphasizes their significant effect on filtration.

Dimensionless numbers are formed:

$$m_0 \left[\frac{dv'_i}{dt'} + v'_i Ds \right] = - \frac{\partial h'}{\partial x'_i} + \frac{1}{sRe} \Delta v'_i, i = 1, 2, 3, \quad \operatorname{div} \mathbf{v}' = Ds,$$

$$Ds = \frac{\rho_g JL}{s\rho U}, \quad Re = \frac{UL}{\nu} - \text{Reynolds number.}$$

For sources and drains contained in liquid $Ds = \frac{JL}{U}$. Here a new dimensionless number is given the name Darcy.

3. Modeling filtering equations with Newton's law of friction

In the well height 1000m and wide 100m with an impenetrable wall accumulated 200m layer of water that displaces soil through the 800m layer of soil so that at the same time at the input upper boundary $y = 1000m$ the water velocity is equal to 0.01m / s. The lower boundary of the soil, $y = 0$, is permeable to liquid. Filtration scales taken: cavity width $L = 100m$, water entry rate through the upper limit $U = 0.001$ m / s, water density $\rho_w = 1000 \text{ kg/m}^3$. Oil density

$\rho_o = 880 \text{ kg/m}^3$, kinematic viscosity of water $\nu_w = 0.00556 \cdot 10^{-4} \text{ m}^2/\text{s}$, oil kinematic viscosity $\nu_o = 22.6 \cdot 10^{-6} \text{ m}^2/\text{s}$, effective soil porosity $s = 10^{-4}$, total porosity $m_0 = 10^{-5}$. Power drain in the ground is such that $Ds = -0.05$. Generalized density

$\rho = \alpha_e \rho_e + \alpha_h \rho_h$ and kinematic viscosity of the medium $\nu = \alpha_e \nu_e + \alpha_h \nu_h$, $\alpha_e + \alpha_h = 1$ calculated by the equation of transfer of water concentration [8]: $\frac{\partial \alpha_e}{\partial t} + \mathbf{v} \cdot \nabla \alpha_e = 0$.

Dimensionless generalized density:

$$\rho' = \alpha_e + \alpha_h \rho_h / \rho_e, \quad \frac{\partial \alpha_e}{\partial t'} + \mathbf{v}' \cdot \nabla \alpha_e = 0$$

The difference grid 100x200, a dimensionless time step, satisfies the condition of counting stability according to a semi-implicit five-point scheme without "circuit diffusion".

Before the ground in the area from 800m to 1000m the numerical calculation was carried out using the dimensionless Navier equations

$$\rho' \frac{d\mathbf{v}'_i}{dt'} = -\frac{\partial h'}{\partial x'_i} + \frac{1}{Re_e} \Delta \mathbf{v}'_i, \quad i = 1, 2, 3, \quad \operatorname{div} \mathbf{v}' = 0$$

There is oil in the ground. Also used were the Navier equations, but with porosity coefficients:

$$\rho' m_0 \left(\frac{d\mathbf{v}'_i}{dt'} + \mathbf{v}'_i Ds \right) = -\frac{\partial h'}{\partial x'_i} + \frac{1}{s Re} \Delta \mathbf{v}'_i, \quad i = 1, 2, 3, \quad \operatorname{div} \mathbf{v}' = Ds$$

The location of water and oil at the initial moment of time is reflected in figure 1. Sticking conditions are set at the lateral boundaries of the well $\mathbf{v}' = 0$, at the output boundary $y = 0$, the vertical derivatives of the velocity components are considered equal to 0. The water entering through the upper boundary $y = 1000m$ begins to displace oil, the diagrams of the velocity vector fields in the cavity are shown in fig.2-4. The parabolic distribution of the velocity vector across the width of the channel in the ground can be seen in fig.2-4. Separately, fig. 5 shows a parabolic vertical velocity profile in one of the soil sections. The nonphysicality of this flow in the ground is evident from the pictures of the velocity vector fields, which is the content of the output: the Navier equations (the old name is Navier-Stokes) are not a filtration model




Fig.1

Fig.2

Fig.3 Fig.4

Fig..5

4.Filtration modeling by power friction equations




Fig.6 Fig.7 Fig.8

In this case, the dynamics of water over the ground is modeled by the equations of Jakupov's power laws of friction:

$$\rho \frac{dv_i}{dt} = -\frac{\partial p}{\partial x_i} + \sum_{j=1}^3 \frac{\partial}{\partial x_j} \left(\frac{\alpha \mu}{m_i^{m_i-1}} \frac{\partial v_i^{m_i}}{\partial x_j} \right) + \rho F_i, i=1,2,3, \operatorname{div} \mathbf{v} = 0$$

This continuity equation corresponds to the fact that there are no sources and sinks in the flow of water.

Equations in dimensionless variables have the form

$$\rho' \frac{dv'_i}{dt'} = -\frac{\partial h'}{\partial x'_i} + \sum_{j=1}^3 \frac{1}{\operatorname{Re}} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_i} \right)^{m_i-1} m_i v_i^{m_i-1} \frac{\partial v'_i}{\partial x'_j} \right], i=1,2,3, \operatorname{div} \mathbf{v}' = 0, \alpha = 1 \frac{c \kappa}{m}$$

The exponents are determined in intervals [13-14]:

$$|v_i| < 1/9 \quad m_i = 1; \quad 1/9 \leq |v_i| < 3/9 \quad m_i = 3; \quad (3)$$

$$3/9 \leq |v_i| < 5/9 \quad m_i = 5; \quad 5/9 \leq |v_i| < 7/9 \quad m_i = 7; \quad 7/9 \leq |v_i| \quad m_i = 9$$

The enormous resistance to movement (leakage) of a liquid in the soil is taken into account in the mass conservation equation and in the power law equations using the effective filtration coefficient s:

$$\rho' m_0 \left(\frac{dv'_i}{dt'} + v'_i Ds \right) = -\frac{\partial h'}{\partial x'_i} + \sum_{j=1}^3 \frac{1}{s \operatorname{Re}} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_i} \right)^{m_i-1} m_i v_i^{m_i-1} \frac{\partial v'_i}{\partial x'_j} \right], i=1,2,3,$$

$$\operatorname{div} \mathbf{v}' = Ds, \quad Ds = \frac{\rho_g J L}{s \rho U}$$

Initially, the determination of the degrees in the ground was carried out according to the distribution (3).

The computed velocity fields in FIG. 6 and 7 show the unsuitability of this velocity distribution in the ground. In the ground, the equations of the vertical velocity proved to be effective as a constant exponent

$$m_i = 17, i = 1, 2, 3 :$$

$$\rho' m_0 \left(\frac{dv'}{dt'} + v'_i D s \right) = - \frac{\partial h'}{\partial x'_i} + \sum_{j=1}^3 \frac{1}{s \operatorname{Re}} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{17} \right)^{16} 17 v'^{16}_i \frac{\partial v'_i}{\partial x'_j} \right], i = 1, 2, 3,$$

$$\operatorname{div} \mathbf{v}' = D s \quad (4)$$




Fig.9 Fig.10

Fig.11

Fig.8 shows the field of the vector of water flow rates simply in the channel without soil, without sources-effluents, calculated according to the power law (2) and (4).

On fig. 9 and 10 show the velocity vector fields at different points in time. The difference from the parabolic velocity fields obtained by the Navier equations (-Stok's) is simply amazing !!! Fig. 11 represents the vertical velocity distribution v the height of the channel in the cross section $x = 50$ m.

On fig. 12 shows the trapezoidal profile of the vertical velocity v in the horizontal plane of the water $y = 900m$, on fig. 13 in the horizontal plane of the soil $y = 400m$.

In the ground, the speed of the filtration fluid is significantly reduced, as can be seen on fig. 9, 10, 11.




Fig.12

Fig.13

5. Filtration (drainage) under the action of gravity

Above are the results of calculations of forced filtration, when the upper limit of the channel $y=1000m$ water is supplied at a speed of $0.001 m/s$.

In this paragraph, the numerical calculations of liquid filtration (drainage) under the influence of gravity, which acts on water from 800m to 1000m (the number of Froude is equal to $Fr=U^2/(gL)$), in the soil the effect of gravity is taken into account by the coefficient of total porosity " $m_0 = 0.00001$ ". In addition to the above scale, the scale of the speed adopted $U = 0.01\sqrt{gL}$, $g=9.81m/c^2$.

Before the ground $800m \leq y \leq 1000m$ the equations with the Froude number are applied (for the above reasons):

$$\rho' \frac{du'}{dt'} = -\frac{\partial p'}{\partial x'_i} + \sum_{j=1}^2 \frac{1}{Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_u} \right)^{m_u-1} m_u u'^{m_u-1} \frac{\partial u'}{\partial x'_j} \right],$$


$$\rho' \frac{dv'}{dt'} = -\frac{\partial p'}{\partial x'_2} + \sum_{j=1}^2 \frac{1}{Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_v} \right)^{m_v-1} m_v v'^{m_v-1} \frac{\partial v'}{\partial x'_j} \right] - \frac{\rho'}{Fr}, \text{div}'w' = 0, \alpha = 1 \frac{csek}{m}$$

In the ground, equations with a constant exponent are applied $m_i = 17, i = 1, 2, 3$ and with a total porosity coefficient are applied:

$$m_0 \rho' \left(\frac{du'}{dt'} + u' D_s \right) = -\frac{\partial p'}{\partial x'_1} + \sum_{j=1}^2 \frac{1}{s Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{17} \right)^{16} \cdot 17 \cdot u'^{16} \frac{\partial u'}{\partial x'_j} \right],$$

$$m_0 \rho' \left(\frac{dv'}{dt'} + v' D_s \right) = -\frac{\partial p'}{\partial x'_2} + \sum_{j=1}^2 \frac{1}{s Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{17} \right)^{16} \cdot 17 \cdot v'^{16} \frac{\partial v'}{\partial x'_j} \right] - \frac{\rho' m_0}{Fr}, \text{div}'w' = D_s$$

Fig.14 and 15 are the fields of the velocity vector at different times of oil displacement by water. Fig. 16 represents the distribution of the vertical velocity v along the height of the channel in the cross section $x=50$ m. the Difference between the distributions of the vertical velocities in Fig. 11 and Fig.16 the obvious.



6. Displacement of oil by water from underground volume

Before the ground in the water are applied (for the above reasons) equations with the number of Froude:

$$\rho' \frac{du'}{dt'} = -\frac{\partial p'}{\partial x'_i} + \sum_{j=1}^2 \frac{1}{Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_u} \right)^{m_u-1} m_u u^{m_u-1} \frac{\partial u'}{\partial x'_j} \right],$$

$$\rho' \frac{dv'}{dt'} = -\frac{\partial p'}{\partial x'_2} + \sum_{j=1}^2 \frac{1}{Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{m_v} \right)^{m_v-1} m_v v^{m_v-1} \frac{\partial v'}{\partial x'_j} \right] - \frac{\rho'}{Fr}, \quad div \mathbf{w}' = 0, \quad \alpha = 1 \frac{cek}{m}$$

Water is supplied to the well at a rate $U=2m / s$ (figures.17). In linear scale taken as the diameter of the borehole $L=1 m$. the Reynolds Number is equal to $Re=\alpha_e Re_e + \alpha_h Re_h$, where Re_e - Reynolds number for water, Re_h - Reynolds number for oil. In the ground, equations with a constant exponent are applied $m_u = 11$, $m_v = 11$ and with the ratio of **total porosity** $m_0 = 0.000021$:

$$\rho' m_0 \left(\frac{du'}{dt'} + u' D_s \right) = -\frac{\partial p'}{\partial x'_1} + \sum_{j=1}^2 \frac{1}{s Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{11} \right)^{10} \cdot 11 \cdot u'^{10} \frac{\partial u'}{\partial x'_j} \right],$$

$$\rho' m_0 \left(\frac{dv'}{dt'} + v' D_s \right) = -\frac{\partial p'}{\partial x'_2} + \sum_{j=1}^2 \frac{1}{s Re} \frac{\partial}{\partial x'_j} \left[\left(\frac{\alpha U}{11} \right)^{10} \cdot 11 \cdot v'^{10} \frac{\partial v'}{\partial x'_j} \right] - \frac{m_0 \rho'}{Fr}, \quad div \mathbf{v}' = D_s$$




Fig.17




Fig.18




Fig.19




Fig.20




Fig.21




Fig.22




Fig.23




Fig.24

Fig.25

Fig.18-22 the pictures of water penetration into the soil with simultaneous oil displacement through 2 vertical pits $0 < x' < 1$ and $6 < x' < 7$ are presented. Fig.23 the field of the velocity vector and the location of water at almost complete displacement of oil obtained by the equations of "Darcy's law" are presented. Horizontal and vertical arrangement of velocity vectors $\mathbf{v}' = u' \mathbf{i} + v' \mathbf{j}$ fig.23 caused by neglect of the forces of inertia (acceleration) in the equations of "Darcy's law". The influence of the inertia forces to the filter demonstrated with paintings of fields of velocity vectors in Fig. 18-22.

Fig.24 and 25 shows a plot of the vertical velocity at the height of the wells

REFERENCES

- [1] Jakupov K.B. COMPILATIVITY OF THE "DARCY LAW" IN THE THEORY OF FILTRATION // News of the National Academy of Sciences of Kazakhstan, Ser. Phys. Mat., 6 (316) 2017. P.115-131. ISSN 2518-1726 (Online) ISSN 1991-346X (Print)
- [2] Jakupov K.B. GENEALOGY OF THE STOCK AND NAVIER EQUATIONS. POWERED RHEOLOGICAL LAWS AND EQUATIONS // News of the National Academy of Sciences of Kazakhstan, ser. Phys.-Math., 3 (313) 2017. C.64-81. ISSN 2518-1726 (Online) ISSN 1991-346X (Print)
- [3] Basniev V.S., Kochina I.N., Maksimov V.M. Underground fluid mechanics. M.: Nedra, 1993. 416s.
- [4] Ponomareva I.N., Mordvinov V.A. UNDERGROUND HYDROMECHANICS. -Perm 2009
- [5] Polubarinova-Kochina P.Ya. Theory of groundwater movement. -M.: Publishing House "Science", 1977. P.664.
- [6] H.Darcy. Les fontaines publiques de la ville de Dijon. Paris, 1856.
- [7] Loitsyansky L.G. Fluid and gas mechanics. -M.: "Science", 1973.
- [8] Aravin V.I. and Numerov S.N. Theory of motion of liquids and gases in non-deformable porous medium. M.: Gostekhizdat. 1953 P.616.
- [9] Nied D.A., Bejan A. Convection in Porous Media. N. Y. etc: Springer, 1992. 408p. [ten].
- [10] Numerov S.N. On the need to take into account the forces of inertia in the basic equations of the theory filtering // In Sat: Vopr. applied mathematics and geometric modeling. Leningrad Ing. -p. in-t, 1968, p.18-21.
- [11] C.W.Hirt and B.D.Nichols. Volume of fluid (VOF) method boundaries // J.Comput.Phys., 1981, Vol.39, pp.201-225.
- [12] Jakupov K.B. REPRESENTATIVITY OF THE METHOD OF FICTIVE AREAS IN HYDRODYNAMICS // News of the National Academy of Sciences of Kazakhstan, Phys. Mat, 6 (316) 2017. Pp.85-96. ISSN 2518-1726 (Online) ISSN 1991-346X (Print).
- [13] Jakupov K.B. LIQUIDATION OF FALSIFICATIONS and MODERNIZATION OF THE BASES OF CONTINUOUS MECHANICS.-Almaty: "UlymOrdasy" Printing House, 2017.P.435. ISBN 978-601-280-859-9.
- [14] Jakupov K.B. RHEOLOGICAL LAWS OF VISCOUS FLUID DYNAMICS // Proceedings of the National Academy of Sciences of the Republic of Kazakhstan, main body-mat, 1 (293), 2014, pp. 51-55. ISSN 1991-346X.
- [15] Jakupov K.B. . Simulation of thermobarodiffusions with chemical reactions in liquids and gases // Proceedings of the National Academy of Sciences of Kazakhstan, series physical-mathematical., 6 (310), 2016, pp. 80-88. ISSN 2518-1726.ISSN 1991-346X.

DOI <https://doi.org/10.32014/2018.2518-1726>

К. Б. Жақып-тегі

ҚР БФМ Математика және математикалық моделдеу институты, Алматы, Қазақстан

**СҮЗГІНІЦ ТАБИГАТТЫҚ ТЕНДЕУЛЕРІ.
«Дарси ЗАҢЫНЫҢ» ҚҰРЫҒАНЫ**

Аннотация. Сүзгінің табигаттық тендеулерінің теориясы корытлған. Жаңа тендеу- лердің табигаттығы мынада тұр: олар физиканың негізгі заңдарынан шыққан нақты сал- дары, грунттың тығыздығын және кеуектілігін, сұзбелі сұйықтықтың тұтқырлығы мен тығыздығын, дренажды, аурылық күштің әсерін тікелей есепке алғандығы. Сүзгі теория- сында пайдаланатын үзіліссіздік тендеуіндің жалғандығы көрсетілген. Сүзгінің жаңа тен- деулері тұтас ортаның динамикасының керенеулер арқылы жазылған тендеулерінен шыға-рылған, олрадын құрылышына сұйықтықтың тұтқырлығы мен тығыздығы жәнегрунтың кеуектілігі енгізілген.. Сүзгінің модельдеуге Ньютоның үйкеліс заңына сәйкес құрылған тендеулерді пайдаланудың жәрәмсіздігі көрсетілген. Сүзгінің модельдеуге автордың дәрежелі үйкеліс заңдарына дәрежесі дақ сандар болған тендеулерін пайдалану жәрәмді екені сандық турде әшкереленген. Осыларды жұмысап скважинадағы сүзгі, ауырлық күш- пен болатын дренажды, жердің астындағы қоймадан мұнайды еki беттескен шурфтар арқылы сығып шығару сандық есептермен орындалған. Библ.18.

Тірек сөздер: сүзгі, қысым, жылдамдық, үдеу.

К.Б.Джакупов

Казахский Национальный Университет им.Аль-Фараби

УРАВНЕНИЯ ЕСТЕСТВЕННОЙ ФИЛЬТРАЦИИ. ФИАСКО "ЗАКОНА ДАРСИ"

Аннотация. Дано теория натуральных уравнений фильтраций. Натуральность новых уравнений фильтраций заключается в том, что они являются точными следствиями фундаментальных законов физики, прямо учитывают плотность и пористость грунта, вязкость и плотность фильтрационной жидкости, дренаж, влияние силы тяжести и др. Установлена фальшивость традиционного уравнения неразрывности в теории фильтрации. Из уравнения динамики сплошной среды в напряжениях выводятся новые уравнения фильтрации, включающие плотность и вязкость жидкости и пористость грунта. Установлено неадекватность моделирования фильтрации уравнениями с законом трения Ньютона. Численно подтверждена эффективность моделирования фильтрации уравнениями Джакупова, основанных на степенных законах трения с нечетными показателями степеней, с применением которых проведены расчеты фильтрации в скважине, дренажа под действием силы тяжести, вытеснения нефти водою из подземного ареала через две симметрично расположенные шурфы.

Ключевые слова: фильтрация, давление, скорость, ускорение, уравнения.

About the author:

Dzhakupov Kenes Baikenovich - doctor of physico-mathematical Sciences, Professor, academician Office address: RSE Institute of mathematics and mathematical modeling KM MES RK, 050010, Pushkin street, 125, Almaty, Kazakhstan. E-mail: jakupovKB@mail.ru

МАЗМУНЫ

<i>Асқарова А.С., Бөлекенова С.Ә., Шафаржык П., Бөлекенова С.Ә., Максимов В.Ю., Бекетаева М.Т., Нұғманова А.О.</i> Қазандықтардың жану камераларында шантектес көмірдің жану процестерінің заманауи компьютерлік тәжірибелері....	5
<i>Насурла Маулен, Бұртебаев Н., Керимкулов Ж. К., Сузуки Т., Сакута С. Б., Насурла Маржсан, Ходжаев Р.</i> Энергисы 14.5 МэВ дейтрондардың ^7Li ядроларынан шашырауын зерттеу.....	15
<i>Макаренко Н.Г., Чойонг-беком, Есеналиева А.Б.</i> Текстураларды тану үшін риманметрикасы.....	23
<i>Дауылбаев М.Қ., Атахан Н., Мирзакурова А.Е.</i> Жоғарғы ретті сингулярлы ауытқыған интегралды- дифференциалдық теңдеу үшін жалпыланған бастапқы секірісті шеттік есебі шешімінің асимптотикалық жіктелуі.....	28
<i>Жұматов С.С.</i> Автономды емес негізгі басқару жүйелерінің бағдарламалық көпбейнесінің абсолют орнықтылығы	37
<i>Амангельдиева А., Қайратқызы Д., Қонысбаев Т.</i> Қараңғы материя үшін бейстационар күй параметрі.....	44
<i>Бадаев С.А., Калмурзаев Б.С., Кабылжанова Д.К., Абешев К.Ш.</i> Универсал позитив жарты реттер.....	49
<i>Жақып-тегі К. Б.</i> Сұзгінің табигаттық теңдеулері. «Дарси заңының» құрығаны.....	54

СОДЕРЖАНИЕ

<i>Аскарова А.С., Болегенова С.А., Шафаржик П., Болегенова С.А., Максимов В.Ю., Бекетаева М.Т., Нугманова А.О.</i>	
Современные компьютерные эксперименты процессов сжигания угольной пыли в топочных камерах котлов.....	5
<i>Насурлла Маулен, Буртебаев Н., Керимкулов Ж. К., Сузуки Т., Сакута С. Б., Насурлла Маржсан, Ходжаев Р.</i>	
Исследование рассеяния дейтеронов на ядрах ^7Li при энергии 14.5 МэВ.....	15
<i>Макаренко Н.Г., Чойонг-беом, Есеналиева А.Б. Риманова метрика для распознавания текстур.....</i>	23
<i>Дауылбаев М.К., Атахан Н., Мирзакулова А.Е. Асимптотическое разложение решения общей краевой задачи с начальными скачками для высшего порядка сингулярно возмущенное интегро-дифференциальное уравнение.....</i>	28
<i>Жуматов С.С. Абсолютная устойчивость программного многообразия неавтономных основных систем управления.....</i>	37
<i>Амангельдиева А., Кайраткызы Д., Конысбаев Т. О нестационарном параметре состояния темной материи.....</i>	44
<i>Бадаев С.А., Калмурзаев Б.С., Кабылжанова Д.К., Абешев К.Ш. Универсальные позитивные предпорядки.....</i>	49
<i>Жакупов К. Б. Уравнения естественной фильтрации. Фиаско "закона Дарси".....</i>	54

CONTENTS

<i>Askarova A.S., Bolegenova S.A., Safarik P., Bolegenova S.A., Maximov V.Yu., Beketayeva M.T., Nugymanova A.O.</i>	
Modern computing experiments on pulverized coal combustion processes in boiler furnaces.....	5
<i>Nassurlla Maulen, Burtebayev N., Kerimkulov Zh.K., Suzuki T., Sakuta S.B., Nassurlla Marzhan, Khojayev R.</i>	
Investigation of deuteron scattering BY ^7Li nuclei at energy of 14.5 MeV	15
<i>Makarenko N.G., ChoYong-beom, Yessenaliyeva A.B.</i> Riemannian metric for texture recognition.....	23
<i>Dauylbayev M.K., Atakhan N., Mirzakulova A.E.</i> Asymptotic expansion of solution of general bvp with initial jumps for higher-ordersingularly perturbed integro-differential equation.....	28
<i>Zhumatov S.S.</i> Absolute stability of a program manifold of non-autonomous basic control systems	37
<i>Amangeldyieva A., Kairatkzy D., Konysbayev T.</i> On the nonstationary parameter of state for dark matter.....	44
<i>Badaev S.A., Kalmurzayev B.S., Kabylzhanova D.K., Abeshev K.Sh.</i> Universal positive preorders.....	49
<i>Jakupov K. B.</i> Natural filtration equations. Fiasco“ of Darcy's LAW”.....	54

**Publication Ethics and Publication Malpractice
in the journals of the National Academy of Sciences of the Republic of Kazakhstan**

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайтах:

[www:nauka-nanrk.kz](http://www.nauka-nanrk.kz)

<http://www.physics-mathematics.kz>

ISSN 2518-1726 (Online), ISSN 1991-346X (Print)

Редакторы М. С. Ахметова, Т.А. Апендиев, Д.С. Аленов
Верстка на компьютере А.М. Кульгинбаевой

Подписано в печать 05.12.2018.
Формат 60x881/8. Бумага офсетная. Печать – ризограф.
4,75 пл. Тираж 300. Заказ 6.

Национальная академия наук РК
050010, Алматы, ул. Шевченко, 28, т. 272-13-18, 272-13-19